

## 半柔性太阳能电池板电性参数

Solar cell (电池片)	单晶硅
Maximum power (Wp) (最大功率)	<b>6wp</b>
Maximum power voltage (V) (最大工作电压)	6v
Maximum power current (A) (最大工作电流)	1a
Open circuit voltage (V) (开路电压)	7.2v
Short circuit current (A) (开路电流)	1.1a
Size of module (mm) (太阳能板的尺寸)	275*170 mm
Maximum system voltage (V) (最大系统电压)	600
Temperature coefficients of Isc (%) (短路电流的温度系数)	0.065+/-0.015%/°C
Temperature coefficients of Voc (%) (开路电压的温度系数)	- (2.23+/-0.1) mv/ °C
Temperature coefficients of Pm (%) (最大功率的温度系数)	- (0.5+/-0.05) / °C
Temperature coefficients of Im (%) (最大电流的温度系数)	+0.1/ °C
Temperature coefficients of Vm (%) (最大电压的温度系数)	-0.38/ °C
Temperature Range (工作温度范围)	-40°C ~ +85°C
Tolerance Wattage (e.g. +/-5%) (功率的公差)	+/-5%
Surface Maximum Load Capacity (太阳能板表面可以承受的最大压力)	15m/s(100kg/sq.m)
Allowable Hail Load (冰雹压力测试)	steel ball fall down from 1m height
Weight per piece (kg) (每块太阳能板的重量)	300g
Aangle of greatest flexion (最大弯曲角度)	30°
Length of Cables (mm) (连接线长度)	-
Cell Efficiency (%) (电池效率)	20%
Output tolerance (%) (输出功率公差)	+/-5%
Frame (Material, Corners, etc.) (边框材料)	Anodized Aluminum Alloy
Standard Test Conditions (标准测试条件)	AM1.5 100mW/C m² 25°C
Warranty (产品质量保证)	5 years product warranty and 25 years 80% of power
FF (%) (填充因子)	75%
Packing (包装)	carton (硬纸盒, 纸板箱)

