

# Type-Directed TDD in Rust

## A case study using FizzBuzz

Franklin Chen

<http://franklinchen.com/>

July 21, 2014  
Pittsburgh Code and Supply

# Outline

- 1 Introduction
- 2 Original FizzBuzz problem
- 3 FizzBuzz 2: user configuration
- 4 FizzBuzz 3: FizzBuzzPop and beyond
- 5 Parallel FizzBuzz
- 6 Conclusion

# Outline

- 1 Introduction
- 2 Original FizzBuzz problem
- 3 FizzBuzz 2: user configuration
- 4 FizzBuzz 3: FizzBuzzPop and beyond
- 5 Parallel FizzBuzz
- 6 Conclusion

# Goals of this presentation

- Give a taste of a **practical** software development **process** that is:
  - ▶ **test**-driven
  - ▶ **type**-directed
- Show everything for real (using Rust):
  - ▶ project build process
  - ▶ testing frameworks
  - ▶ all the code
- Use FizzBuzz because:
  - ▶ problem: easy to understand
  - ▶ modifications: easy to understand
  - ▶ fun!
- Encourage you to explore a modern typed language; now is the time!
  - ▶ Recently, Apple ditched Objective C for its new language **Swift!**



# Test-driven development (TDD)

- Think.
- Write a test that **fails**.
- Write code until test **succeeds**.
- Repeat, and **refactor** as needed.

Is TDD dead?

Short answer: No.

# Type systems

## What is a type system?

A **syntactic** method to **prove** that bad things can't happen.

## "Debating" types "versus" tests?

- Let's use both types and tests!
- But: use a **good** type system, not a bad one.

## Some decent practical typed languages

- OCaml: 20 years old
- Haskell: 20 years old
- Scala: 10 years old
- Swift: < 2 months old
- Rust (still not at 1.0!)

# Outline

- 1 Introduction
- 2 Original FizzBuzz problem
- 3 FizzBuzz 2: user configuration
- 4 FizzBuzz 3: FizzBuzzPop and beyond
- 5 Parallel FizzBuzz
- 6 Conclusion

# Original FizzBuzz problem

## FizzBuzz defined

Write a program that prints the numbers from 1 to 100.

But for multiples of three, print “Fizz” instead of the number.

And for the multiples of five, print “Buzz”.

For numbers which are multiples of both three and five, print “FizzBuzz”.

## Starter code: main driver



Rust: a modern systems programming language for efficiency and safety in time, space, and concurrency.

```
fn main() {  
    // Will not compile yet!  
    for result in run_to_seq(1i, 100).iter() {  
        println!("{}", result)  
    }  
}
```

- Type-directed design: separate out effects (such as printing to terminal) from the real work.
- Type-directed feedback: compilation fails when something is not implemented yet.

# Compiling and testing with Cargo



Cargo: build tool for Rust

## Features

- Library dependency tracking.
- cargo build
- cargo test

My wish list, based on Scala SBT

- Triggered compilation and testing
- Interactive REPL

# First compilation failure

src/main.rs:

```
$ cargo build  
src/main.rs:16:19:  
error: unresolved name 'run_to_seq'
```

## Write type-directed stub

```
fn main() {  
    for result in run_to_seq(1i, 100).iter() {  
        println!("{}", result)  
    }  
}  
  
fn run_to_seq(start: int, end: int) -> Vec<String> {  
    fail!()  
}
```

## Write wanted type signature

fail! is convenient for stubbing.

- In Rust standard library
- Causes whole task to fail

## Write acceptance test (simplified)

```
#[test]
fn test_1_to_16() {
    let expected = vec![
        "1", "2", "Fizz", "4", "Buzz", "Fizz",
        "7", "8", "Fizz", "Buzz", "11", "Fizz",
        "13", "14", "FizzBuzz", "16",
    ]
    .iter()
    .map(|&s| s.to_string())
    .collect();
    assert_eq!(run_to_seq(1, 16), expected)
}
```

## Test passes type check, but fails


```
$ cargo test  
task 'test::test_1_to_16' failed at 'write run_to_seq',  
...src/main.rs:37
```

# Outside-in: for a fizzbuzz module

Types are shapes to assemble logically.

```
fn run_to_seq(start: int, end: int) -> Vec<String> {  
    range_inclusive(start, end)  
        .map(fizzbuzz::evaluate)  
        .collect()  
}
```

- `range`(include, exclude) returns an `iterator`.
- `map` takes an iterator of one type to an iterator of another:



- Therefore: need to implement function  
`fizzbuzz::evaluate: int -> String.`

# Implement new fizzbuzz module

A failing acceptance test drives **discovery** of

- A **unit**, fizzbuzz
- A function with a particular type, **int** → **String**

```
pub fn evaluate(i: int) -> String {  
    fail!()  
}
```

**Types** are better than **comments** as **documentation!**

Comments are not checkable, unlike types and tests.

## First part of **unit test**: example-based

Manually write some **examples**.

```
#[test] fn test_15() {  
    assert_eq!(evaluate(15), "FizzBuzz".to_string())  
}  
  
#[test] fn test_20() {  
    assert_eq!(evaluate(20), "Buzz".to_string())  
}  
  
#[test] fn test_6() {  
    assert_eq!(evaluate(6), "Fizz".to_string())  
}  
  
#[test] fn test_17() {  
    assert_eq!(evaluate(17), "17".to_string())  
}
```

# The joy of property-based tests

QuickCheck for Rust: a framework for writing **property-based** tests.

```
#[quickcheck]
fn multiple_of_both_3_and_5(i: int) -> TestResult {
    if i % 3 == 0 && i % 5 == 0 {
        TestResult::from_bool(evaluate(i) ==
                               "FizzBuzz".to_string())
    } else {
        TestResult::discard()
    }
}
```

## Winning features

- Auto-generates **random** tests for each property (100 by default).
- **Type-driven**: here, generates random **int** values.

## Property-based tests (continued)

```
#[quickcheck]
```

```
fn multiple_of_only_3(i: int) -> TestResult {  
    if i % 3 == 0 && i % 5 != 0 {  
        TestResult::from_bool(evaluate(i) == "Fizz".to_string())  
    } else {  
        TestResult::discard()  
    }  
}
```

```
#[quickcheck]
```

```
fn not_multiple_of_3_and_5(i: int) -> TestResult {  
    if i % 3 != 0 && i % 5 != 0 {  
        TestResult::from_bool(evaluate(i) == i.to_string())  
    } else {  
        TestResult::discard()  
    }  
}
```


# A buggy and ugly solution

```
// Buggy and ugly!
if i % 3 == 0 {
    "Fizz".to_string()
} else if i % 5 == 0 {
    "Buzz".to_string()
} else if i % 3 == 0 && i % 5 == 0 {
    "FizzBuzz".to_string()
} else {
    i.to_string()
}
```

```
$ cargo test
task 'fizzbuzz::test::test_15' failed at
  assertion failed: `!(left == right) && !(right == left)`
  (left: 'Fizz', right: 'FizzBuzz'), .../src/fizzbuzz.rs:21
```

# Booleans are evil!

Maze of twisty little conditionals, all different



- Too easy to write incorrect sequences of nested, combined conditionals.
- Overuse of Booleans is a type **smell**.

# Pattern matching organizes information

```
pub fn evaluate(i: int) -> String {  
    match (i % 3 == 0, i % 5 == 0) {  
        (true, false) => "Fizz".to_string(),  
        (false, true)  => "Buzz".to_string(),  
        (true, true)   => "FizzBuzz".to_string(),  
        (false, false) => i.to_string(),  
    }  
}
```

## Winning features

- Visual **beauty** and clarity.
- No duplicated conditionals.
- No ordering dependency.
- Type checker verifies **full coverage** of cases.

## Example of non-exhaustive pattern matching

```
pub fn evaluate(i: int) -> String {  
    match (i % 3 == 0, i % 5 == 0) {  
        (true, false) => "Fizz".to_string(),  
        (false, true) => "Buzz".to_string(),  
        (true, true) => "FizzBuzz".to_string(),  
        // (false, false) => i.to_string(),  
    }  
}
```

```
$ cargo test  
.../src/fizzbuzz.rs:16:5: 21:6 error:  
non-exhaustive patterns: '(false, false)' not covered
```

# Acceptance test passes

```
$ cargo test  
test test::test_1_to_16 ... ok
```

Done?

No. Client wants more features.

# Outline

- 1 Introduction
- 2 Original FizzBuzz problem
- 3 FizzBuzz 2: user configuration
- 4 FizzBuzz 3: FizzBuzzPop and beyond
- 5 Parallel FizzBuzz
- 6 Conclusion

# Adding new features

Client wants to:

- Choose two **arbitrary** divisors in place of 3 and 5
  - ▶ such as 4 and 7
- Choose other **arbitrary** words in place of "Fizz" and "Buzz"
  - ▶ such as "Moo" and "Quack"

# Type-driven refactoring

Types mean: refactoring is much more fun!

- Add **new** tests.
- Change types and code: to make new tests **type check**.
- **Refactor** original code and tests: use new APIs.
- Keep passing the **old** tests.
- Delay writing code for new features.

## More features means more types

Change fizzbuzz::evaluate to defaults::fizzbuzzer:

```
mod defaults;

fn run_to_seq(start: int, end: int) -> Vec<String> {
    range_inclusive(start, end)
        .map(defaults::fizzbuzzer)
        .collect()
}
```

Add new types to FizzBuzz module:

```
pub type Pair<'a> = (int, &'a str);
pub struct Config<'a>(pub Pair<'a>, pub Pair<'a>);

pub fn evaluate(Config((d1, w1), (d2, w2)): Config, i: int)
    -> String {
    fail!()
}
```

## New default configuration

```
// We can store a static Config as in C.  
static fizzbuzzer_config: Config<'static> =  
    Config((3, "Fizz"),  
           (5, "Buzz"));  
  
pub fn fizzbuzzer(i: int) -> String {  
    fizzbuzz::evaluate(fizzbuzzer_config, i)  
}
```

## More types means more tests

Write new property-based test over **arbitrary** user configurations:

```
#[quickcheck]
fn d1_but_not_d2((d1, w1): (int, String),
                  (d2, w2): (int, String),
                  i: int) -> TestResult {
    let config = Config((d1, w1.as_slice()),
                        (d2, w2.as_slice()));

    if i % d1 == 0 && i % d2 != 0 {
        TestResult::from_bool(fizzbuzz(i) == w1)
    } else {
        TestResult::discard()
    }
}
```

## Problem: coarse Config type

```
$ cargo test  
task 'fizzbuzz::test::d1_but_not_d2' failed at  
  '[quickcheck] TEST FAILED (runtime error).  
Arguments: ((0, ), (0, ), 0)'
```

- 0 as a divisor **crashes!**
- We discovered client's **underspecification**.
- Client says: meant to allow only divisors within 2 and 100.

We need to:

- Add runtime **validation** when **constructing** Config.
- Refine Config random generator.

## Add (runtime) validation

Runtime precondition contract: Rust's assert! (very primitive; fails a task on failure):

```
static DIVISOR_MIN: int = 2; static DIVISOR_MAX: int = 100;

fn validate_pair(&(d, _): &Pair) {
    assert!(d >= DIVISOR_MIN,
           "divisor {} must be >= {}", d, DIVISOR_MIN);
    assert!(d <= DIVISOR_MAX,
           "divisor {} must be <= {}", d, DIVISOR_MAX);
}

impl<'a> Config<'a> {
    pub fn new(pair1: Pair, pair2: Pair) -> Config {
        validate_pair(&pair1); validate_pair(&pair2);
        Config(pair1, pair2)
    }
}
```

# A note on error handling

- Rust does not have exceptions!
  - ▶ Exceptions are evil because they escape the type system.
- Rust task failures are brutal.
- Outside scope of this presentation: principled type-based error handling using `Result<T, E>`:

## Some changes to defaults setup

```
// Cannot be static variable because of runtime
// validation and also use of Vector.
fn fizzbuzzer_config<'a>() -> Config<'a> {
    Config::new(vec![(3, "Fizz"),
                    (5, "Buzz")])
}

pub fn fizzbuzzer(i: int) -> String {
    fizzbuzz::evaluate(fizzbuzzer_config(), i)
}
```

## Improve Config random generator

```
#[quickcheck]
fn d1_but_not_d2((d1, w1): (int, String),
                  (d2, w2): (int, String),
                  i: int) -> TestResult {
    if (d1 >= DIVISOR_MIN && d1 <= DIVISOR_MAX)
        && (d2 >= DIVISOR_MIN && d2 <= DIVISOR_MAX) {
        let config = Config::new(vec![(d1, w1.as_slice()),
                                       (d2, w2.as_slice())]);

        if i % d1 == 0 && i % d2 != 0 {
            TestResult::from_bool(evaluate(config, i) == w1)
        } else { TestResult::discard() }
    } else { TestResult::discard() }
}
```

## New test runs further, still fails

Refactor old code to `fizzbuzz::evaluate`, to pass old tests and new test.

```
pub fn evaluate(Config((d1, w1), (d2, w2)): Config, i: int) -> String {
    match (i % d1 == 0, i % d2 == 0) {
        (true, false) => w1.to_string(),
        (false, true)  => w2.to_string(),
        (true, true)   => w1.to_string().append(w2),
        (false, false) => i.to_string(),
    }
}
```

# Outline

- 1 Introduction
- 2 Original FizzBuzz problem
- 3 FizzBuzz 2: user configuration
- 4 FizzBuzz 3: FizzBuzzPop and beyond
- 5 Parallel FizzBuzz
- 6 Conclusion

# Generalizing to more than two divisors

Client wants FizzBuzzPop!

- Given three divisors (such as 3, 5, 7).
- Given three words (such as "Fizz", "Buzz", "Pop").
- Example: 21 should output "FizzPop".

## More features means more tests

Write new tests for new defaults::fizzbuzzpopper:

```
#[test] fn test_fizzbuzzpopper_2() {
    assert_eq!(fizzbuzzpopper(2), "2".to_string())
}

#[test] fn test_fizzbuzzpopper_21() {
    assert_eq!(fizzbuzzpopper(21), "FizzPop".to_string())
}

#[test] fn test_fizzbuzzpopper_9() {
    assert_eq!(fizzbuzzpopper(9), "Fizz".to_string())
}

#[test] fn test_fizzbuzzpopper_7() {
    assert_eq!(fizzbuzzpopper(7), "Pop".to_string())
}

#[test] fn test_fizzbuzzpopper_35() {
    assert_eq!(fizzbuzzpopper(35), "BuzzPop".to_string())
}
```

Change configuration to use pairs instead of just two:



## More tests means more (or changed) types

```
error: this function takes 2 parameters
      but 1 parameter was supplied
Config::new(vec![(3, "Fizz"),
                  (5, "Buzz")])
```

Change **type** Config to allow a sequence of pairs:

```
pub struct Config(pub Vec<Pair>);

impl<'a> Config<'a> {
    pub fn new(pairs: Vec<Pair>) -> Config {
        for pair in pairs.iter() {
            validate_pair(pair);
        }
        Config(pairs)
    }
}
```

## Fix remaining type errors

Refactoring reveals need to implement case of more than two divisors.

```
pub fn evaluate(Config(pairs): Config, i: int)
    -> String {
    // Can crash! And incorrect except for 2 pairs.
    let (d1, w1) = pairs[0];
    let (d2, w2) = pairs[1];

    match (i % d1 == 0, i % d2 == 0) {
        (true, false) => w1.to_string(),
        (false, true)  => w2.to_string(),
        (true, true)   => w1.to_string().append(w2),
        (false, false) => i.to_string(),
    }
}
```

# More computation means more types

Associate each divisor with a “rule” that awaits input.

```
// Make the decision to allocate a String here.  
fn rule(&(n, word): &Pair, i: int) -> String {  
    if i % n == 0 {  
        word.to_string()  
    } else {  
        String::new()  
    }  
}
```

## FizzBuzz demo time!


- Two volunteers: each to play role of Rule.
- One “manager” to combine two sub-results.

## Assemble the types

```
pub fn evaluate(Config(pairs): Config, i: int)
              -> String {
    let combined: String = pairs.iter()
        .map(|pair| rule(pair, i))
        .fold(String::new(),
              |result, s| result.append(s.as_slice()));
    if combined.is_empty() {
        i.to_string()
    } else {
        combined
    }
}
```

## A note on fold

For any value of type `Iterator<A>`, we can apply fold:  $(B, |B| \rightarrow B) \rightarrow B$ .



Example: for `Vec<String>`, fold with string concatenation + returns the concatenation of all the strings in the vector.

## Test failure: coarse types again

```
$ cargo test
task 'fizzbuzz::test::d1_but_not_d2' failed at
'[quickcheck] TEST FAILED.
Arguments: ((2, ), (3, ), 2)
```

### Demo time!

- Configuration: `vec![(3, ""), (5, "Buzz")]`
- Input: 9 (note: divisible by 2)
- Output: should be `" "` (because of the part divisible by 3)
- Output was: `"9"`

## Assemble the types

```
pub fn evaluate(Config(pairs): Config, i: int)
              -> String {
    let combined: String = pairs.iter()
        .map(|pair| rule(pair, i))
        .fold(String::new(),
              |result, s| result.append(s.as_slice()));
    if combined.is_empty() {
        i.to_string()
    } else {
        combined
    }
}
```

# Property-based testing rescued us again!

Be honest: would you have caught this bug manually?

- I didn't.
- I never wrote FizzBuzzPop examples testing empty strings.
- Property-based testing reveals **unexpected** corner cases.
  - ▶ (Empty “fizz” and “buzz” word strings).

# An empty string is **not** equivalent to no string

Presence of something “empty” is **not** equivalent to no thing.

Sending someone an empty email versus not sending any email.

Many programming languages get this wrong.

## Option<A> type

Option<A> is one of two possibilities:

- None
- Some(a) wraps a value a of type A.

For example, Some(String::empty()) is not the same as None.

```
let fizzFor3      = Some(String::new()) // multiple of 3
let buzzFor3     = None                // not multiple of 5
let fizzbuzzFor3 = Some(String::new()) // fizzed ""

let fizzFor2      = None      // not multiple of 3
let buzzFor2      = None      // not multiple of 5
let fizzbuzzFor2 = None      // not multiple of any
```

## Cleaning up the types

```
// rule type was: |&Pair, int| -> String  
//     changed to: |&Pair, int| -> Option<String>
```

### Useful type errors:

```
mismatched types: expected 'Option<String>' but found  
                      'String'
```

```
if i % n == 0 {  
    word.to_string()  
} else {  
    String::new()  
}
```

```
failed to find an implementation of trait Str for  
                      Option<String>  
result + s
```

## Fix the type errors: our rule builder

```
fn rule(&(n, ref word): &Pair, i: int) -> Option<String> {
    if i % n == 0 {
        Some(word.to_string())
    } else {
        None
    }
}
```

### Demo time!

- (Instructions: for result `Some(s)`, hold up the string, else don't hold up anything)
- Configuration: `vec![(3, ""), (5, "Buzz")]`
- Input: 9
- Output: now correctly is `" "`

## Fix the type errors: our compiler

```
pub fn evaluate(Config(pairs): Config, i: int)
    -> String {
    let combined: Option<String> = pairs.iter()
        .map(|pair| rule(pair, i))
        .fold(None, add_option);
    combined.unwrap_or_else(|| i.to_string())
}
```

- We need to write: addOption
- Rust standard library provides: unwrap\_or\_else

## “Addition” for Option[String]

```
fn add_option(a1: Option<String>, a2: Option<String>)
    -> Option<String> {
    match (a1, a2) {
        (Some(s1), None)      => Some(s1),
        (None,      Some(s2))  => Some(s2),
        (Some(s1), Some(s2))  => Some(s1.append(s2)),
        (None,      None)     => None,
    }
}
```

# Getting A back out of Option<A>

Do not lose information!

`unwrap_or_else` inspects the and either

- returns the value v inside a `Some(v)`,
- or else returns the value from a closure.

## Transform information; don't destroy it

Our complete code only uses `if` in one place.

### Bug cause: destroying information, using `if`

- `if i % n == 0 { word } else { String::new() }`
- `if combined.is_empty() {i.to_string()} else {combined}`

## Transforming information

- To `Option[String]`:  
`if i % n == 0 { Some(word.to_string()) } else { None }`
- Back to String: `combined.unwrap_or_else(|| i.to_string())`

## Type-directed design tip

We could have saved trouble **up front**, by using precise **types**.

- Avoid `if`, when possible.
- Avoid `String` (but required at I/O boundaries of program).

# Outline

- 1 Introduction
- 2 Original FizzBuzz problem
- 3 FizzBuzz 2: user configuration
- 4 FizzBuzz 3: FizzBuzzPop and beyond
- 5 Parallel FizzBuzz
- 6 Conclusion

# Parallelism

Some easy parallelism possible (not yet in Rust standard libraries):

- Use of `map`.
- Use of `fold`: parallelizable because of the monoid property:

## Option<String> is a Monoid

- ▶ There is an identity element (`None`).
- ▶ There is a binary associative operator (`add_option`).
- ▶ Fantastically important in practice!

## Final (hypothetical) parallelized code

```
pub fn evaluate(Config(pairs): Config, i: int)
    -> String {
    pairs.par
        .iter()
        .map(|pair| rule(pair, i))
        .reduce(add_option)
        .unwrap_or_else(|| i.to_string())
}
```

### Coding style tip

This level of conciseness is not always best: maybe too “clever”?

# Final demo!

## Demo time!

- Configuration:  
`vec![(3, "Fizz"), (5, "Buzz"), (7, "Pop"), (2, "Boom")]`
- Tree of volunteers to simulate concurrency:
  - ▶ Four at leaves.
  - ▶ Two “middle managers” each handling two leaves.
  - ▶ One top-level manager handling two middle managers.
- Input: 42
- Output: `"FizzPopBoom"`

# Parallelism summary

We discovered a theoretical speedup for generalized FizzBuzz:

- Sequential:  $O(n)$
- Parallel:  $O(\log n)$  (given  $\log n$  processors, and omitting some technical subtleties)

Also, driver outer loop can be sped up:

- Sequential loop on 1 to  $m$ :  $O(m)$
- Parallel loop:  $O(1)$  (given  $m$  processors)

# Current (July 2014) Rust limitations

- Rust **closures**: still limited (work in progress!!).
- Scala/Swift/Haskell/etc. have unrestricted closures: less complex types, easy staged **compilation**.
- Needs standard libraries for parallelism, using concurrency primitives such as **spawn**.
- Need faster compiler, build system.
- Need better test frameworks.

# Outline

- 1 Introduction
- 2 Original FizzBuzz problem
- 3 FizzBuzz 2: user configuration
- 4 FizzBuzz 3: FizzBuzzPop and beyond
- 5 Parallel FizzBuzz
- 6 Conclusion

# Conclusion

- Tests are great.
- Types are great.
- Tests and types work hand in hand, driving design and program evolution.
- Modern typed languages such as Rust promote fun, correct programming!
- It's a great time to be learning and using a modern typed language.

## Code, slides, article

- <https://github.com/franklinchen/type-directed-tdd-rust>
- The article has more detail omitted in the presentation.
- The hyperlinks in all provided PDFs are clickable.
- Scala: <https://github.com/franklinchen/talk-on-type-directed-tdd-using-fizzbuzz>
- Swift: <https://github.com/franklinchen/fizzbuzz-swift>