

Offline vs Online Remapping Workflows

A COMPARISON OF SPATIAL REMAPPING IMPLEMENTATIONS IN E3SM CLIMATE MODEL

Vijay Mahadevan¹ Iulian Grindeanu¹ Jason Sarich¹ and
Robert Jacob¹

¹Argonne National Laboratory

5th Workshop on Coupling Technologies for Earth System Models

Date: September 21, 2020

Sponsors

This work is supported by the DOE-BER E3SM climate project.



<https://e3sm.org/>

1. Motivation and Challenges
2. E3SM Couplers Strategies
3. E3SM Software Updates and Interesting Results
4. Summary

Solution remapping on unstructured meshes is a complex process

Sensitivity: Algorithmic invariance to underlying mesh topology

Conservation: Ensure global, (and) local conservation of critical quantities

Consistency: Retain discretization order and accuracy in a given norm

Monotonicity: Preserve global solution bounds during remap

Scalability: Dynamic load balancing for optimal performance

Current state of art: Offline-Online model in E3SM

Imposes severe bottlenecks in the overall workflow

SOFTWARE TOOLS


- **ESMF-RegridWeightGen:** Bilinear, higher-order patch, first/second-order conservative, and two types of nearest neighbor interpolations.
- **TempestRemap:** Arbitrary order conservative and consistent remapping with monotonicity, between FEM/FDM/FVM discretizations
- **ncremap:** Optionally re-use ESMF or TempestRemap with specific support for climate NetCDF files, and parallelization with OpenMP
- **Alternatives:** SCRIP, Common Remapping Software (CoR), YAC interpolator

MOAB: A flexible infrastructure for grid aware coupling

- Full online computation of conservative and monotone remaps
- No approximations to mesh topology or field discretization description
- Optimal parallel performance characteristics with arbitrary PE layouts


WORKFLOW

- ▶ Offline: mbtempest tool
Conservative map generation and I/O on colocated PEs
- ▶ Online: iMOAB API
Scalable linear map generation on arbitrary component and coupler PE layouts



Spectral projection with Zoltan repartitioner on Cori

- Higher resolution model provides excellent scalability upto 1024 processes
- The coverage and intersection mesh computation time are bounded
- More optimizations for the bandwidth-limited weight assembly possible
- Switch from offline-online to fully-online seamlessly based on case demands



NE120 test case with different PE layouts on Cori (KNL)

Mahadevan V. S.
et al., (2020),
Geoscientific Model
Development


E3SM v2+ Changes for Coupling

Tri-grid configuration will be default


- What is Tri-grid ? Atmosphere, Land/River, Ocean/Sea-ice.
- New ATM-LND/RIV maps; Enables closer coupling between land and river models: water management, irrigation, inundation, ...

Atmospheric physics now uses a FV “Physgrid”

- Compute physics on subcells of spectral element (SE) instead of GLL point locations; E3SM v2 will use 2x2 subcells “pg2” per SE
- Physics columns reduced by factor=4/9 compared to SE; Speedup > 100%
- Transformation between SE and PG done internal to EAM with mass conserving algorithm; supports new Regionally Refined Meshes



New RRM Grid



SE4-PG2 Mapping

E3SM v2.0 scheduled release: Sept, 2021


MOAB-TempestRemap Tri-Grid online remap computations for E3SM

ATM→OCN

(Coupling with MPAS is
FV-FV instead of SE-FV)


ATM→ $\frac{1}{2}^\circ$ LND grid

(LND and RIV
components now on
separate common $\frac{1}{2}^\circ$ grid)




Coupler Grid Decomposition Optimization

Subset
Var: ParallePartition
512 subsets





MPAS mesh

Subset
Var: ParallePartition
512 subsets



HOMME mesh



"Inferred" Partitions on 3-D grid (top) and on its gnomonic projection (bottom)

Topological holes increase computation cost of $\Omega_{S \cap T}$ for $OCN \rightarrow ATM$ vs $ATM \rightarrow OCN$

Load-Balance Analysis: 1024 cores

- ▶ RCB: Independent parts
- ▶ iRCB: Inferred target partition in 3-D
- ▶ iRCB-G: Inferred target in 2-D Gnomonic plane

NE256-PG2

OCN(3.7M) \rightarrow ATM(1.57M)

Strategy	$\Omega_{S,C}$	$\Omega_{S \cap T}$
RCB	1.81	20.49
iRCB	0.66	7.72
iRCB-G	0.43	3.08

MCT version: 2.11

Minor changes:

- Fix bug in Rearranger when using alltoall
- impi optimization for large task counts
- Support for new ifx Intel compiler

To be released next month!

MOAB-TempestRemap

New Release:

- MOAB version 5.2.1 released on August 22, 2020
- TempestRemap version 2.0.5 released on June 12, 2020
- New Conda package available for MBTR stack usage

- ▶ With **MOAB-TempestRemap** (MBTR) integrated in E3SM, a path to achieve scalable performance, without sacrificing coupling accuracy
- ▶ MOAB-E3SM interface implemented for ATM, OCN/ICE and LND/RIV components with remap of two-way coupled data
- ▶ Performance comparison of MBTR vs MCT coupler in E3SM underway

MILES TO GO BEFORE WE SLEEP ...

- Property preservation in MBTR with **ClipAndAssuredSum (CAAS)**
- Utilize advanced **multi-grid inferred partitions** in the online remapping case for synchronized grid and coupled data transfers
- Distributed **component-to-component** direct transfers (same API)
- Support **meshless** higher order Weighted Least-Squares ENO and GMLS remap scheme through MOAB for scalar data

EXTRA SLIDES IF NEEDED FOR DISCUSSION

Algorithm 1 Compute Intersection mesh from Ω_S and Ω_T on N_x

1: **procedure** COMPUTE SOURCE COVERAGE AND INTERSECTION MESH

Input: *Partitioned Ω_S and Ω_T on coupler PEs.*

Output: Intersection mesh $\Omega_{S \cap T} = \Omega_S \cup \Omega_T$.

2: *Migrate* component mesh from component to coupler PEs with dynamic repartitioning with Zoltan2

3: Accumulate *source coverage* mesh to localize work

4: Compute *source-target mesh intersection* on coupler PEs

a: Advancing front intersection based on adjacency graph

b: Kd-tree based search and locate point

5: Store *communication graph* for point-to-point **c2x/x2c** transfers

6: Utilize TempestRemap to *compute remapping weights* operator ($A_{S \rightarrow T}$)

7: **end procedure**

Algorithm 2 Compute solution remap from Ω_S and Ω_T

1: **procedure** COMPUTE SOLUTION PROJECTION WITH REMAPPING WEIGHTS

Input: Coupled solution $X_S \in \Omega_S$ on source component PEs.

Output: Coupled solution $X_T \in \Omega_T$ on target component PEs.

- 2: Communicate X_S to coupler PEs using *communication graph* for **c2x**
 - 3: Apply remap weights operator: $X_T = A_{S \rightarrow T} X_S$ using SpMV algorithm
 - 4: Reduce X_T in coupler PEs for shared DoFs
 - 5: Communicate X_T on coupler PEs to target component using *communication graph* for **x2c**
 - 6: **end procedure**
-