



Cycles and Julia Sets: Novel algorithms for Numerical Analysis

Víctor Álvarez Aparicio¹

¹University of La Rioja

Summary. We present Lyapunov Cycle Detector (LCD.jl), a package that provides useful tools to study and visualize the basins of attraction induced by a complex rational map. The algorithms implemented in it utilize Hopf-endomorphisms and Lyapunov exponents to compute and distinguish the basins of attraction. Also, they benefit from the structure of the complex projective line $P^1(\mathbb{C})$ in order to avoid numerical overflows and indeterminations, and use some of Julia's built-in multi-threading features, reducing significantly the execution time of the algorithms.



Presentation. To describe and compute the basins of attraction induced by a complex rational map has traditionally been a very relevant matter in the study of certain branches of Mathematics, such as Numerical Analysis, Complex Dynamics or Discrete-time Dynamical Systems. From a computational perspective, when performing this calculations, some numerical problems as overflows, underflows or indeterminations might arise and affect the obtained results. In addition, approximating the basins of attraction often has a significant computational cost, depending on the parameters and precision considered.

In the Lyapunov Cycle Detector (LCD.jl) package [1], we include the implementation in Julia Language [3] of the methods described by the authors in [2], where one can find the proofs and the mathematical background that support these algorithms. They have been developed according to several goals, among which we highlight the following:

- (1) Being able to avoid indeterminations, overflows, underflows and other computational problems that often appear in software devoted to Numerical Analysis.
- (2) Consider the infinity point and work comfortably with it.
- (3) Achieve a fast and efficient execution of the algorithms.
- (4) In addition to computing the basins of attraction, extract some useful information about the discrete-time dynamical system induced by the iteration of the rational map.

Thanks to this approach, the benefits that this newly implemented algorithms provide have lead to better results both numerically (avoiding the previously mentioned computational problems) and computationally (in terms of efficiency and execution time) in comparison with other algorithms that have been developed by the authors, see [4], [5], [6].

Usage. In the Lyapunov Cycle Detector repository one can find multiple methods for many different purposes, such as iterating the Hopf-endomorphism associated to a given rational map or approximating the Lyapunov function described in [2]. However, the main functionality of this package is to compute and visualize the



basins of attraction of a complex rational map. This can be achieved through the following method:

```
gra=LCD.plotBasinsOfAttraction_Lyapunov(coefnum,
    coefden, (-1.5,1.5), (-1.5,1.5), 200, 1, 8;
    coloringStrat="position", inverted=false)
img=gra[1]
numColors=gra[2]
```

where *coefnum* and *coefden* contain the coefficients of the numerator and denominator of the rational map respectively, the considered region of the complex plane \mathbb{C} is $(-1.5, 1.5) \times (-1.5, 1.5)$, 200 is the maximum number of iterations allowed, 1 is the maximum length of the n -cycles we want to compute, 8 corresponds to the considered tolerance (10^{-8}), and *coloringStrat* and *inverted* determine how the basins are visualized.

In the two previous images we can see the resulting graphs of this method, considering *inverted* as *false* or *true* respectively.

1. References

- [1] V. Álvarez-Aparicio. Lyapunov Cycle Detector (LCD.jl), 3 2022.
- [2] V. Álvarez-Aparicio, J.M. García-Calines, L.J. Hernández-Paricio, and M.T. Rivas-Rodríguez. Algorithms for computing basins of attraction associated with a rational self-map of the Hopf fibration based on Lyapunov exponents. *Preprint*, 2022.
- [3] Jeff Bezanson, Alan Edelman, Stefan Karpinski, and Viral B Shah. Julia: A fresh approach to numerical computing. *SIAM review*, 59(1):65–98, 2017.
- [4] J.I. Extremiana-Aladana, J.M. Gutiérrez-Jiménez, L.J. Hernández-Paricio, and M.T. Rivas-Rodríguez. An implementation in Julia Language for the iteration of rational functions on the Riemann sphere. *Applications to Numerical Methods*, 2019.
- [5] L.J. Hernández-Paricio. Plotting Basins of a Univariate Rational map (PBURF.jl), 2019.
- [6] L.J. Hernández-Paricio, M. Marañón-Grandes, and M.T. Rivas-Rodríguez. Plotting basins of end points of rational maps with Sage. *Tbilisi Mathematical Journal*, (5):71–99, 2012.