






Check the transmission of the robot. How does the lifting and lowering of the gate work now? How can a motor drive be built?







One possible solution is to use a belt drive. Install the driven pulley and belt.





Program the gate controls using the buttons as on the remote control





Task 3. Program



Scratch



WeDo Software



Program the robot controls using the buttons.

In the Scratch 3.0 programming environment, the program looks like this:



Adjust the duration of the movement so that the cogging of the toothed racks does not occur.

```
when u ▼ key pressed

set motor ▼ power to 100

set motor ▼ direction to that way ▼

turn motor ▼ on for 4 seconds
```



Task 3. Program





WeDo Software

Program the robot controls using the buttons.

In WeDo Software, a similar program looks like this:





The gate is equipped with a motion sensor. Use it to automatically open and close the gate.






Task 4 *. Program



Scratch



WeDo Software




In the Scratch 3.0 programming environment, the program looks like

this:

```
when | clicked
                 distance < 50
      set motor ▼ power to 100
      set motor ▼ direction to that way ▼
     turn motor ▼ on for 4 seconds
    5 seconds
      set motor ▼ power to 100
      set motor ▼ direction to this way ▼
      turn motor ▼ on for 4 seconds
```








Question




How should the motion sensor be placed so that it can detect the approach of the car to the gate?
























Which of the waiting blocks reacts to the appearance of the car?

WeDo Software

| el |







Discuss!

- What gear did you use to build the robot's transmission?
- What part prevented the gate from closing in manual mode?
- What parts have been used so that the motion sensor can be configured to work with different cars?
- How does the gate rise and fall without distortion?



