

BenchMark ULTRA

Specifications

BenchMark ULTRA Slide Staining System specifications

General characteristics

Fully automated	Baking, deparaffinization, cell conditioning and staining, including IHC, ISH, SISH, immunofluorescence, multiparameter IHC staining (dual, triple), counter stain and titration
Slide position	1 – 30 slides with independent processing/functionality and temperature control for each position
Reagent carousel	35 reagent positions
Slides	25 x 75 mm, 1 x 3 in or 26 x 76 mm positively charged slides
Bulk solutions	Up to 7 different bulk solutions can be changed “on the fly” without process interruption
Waste	Two 20 L carboys, can be changed “on the fly” without process interruption
DI Water supply	NCCLS Type II water or equivalent (deionized water)
Temperature cControl	Ambient to 100°C
Modularity	One to eight VENTANA BenchMark ULTRA, VENTANA Discovery ULTRA or VENTANA BenchMark Special Stains instruments may be controlled from one BenchMark ULTRA computer system
Configuration	Free standing
Certifications	EC/EN 61010-1, IEC/EN 61010-2-010, IEC/EN 61010-2-101, IEC/EN 61010-2-081, EN 61326-2-6
Catalog number	N750-BMKU-FS 05342716001

Unique features

- Automated IHC/ISH platform manages STAT requests with no impact to in-process slides
- Exceptional throughput – 90 slides per 8 hour shift
- Individual slide heaters which eliminates need to batch runs

Environmental requirements

BTU/Hour output	400 BTU/Hr idle, 1000 BTU/Hr running
Room temperature	68°F to 90°F (20°C to 32°C)
Humidity	10% to 90%, non-condensing

Electrical specifications

Voltage	~100-230V
Current	4-6 Amps
Frequency	50/60 Hz

Physical characteristics

Size (W x D x H)	44.00 in x 33.10 in x 62.40 in (111.76 cm x 84.07 cm x 158.50 cm) 13.5 in x 14.5 in x 13.5 in (34 cm x 37 cm x 34 cm)
Weight	650 lbs (294.8 kg)
Clearances	- Top 15 in (38.1 cm) - Sides 4 in (10.2 cm) - Rear 6 in (15.2 cm)



BenchMark ULTRA

www.roche.com
www.ventana.com

© 2013 Ventana Medical Systems, Inc.

VENTANA, the VENTANA logo, BENCHMARK
and DISCOVERY are trademarks of Roche.
All other trademarks are the property of their
respective owners.
N2504-6 0512B

VENTANA

Empowering | Testing Efficiency