



FUZHOU CONSSIN LIGHTING CO.,LTD

PRODUCT SPECIFICATION

	Product Model:	MKT1-480
Lighting & electrical performance	Rated power	480(±5%)W
	Input voltage (AC)	100-240V
		277V~Max.2.2A 50/60Hz(for North America only)
	Electrical Protection	Overcurrent, short circuit, over-temperature, low voltage protection
	Light Source	High-efficiency LED module
	Rated Luminous Flux	67200-72000 Lm
	Output Modes	4-level dimming
	Color Temperature / CCT	5000K
	Color Rendering Index / CRI	Ra70,optional Ra80/90
	Beam Angle	100°X30°
	Light Head Adjustment	The four lamp heads can rotate 270 degrees horizontally and 180 degrees vertically.
	Glare Control	With anti-glare hood
Mast & Mechanical Design	Maximum Deployed Height	2900mm
	Folded Dimensions	1060 × ϕ 140
	Mast Type	Manual
	Mast Locking Mechanism	pin lock
	Base & Mobility	tripod base
	Wind Resistance	At the specified height of 2900mm and with the legs extended, the wind speed level is 6.
	Housing / Enclosure Material	steel
Environmental & Durability	Ingress Protection / IP Rating	IP67
	Impact Protection / IK Rating	IK10
	Operating Temperature	-30°C to +45°C
	Corrosion Resistance	C3M
Dimensions, Packaging & Options	Net Weight	30KG
	Package Dimensions	1185(L)x200(W)x525(H)mm
	Standard Kit Contents	Lamp main unit x1, lamp pole x1, power cord x1, anti-glare cover x4, sandbags x4, spring cord x1, manual x1
	Warranty	3 Years
	Certifications	CE / UKCA / CSA /RoHS/SAA/PSE

