

EE 710 CODING THEORY MINOR 1 MM 25 AUG 29 2016

Note: (i) Answer all parts at the same place (scattered answers will not be graded).
(ii) Write assumptions wherever made. (iii) Show all intermediate steps. Good Luck!

1. Entropy of coin toss [5]

Let X denote the number of tosses required for a coin until the first tail appears.

- (a) Assume the coin to be unfair with p being the probability of getting a tail. Find the entropy, $H_2(X)$. [3]
- (b) What happens when $p \rightarrow 0$? Explain mathematically and intuitively (< 3 sentences). [2]

2. Variable Length Codes [5]

- (a) Can we construct a ternary Huffman code with codeword lengths 2, 2, 2, 2, 2, 2, 2, 2, 3, 3 and 3? Explain. [3]
- (b) Consider the variable length code $C_1 = \{00, 01, 0\}$. Is it uniquely decodable? Is it an instantaneous code? What about the variable length code $C_2 = \{00, 01, 100, 101, 11\}$? Is it uniquely decodable? Instantaneous? [2]

3. Z Channel [10]

Consider the Z channel shown Fig.1.

- (a) Find the input probabilities that result in capacity. [5]
- (b) If N such channels are cascaded, find the equivalent channel. Also, draw the equivalent channel and show the transition probabilities. [3]
- (c) What is the capacity of the combined channel as $N \rightarrow \infty$? [2]




Fig. 1.

4. Linear Codes [5]

- (a) Show that if C is a binary linear code, then the code obtained by adding an overall parity check bit to C is also linear. [3]
- (b) For the code $C = \{00000, 10101, 01010, 11111\}$ construct the generator matrix. [2]

▲▲▲

- RB