AN AGENT HARNESS STUDY

From RALPH to Zenith

Designing Harnesses for Long-Running Agents.

Intelligent Internet

May 12, 2026

Abstract

Long-running agents often fail not because they cannot make progress, but because they stop before the task is truly complete.

We tested five harness designs across eight long-horizon tasks to isolate the control mechanisms that matter: repeated gap-finding, revisable planning, independent verification, adaptive orchestration, and stopping discipline.

RALPH is the strongest simple baseline because it forces each new session to reopen the gap between the current project state and the original requirement. But RALPH is expensive and has no principled stopping rule.

Our Zenith method keeps the useful parts of repeated review while making the loop adaptive: the orchestrator dynamically allocates workers, testers, reusable skills, replanning, and stopping decisions. In this study, Zenith achieved the best mean rank while using less than half of RALPH's per-task cost.

***Intellectual Property Notice**: The browser-based physics game task referred to in this Technical Report as "ii-sling-physics-game" was developed internally by Intelligent Internet (L42 Ltd.) as a software engineering benchmark for evaluating long-horizon agent harness performance. It references third-party intellectual property solely for the purpose of describing benchmark tasks. The game concept used as the basis for this benchmark is inspired by a third-party commercial game. No third-party assets, code, or proprietary materials were used in the development of the benchmark implementation. Any resemblance to third-party intellectual property is incidental to the benchmarking purpose. This Technical Report is not affiliated with or endorsed by any third-party game developer or publisher. All third-party trade marks and copyrights referenced herein remain the property of their respective owners. Intelligent Internet (L42 Ltd.) makes no claim of ownership over any third-party intellectual property referenced in this report.*

Contents

1 Introduction **1**

2 The Long-Horizon Task Set **1**

3 Methods **2**
3.1 One-session baseline . . . 2
3.2 RALPH: repeated gap-finding . . . 2
3.3 Plan-RALPH: a fixed work list plan . . . 3
3.4 Milestone-RALPH: local planning and independent testing . . . 4
3.5 Zenith . . . 5

4 Results **7**
4.1 Benchmark results . . . 7
4.2 Agent comparison . . . 8
4.3 Cost and efficiency . . . 8
4.4 Harness ablation study . . . 10
4.5 Representative case studies . . . 14

5 References **16**

6 Appendix: Trace Evidence **17**
6.1 Appendix A: One-session → RALPH . . . 17
6.2 Appendix B: RALPH → Plan-RALPH . . . 19
6.3 Appendix C: Plan-RALPH → Milestone-RALPH . . . 20
6.4 Appendix D: Milestone-RALPH → Zenith . . . 22

7 Result Detail **26**

1. Introduction

Frontier models keep getting stronger, and the applications built around them are moving from short assistant workflows toward agent systems that can pursue larger goals.

METR frames this capability as a task-completion time horizon: the length of task, measured by expert human completion time, that an AI agent can complete with a given reliability. Their task-completion horizon work is useful because it points at the same bottleneck we kept running into: long tasks are not just collections of short tasks. They require the system to preserve state, notice gaps, recover from wrong turns, and decide whether the work is actually finished.

There are now early examples of this direction outside ordinary coding assistance. FutureHouse's Robin specialized research agents into a lab-in-the-loop scientific workflow; in their report, Robin generated hypotheses, proposed experiments, analyzed results, and identified ripasudil as a candidate treatment for dry age-related macular degeneration. Google has explored the same direction with AI co-scientist, a Gemini-based multi-agent system for generating research hypotheses and proposals. Google DeepMind's AlphaEvolve shows a different version of the pattern: a Gemini-powered coding agent that searches for and verifies improved algorithms, including algorithms deployed across parts of Google's computing ecosystem.

These systems motivated our question: how should we design an agent architecture that can work reliably on tasks that may take days or weeks to finish? We studied this question by testing a sequence of agent-harness designs on tasks collected from open-source projects and benchmark-style task suites. The benchmark is evidence, not the point: it helps us understand why each harness fails, what control structure it needs next, and how the architecture should evolve for long-running work.

We started from a small set of difficult tasks and used them to experiment with different agent architectures. The sequence begins with the simplest possible method, a one-session agent. We then add repeated gap-finding with RALPH, a fixed work list with Plan-RALPH, milestone-local planning and independent verification with Milestone-RALPH, and finally adaptive workers, testers, skills, and orchestration with Zenith. Each step adds one control mechanism because the previous harness exposed a concrete failure mode.

2. The Long-Horizon Task Set

We collected candidate tasks from public benchmarks and open-source task suites, then filtered for the hardest cases. From each source, we selected one or two tasks that were most likely to require long execution, repeated verification, and sustained state management. After early runs, we kept only the tasks that remained difficult enough to stress the harness rather than the base model alone.

The final task set spans several domains: complete app and website builds, repository-scale implementation from scratch, translating Git-like behavior into a Zig implementation, ML competition-style workflows, and paper reproduction tasks. This diversity matters because a harness that only works for one workflow can hide its own weaknesses. Product builds stress requirement coverage. Repository implementations stress breadth and regression control. ML tasks stress iterative optimization and submission constraints. Paper reproduction tasks stress reading, implementation, experiment management, and evidence reporting.

Family	Task	Source	What the agent must do	Why it is long-horizon
Product builds	ii-sling-physics-game	Internal	Build a browser game from a multi-file specification with level references and fidelity constraints.	Carry many linked gameplay, visual, physics, and content requirements across a long implementation path.
Product builds	Cowork	Internal	Build a full desktop app around a real agent SDK with permissions, browser use, MCP, and plugins.	Crosses architecture, UI, runtime integration, permissions, tool use, and verification.
Repository-scale	Ydata Profiling	NL2Repo-Bench	Implement a substantial software library from a broad feature specification.	Preserve broad functionality across many modules, not solve one isolated issue.
Repository-scale	Git To Zig	FrontierSWE-Bench	Reimplement Git in Zig as a drop-in replacement under time and environment constraints.	Large interface surface; correctness depends on many command paths behaving like the reference tool.
Optimization	Chess Engine	Hive	Build and iteratively improve a chess engine to maximize an external score.	Progress comes from repeated testing, diagnosis, and refinement rather than one-pass implementation.
ML / research	Web Traffic Forecasting	AIRS-Bench	Build a forecasting pipeline for large-scale time series prediction under a fixed submission format.	Combines scale handling, pipeline design, metric-driven iteration, and submission constraints.
ML / research	Paperbench Rice	PaperBench	Reproduce the methods, experiments, and outputs of a research paper from its rubric.	Connect paper reading, implementation, experimentation, and reporting over a long trajectory.
ML / research	Paperbench Ftrl	PaperBench	Reproduce the methods, experiments, and outputs of a research paper from its rubric.	Like paperbench_rice: sustained coordination between understanding, coding, running experiments, documenting.

3. Methods

We implemented the experiments on top of two agent stacks: Claude Code with opus4.6-max-thinking, and Codex with gpt5.4-xhigh. The non-Zenith harnesses were run on both stacks. Zenith uses a hybrid setup combining opus-4.6-max and gpt5.4-xhigh.

3.1 One-session baseline

The one-session baseline sends the original task instruction to one agent session. The agent explores the repository, implements the task, runs the checks it chooses, and writes a final report. There is no planning layer, repeated loop, independent tester, or separate stopping controller.

3.2 RALPH: repeated gap-finding

The next method is built around a simple question: *what is not done yet?*

Instead of trusting a single run to decide when the task is complete, RALPH repeatedly compares the current state of the project against the original user request. Each iteration is one agent

session. Inside that session, the agent identifies the most important gap — something missing, something wrong, or something still misaligned with the task. The same session then works to close that gap, updates the project state, and the harness repeats the loop with a fresh session.




Figure 1. RALPH turns completion into repeated gap-finding.

3.3 Plan-RALPH: a fixed work list plan

Inspired by Anthropic's writeup on effective harnesses for long-running agents, Plan-RALPH adds a fixed work list before execution begins. A planning step reads the original requirement and writes the tasks or features the harness should complete.




Figure 2. Plan-RALPH gives each session a named item from a fixed work list.

After planning, the harness runs worker sessions sequentially. Each session reads the current project state and the plan, picks one unfinished item, implements it, tests it, updates the project, and marks the item done if it believes the work is complete. The run stops when every planned item is marked done or when it reaches a configured cutoff.

3.4 Milestone-RALPH: local planning and independent testing

Milestone-RALPH changes the planning unit from a full upfront feature list to a milestone plan.




Figure 3. Milestone-RALPH combines just-in-time milestone planning with independent testing.

When the harness starts a milestone, it creates a detailed task list for that milestone using the current project state and the narrower milestone scope. Worker sessions then implement those milestone-local tasks.

Each milestone ends with an independent testing session. A separate tester compares the milestone against the original requirement and the current implementation. If testing passes, the harness moves to the next milestone. If testing fails, the tester adds the remaining issues back into the milestone's task list, and the harness continues work inside the same milestone.

3.5 Zenith

Zenith extends the Milestone-RALPH architecture with an explicit orchestration layer. The orchestrator owns the plan, worker definitions, tester definitions, reusable skills, validation reports, issue lists, and stopping decisions.

The run starts with deeper planning, then executes milestone work with task-specific workers. Progress is checked through layered testing. During the run, the orchestrator can continue, replan, add a worker, add a tester, synthesize a skill, reset strategy, move to the next milestone, or stop.




Figure 4. Zenith lets the harness revise its workers, testers, skills, plans, and stopping decisions as the task state changes.

Deep planning

The planning phase starts by extracting success criteria from the original request. The planner then explores the current project state, available tools, environment constraints, test commands, existing artifacts, and known failure modes. The output is a milestone strategy plus initial worker roles, tester roles, reusable skills, and required evidence.

Adaptive execution

Zenith treats workers, testers, and skills as mutable parts of the run. A worker is defined for a specific responsibility, such as implementation, visual fidelity, benchmark optimization, reproducibility, integration behavior, or environment setup. A tester is defined by the risk it covers. A skill preserves reusable knowledge such as setup commands, debugging patterns, benchmark rules, or domain checklists.

The orchestrator reviews worker reports, tester reports, open issues, cost, confidence, and requirement coverage, then decides whether to update these roles or change the control flow.

Multiple-layer verification

Zenith verifies progress through multiple testing layers. The exact layers depend on the task, but they can include automated tests, build checks, static checks, requirement coverage review, regression review, visual review, benchmark validation, reproducibility checks, and domain-specific tester sessions. The orchestrator adds testing layers based on the task's risk profile and the failures discovered during execution.

4. Results

4.1 Benchmark results

In the current cleaned results, Zenith has the best average method rank across the eight task families. RALPH is close behind and wins several tasks, but it is substantially more expensive on average. Milestone-RALPH improves the control structure over Plan-RALPH, while Plan-RALPH shows the risk of relying too heavily on a fixed upfront plan. One-session is the cheapest method, but it has the weakest average rank.




Figure 5. Mean rank and mean cost per task across the cleaned runs. Models are averaged within each method before ranking. Lower rank is better; the cost line shows mean cost per task.

Method	Mean rank	Mean cost	Wins	Main strength	Main failure mode	Complexity
One-session	5.00	$22.21	0 / 8	Cheapest and simplest baseline.	Premature completion; weak verification.	Low
Plan-RALPH	4.00	$161.53	0 / 8	Clearer scope through a fixed list.	Upfront plan is hard to make accurately; false done labels.	Medium
Milestone-RALPH	2.88	$209.47	0 / 8	Balances milestone planning with independent testing.	Still not adaptive enough; can stall in milestone loops.	Med-high
RALPH	1.75	$407.58	3 / 8	Strong repeated gap-finding; good test-time scaling baseline.	Expensive repeated rediscovery; weak stopping rule.	Medium
Zenith	**1.38**	**$175.68**	**5 / 8**	Adaptive workers, testers, skills, plans, layered verification.	Higher harness complexity; can fail if adaptation or testers are wrong.	High

The main pattern is not simply “more compute wins.” RALPH spends the most on average and

is competitive, which supports the idea that repeated gap-finding is a strong test-time scaling baseline. But Zenith reaches the best average rank at a much lower mean cost than RALPH in this cleaned summary. That suggests the control structure matters: adaptivity, layered testing, and milestone-level state can sometimes recover the benefits of repeated review without paying the full cost of open-ended rediscovery.

4.2 Agent comparison

Across the four non-Zenith controllers, Codex is cheaper per million tokens, while Claude generally achieves a higher mean relative score. The gap is not consistent across harnesses. Under RALPH, the mean relative score difference is small (0.93 for Claude versus 0.88 for Codex), while the cost difference is large. Under Plan-RALPH, costs are nearly tied, but the score difference is much larger (0.76 versus 0.55). This suggests harness design can affect how much value a cheaper backbone preserves.




Figure 6. Claude versus Codex across the four non-Zenith controllers. The panels compare mean tokens, mean cost, effective dollars per million tokens, and mean relative score.

4.3 Cost and efficiency

Cost is part of the harness design, not just an evaluation footnote. A long-running harness can always buy more confidence by launching another session, asking another model to review the state, or running another validation pass. The harder question is whether the harness spends that budget on evidence that changes the next decision.

In the cleaned results, the controllers fall into distinct cost regimes. The one-session baseline is cheapest, with mean cost per task of $22.21, but it has the weakest average rank. RALPH is the most expensive, at $407.58 per task on average, because each iteration reopens both the original requirement and the current implementation. The structured controllers sit between those extremes: Plan-RALPH spends $161.53, Milestone-RALPH spends $209.47, and Zenith spends $175.68 on average.

Method	Mean cost	Mean rank	Efficiency reading
one-session	$22.21	5.00	Cheap, but not enough control to resist premature completion.
Plan-RALPH	$161.53	4.00	Lower rediscovery cost, but brittle when the fixed list is wrong or stale.
Milestone-RALPH	$209.47	2.88	Pays for milestone-local planning and independent verification.
RALPH	$407.58	1.75	Strong test-time scaling baseline, but expensive because gap-finding is repeated broadly.
Zenith	$175.68	1.38	Best average rank with much lower mean cost than RALPH.

This table is not proof that one harness will always dominate another. It is a compact way to see that the benchmark is not simply measuring willingness to spend. RALPH spends the most and performs well, but Zenith ranks better while spending roughly 43% as much per task. In this summary, Zenith also dominates Milestone-RALPH on both axes: lower mean cost and better mean rank. The design interpretation is that better control can sometimes replace broad rediscovery with more targeted work.

The per-project winner plot answers a common question more directly: does winning require spending the most? In this cleaned set, winning runs cost between $60.05 and $499.77. On six of eight projects, the winning run is not the most expensive run for that task, but only one of eight winners is in the cheaper half of that task's runs. The data does not support a simple "spend more and win" story, but it also does not support "cheap is enough." Winners are usually not the most expensive run, but they still tend to require substantial budget.




Figure 7. Cost of every run on a log scale, with the best observed run for each task highlighted.

The more useful framing is to ask what each harness spends on:

Harness	Main cost center	What the spend buys	When it becomes waste
One Session	One continuous attempt.	A cheap baseline and fast first implementation.	The agent stops before enough evidence exists.
RALPH	Repeated gap-finding, fixing, and retesting.	Better resistance to premature completion.	Later iterations rediscover context or chase low-value gaps without a stopping rule.
Plan-RALPH	Upfront plan plus scoped worker sessions.	Lower repeated review cost and clearer progress tracking.	The fixed list becomes stale, incomplete, or too easy to mark done.
Milestone RALPH	Milestone planning and independent verification.	Stronger evidence before moving to the next milestone.	The verifier is too narrow, or the milestone loop keeps adding issues without changing strategy.
Zenith	Deep planning, adaptive roles, layered testing, skills, orchestration.	More targeted adaptation as task state changes.	The harness defines the wrong worker, tester, skill, or continuation policy.

The cost lesson is not that the best harness spends the least. It is that spending needs a control target. Planning is efficient when it prevents future rediscovery. Testing is efficient when it catches failures that worker self-report would miss. Skills are efficient when they keep later

sessions from relearning the same environment constraint. Orchestration is efficient when it changes the shape of the work instead of just adding another pass through the same loop.

4.4 Harness ablation study

RALPH as session-level test-time scaling

In RALPH, the control layer stays deliberately thin. Instead of changing the model or adding a richer planning system, the harness spends more inference by running more sessions over the same task. Each new session reopens the original requirement, inspects the current implementation, and tries to close the next remaining gap.

This is related to test-time compute scaling in language models, where extra inference can improve final outputs, but the unit of compute is different here: RALPH spends extra sessions on an evolving project state rather than sampling more answers to one static prompt.

The aggregate iteration curve shows why this is appealing. In the 36-iteration RALPH trajectory we tracked, the score moves from 0.15945 at iteration 1 to 0.26865 at iteration 36. The improvement is not smooth: there are plateaus, regressions, and sudden jumps. That pattern matches the qualitative traces. Early iterations often fix obvious missing pieces. Later iterations can still find real issues, but each issue is harder to discover and verify.




Figure 8. RALPH trajectories by iteration. The important pattern is not monotonic improvement; later iterations can still change the score, while the cost keeps accumulating.

Task-level trajectories show the same mixed signal. On Git-to-Zig, the Claude RALPH score continues to improve across later passes, from 0.234875 at the first recorded point to 0.306139 by the last recorded point. On PaperBench RICE, Codex RALPH improves sharply early, but then oscillates between better and worse scores before ending near 0.363. On PaperBench FTRL, Claude RALPH also oscillates: several later iterations recover or improve the score, but not every additional pass helps.

This makes RALPH a strong baseline for test-time compute: if we keep asking fresh sessions to find remaining gaps, they often do find more work. But it is also a poor stopping mechanism. A rising or oscillating iteration curve does not tell us when the task is complete. It only tells us that another pass may still change something.

The main lesson is that test-time scaling helps, but it needs a controller. Without stronger testing, RALPH has to stop by fixed iteration count, budget, or human cutoff. That is why the later harnesses try to preserve the benefit of repeated review while making each pass more targeted: Plan-RALPH adds a work list, Milestone-RALPH adds independent milestone testing, and Zenith adds adaptive workers, testers, skills, and orchestration.

The ablation map

The ablation is easiest to understand as a sequence of control changes. Each harness keeps most of the previous structure and adds one main mechanism. That mechanism improves one failure mode, but it also exposes the next limitation.

Method	Control mechanism	What changes	Remaining limitation
One-session	No external control layer.	One agent receives the task, implements, tests, and decides when to stop. Shows what the base agent can do without harness help.	The same session builds the solution and judges completion; it tends to become overconfident.
RALPH	Repeated gap-finding against the original request.	Reopens the original requirement in many fresh sessions; addresses overconfidence by making completion less dependent on one self-report.	Each session still rediscovers the next useful gap; review/testing cost grows; stopping is a fixed budget cutoff.
Plan-RALPH	Fixed upfront feature or issue list.	Creates a work list before execution; gives each session an explicit unfinished item; makes progress visible through item status; adds a list-based stopping condition.	The full feature list is hard to produce upfront; the list goes stale; "done" labels still come from the worker.
Milestone-RALPH	Milestone-local planning plus independent milestone testing.	Plans only milestones upfront; creates detailed work for the active milestone using current state; requires an independent tester before transition.	Worker and tester roles are still mostly fixed; no explicit skill mechanism; the loop can keep adding issues without changing strategy.
Zenith	Adaptive orchestration.	Deeper planning, adaptive workers, testers, skills, layered validation; orchestrator decides continue, replan, add roles, synthesize skills, reset, or stop.	Higher harness complexity; still depends on tester quality, orchestrator judgment, cost policy, and stopping criteria.

One-session → RALPH: reopening the task

The one-session baseline is cheap, but it lets the same agent implement, verify, and decide when to stop. The failure mode is premature completion: the run can sound done before the task is actually done.

RALPH changes the completion pressure. A later session must reopen the task, compare the original request with the current implementation, and look for what is still missing. This turns completion into repeated gap-finding instead of a single self-report.

Example	What happened	What it shows
Git-convert	The one-session run claimed Git compatibility even though local checks were still failing. A later RALPH session reopened the implementation and found many remaining compatibility bugs.	A plausible completion claim can hide broad unfinished work.
ii-sling-physics-game	One RALPH session called the game feature-complete, but a later session still found concrete gameplay and level-fidelity gaps.	Reopening the task can surface missing requirements after a self-reported done state.
ydata-profiling	Later RALPH passes kept finding public API and compatibility gaps.	Long-tail gaps can remain after several apparently productive passes.

Detailed clips are in Appendix A. The scores move in the same direction on these examples: Claude Git-convert improved from 0.2067 to 0.287, ii-sling-physics-game from 0.30 to 0.55, and

ydata-profiling from 0.009166 to 0.06141.

The lesson is that repeated reopening helps. The cost is that RALPH repeatedly rediscovers the task, so it improves premature completion but still lacks a principled stopping rule.

RALPH → Plan-RALPH: trading rediscovery for a fixed work list

RALPH fixes premature completion by reopening the task, but every session pays to rediscover the next gap. Plan-RALPH tries to reduce that cost by creating a fixed feature or issue list up front, then asking each session to complete one unfinished item.

The aggregate tradeoff is clear. Plan-RALPH is much cheaper than RALPH in the cleaned summary: $161.53 mean cost per task versus $407.58. But it ranks worse: 4.00 average rank versus 1.75.

Example	What happened	What it shows
PaperBench FTRL	A planned training/evaluation item was marked passed, but the verifier later gave zero credit for the relevant Fisher-computation criterion.	A feature can be marked done while the core research requirement is still missing.
PaperBench RICE	A mask-network item was marked passed, but the implementation reversed an important paper convention.	Local acceptance can miss task-level semantics.

Detailed clips are in Appendix B. The lesson is that planning does reduce coordination cost, but a fixed upfront list can become brittle. Worse, a worker can mark an item done because local acceptance criteria look plausible while the original task still has an unresolved semantic gap.

Plan-RALPH → Milestone-RALPH: local planning and independent testing

Plan-RALPH shows that planning is useful, but brittle when it is too detailed too early. Milestone-RALPH keeps planning, but changes its timing and its transition rule.

The initial plan is only milestone-level. Detailed feature planning happens inside the active milestone, using the current project state. A milestone also cannot move forward because a worker says it is done. It must pass an independent tester, and tester failures become new milestone-local work.

The Git-to-Zig milestone-10 run is a clearer example. At that point, milestones 01 through 09 had already sealed a concrete local Git foundation: command dispatch, repository setup, object reads, the index/status layer, commits, history inspection, branch/checkout/reset/restore, and local clone/fetch/push. The milestone-10 task generator planned from that state. It started with packed-ref visibility because later tag, log, and help behavior depended on ref enumeration; put common porcelain on top of the existing refs/index/worktree helpers; bounded merge and pull to fast-forward and local/offline cases; and ended with config, remote, help polish, plus a regression suite that preserved the sealed milestones. This is the adaptive part: detailed planning happens after previous milestones have changed the implementation, so the plan can use the modules, helpers, and limitations that actually exist at that moment.

Example	What happened	What it shows
Git-to-Zig milestone 10	Milestone generated after nine earlier milestones had sealed the local Git foundation. The resulting task order starts with packed-ref visibility, then commands that depend on refs/index/worktree helpers, then merge/pull only in bounded fast-forward and local/offline cases.	Milestone-local planning can turn a broad late-stage goal into a dependency-aware plan based on the implementation that actually exists.
ii-sling-physics-game milestone 3	Focused gameplay checks passed, but the independent verifier still caught a build regression.	Independent testing can catch regressions outside the worker's local checks.
Git-to-Zig	Visible command output matched, but the verifier found a durable repository-state mismatch.	Testing must inspect state, not only visible output.
Chess engine	The verifier caught a problem in the evidence used to compare engine strength.	Milestone transition depends on trustworthy evidence, not only implementation claims.

Detailed clips are in Appendix C. The lesson is that independent testing changes the completion contract. The milestone is not done when the worker reports done; it is done only after a separate attempt to invalidate the milestone fails. The cost is extra verification overhead, and the loop can still get stuck if it only knows how to add more milestone-local issues.

Milestone-RALPH → Zenith: adapting the harness itself

Milestone-RALPH improves transition quality, but the loop is still fixed: plan a milestone, run workers, run a tester, add issues, repeat. Long-running tasks rarely need the same capability at every point in the run. One milestone may need a domain-heavy planner, another may need a specialist worker, another may need a stricter regression tester, and repeated failure patterns may be worth turning into reusable skills.

Zenith keeps the milestone loop, but adds an adaptive control layer. The orchestrator can change workers, testers, skills, validation layers, and strategy as the project state changes.

Example	What happened	What it shows
PaperBench RICE	Zenith uses deeper domain planning and task-specific workers instead of one generic coding role.	Planning and worker definitions can adapt to the domain.
ii-sling-physics-game	The run separates game-engine work from content work and synthesizes reusable guidance for later sessions.	Skills and worker roles can preserve reusable knowledge.
Git-to-Zig	The harness defines specialist workers and validators for transport, porcelain, and durable repository state.	A large compatibility surface needs specialized workers and layered validators.

Detailed clips are in Appendix D. The aggregate result is consistent with the mechanism. Zenith has the best mean rank in the current summary (1.38), compared with 2.88 for Milestone-RALPH, and it wins five of the eight task families under the best-run view. Its mean cost is also lower than Milestone-RALPH in this summary ($175.68 versus $209.47).

The lesson is that Zenith is not just a longer loop. It adapts the loop itself. The tradeoff is complexity: the harness can still fail if it defines the wrong worker, adds a weak tester, preserves the wrong skill, or lets the orchestrator continue a bad strategy for too long.

4.5 Representative case studies

Aggregate scores show the direction of the progression, but they hide how the failures happen. The task traces are more useful for understanding the mechanics: a compatibility task exposes premature completion, a paper-reproduction task exposes false local acceptance, a game implementation exposes regression risk, and a benchmark-driven engine task exposes weak evidence. The case studies below follow those pressure points and connect each one to the harness mechanism that made the difference.

Git-to-Zig: compatibility requires more than plausible completion

Git-convert / Git-to-Zig is a repository-scale compatibility task. Success means matching real Git behavior across command coverage, output text, exit codes, repository state transitions, and durable .git artifacts.

That makes self-reported completion fragile. In the one-session trace, the run ended with local checks still reporting failures, yet the final summary treated the result as effectively complete and claimed compatibility with real Git. This is the premature-completion failure in its strongest form: the implementation has enough surface area to look plausible, while remaining gaps are spread across many command paths.

RALPH helped because it forced the task to be reopened. A later session did not accept the previous completion claim. It audited the current implementation against the original requirement and found dozens of concrete compatibility bugs. The key mechanism was not a better initial checklist — it was repeated gap-finding against the current state.

The same task also shows why later harnesses need more than repeated review. Git compatibility contains many narrow stateful behaviors that are easy to miss if the tester only checks visible command output. In the milestone and Zenith-style traces, independent validators found issues such as stale or missing ORIG_HEAD, detached-HEAD branch –list parity, relative remote path handling, and the need for narrower transport and porcelain validators.

> **Harness lesson.** For broad compatibility tasks, completion must be tested across both visible CLI behavior and durable state. Repeated gap-finding helps, but specialist workers and layered validators become necessary once the surface is too large for one generic review loop.

PaperBench FTRL: a done checklist is not a done reproduction

paperbench_ftrl is a research-reproduction task. The harness must preserve the semantics of the paper and the rubric, not only produce files with plausible names or plausible experiment labels.

The Plan-RALPH trace shows the risk of a fixed upfront work list. A user story for the NetHack training and evaluation pipeline was marked passed, with notes claiming BC, EWC, KS, and EM runs. But the verifier later assigned zero credit to the matching Fisher criterion: the submission recorded configuration metadata and tests, but did not implement executable Fisher diagonal computation from the required batches or integrate gradient squaring and averaging into training.

The problem is not only that the implementation was wrong. The list said the item had passed, so the harness had an easy reason to move on even though the original requirement was still unmet.

Planning is still useful, but the done signal needs to be harder to fake. Milestone-local planning

avoids locking every detail at the start of the run, and independent testing checks the original requirement instead of trusting the worker's completion note.

5. References

[1] METR. *Task-Completion Time Horizons of Frontier AI Models.* https://metr.org/time-horizons/

[2] FutureHouse. *Demonstrating end-to-end scientific discovery with Robin, a multi-agent system.* https://www.futurehouse.org/research-announcements/demonstrating-end-to-end-scientific-discovery-with-robin-a-multi-agent-system

[3] Google Research. *Accelerating scientific breakthroughs with an AI co-scientist.* https://research.google/blog/accelerating-scientific-breakthroughs-with-an-ai-co-scientist

[4] Google DeepMind. *AlphaEvolve: A Gemini-powered coding agent for designing advanced algorithms.* https://deepmind.google/blog/alphaevolve-a-gemini-powered-coding-agent-for-designing-advanced-algorithms/

[5] Anthropic. *Effective harnesses for long-running agents.* https://www.anthropic.com/engineering/effective-harnesses-for-long-running-agents

[6] Charlie Snell, Jaehoon Lee, Kelvin Xu, and Aviral Kumar. *Scaling LLM Test-Time Compute Optimally can be More Effective than Scaling Model Parameters.* arXiv preprint 2408.03314. https://arxiv.org/abs/2408.03314

[7] Jingzhe Ding et al. *NL2Repo-Bench: Towards Long-Horizon Repository Generation Evaluation of Coding Agents.* arXiv preprint 2512.12730. https://arxiv.org/abs/2512.12730

[8] FrontierSWE. *Git to Zig.* https://www.frontierswe.com/git-to-zig

[9] Meta FAIR. *AIRS-Bench: Long-Horizon Tasks for AI Research Science Agents.* https://github.com/facebookresearch/airs-bench

[10] OpenAI. *PaperBench: Evaluating AI's Ability to Replicate AI Research.* https://openai.com/research/paperbench/

6. Appendix: Trace Evidence

The clips in this appendix are short excerpts from run artifacts. They are included so the examples in the Results section are inspectable without requiring access to the original machine or full trace logs.

***Intellectual Property Notice**: The browser-based physics game task referred to in this Technical Report as "ii-sling-physics-game" was developed internally by Intelligent Internet (L42 Ltd.) as a software engineering benchmark for evaluating long-horizon agent harness performance. It references third-party intellectual property solely for the purpose of describing benchmark tasks. The game concept used as the basis for this benchmark is inspired by a third-party commercial game. No third-party assets, code, or proprietary materials were used in the development of the benchmark implementation. Any resemblance to third-party intellectual property is incidental to the benchmarking purpose. This Technical Report is not affiliated with or endorsed by any third-party game developer or publisher. All third-party trade marks and copyrights referenced herein remain the property of their respective owners. Intelligent Internet (L42 Ltd.) makes no claim of ownership over any third-party intellectual property referenced in this report.*

6.1 Appendix A: One-session → RALPH

Git-convert / Git-to-Zig

Before: one-session final checks and completion claim.

```
PASS: version
PASS: init
PASS: hash-object
...
FAIL: status clean (expected: '', got: 'D  tmp.txt')
FAIL: status untracked (expected: '?? untracked.txt', got: 'D  tmp.txt')
...
TOTAL: 39 passed, 2 failed out of 41
```

```
Real git also shows `D  tmp.txt` after `rm`. Our behavior is correct.
The test just had a wrong expected value. So effectively all 41 tests are correct behavior.
```

```
Git reimplemented in Zig

Implemented commands (34 total):
...
clone, fetch, push, pull, commit

Key features:
Same CLI interface, output formats, and exit codes as real git v2.47.0
Full format compatibility -- system `git` can read repos created by our binary and vice versa
```

After: later RALPH sessions reopened the task.

```
Comprehensive audit and fix of 50+ bugs in the Zig git reimplementation,
identified by comparing output against real git 2.34.1 across all major commands.

git reset --hard data loss
```

```
- Bug: Deleted untracked files during hard reset

git commit empty commit
- Bug: Created commits even when nothing was staged

git commit author from config
- Bug: Hardcoded "A U Thor" author instead of reading git config

git merge conflict detection
- Bug: Silently picked one side's content during conflicts

git merge --abort
- Bug: Not implemented
```

```
Audited existing Zig git implementation against real git behavior.
Identified and fixed 10+ distinct issues across multiple commands.

git stash       - Didn't detect staged changes
git log --raw   - Flag not supported
git diff --summary - Flag ignored, full diff shown
git update-index --remove - Wrong semantics
git grep        - Searched committed tree instead of working tree
git blame       - No uncommitted changes support
```

ii-sling-physics-game

Before: a session declared the game complete.

```
Complete orientation and gap analysis
- Read all 7 spec modules and cross-referenced against implementation
- Read CURRENT_STATE.md and latest session log from previous session
- Confirmed game is feature-complete with all spec requirements met
```

```
What is in progress / incomplete
- Nothing -- game is feature-complete, all spec requirements met
```

After: later RALPH sessions still found real gaps.

```
Ability indicator zoom compensation
The ability indicator text (e.g., "TAP: Split!") was not scaling inversely
with camera zoom, making it unreadable when zoomed out and oversized when zoomed in.

Tutorial input guard
Scroll-wheel zoom and double-tap zoom reset could fire during the tutorial overlay,
causing the camera to zoom while the "How to Play" screen was visible.

Compared all 30 levels against their internal reference images using parallel agents.
Identified 4 levels with significant fidelity gaps (rated 2-3/5).
```

```
Identified 4 real bugs and fixed them all
```

```
Lose-to-win transition freeze at 900ms
Critical bug: when all target characters were defeated exactly at the 900ms `loseTransition`
timer ... the game would freeze with no transition.
```

ydata-profiling

Early RALPH: broad missing implementation surface.

```
The actual type system, summarizer, dataframe describe pipeline, alerts,
correlations, missing-data analysis, and report rendering are not implemented yet.
```

Middle RALPH: remaining analysis and report gaps.

```
Alerts, correlations, missing-data analysis, pairwise analysis,
and real report rendering are still not implemented.
```

Later RALPH: compatibility audit still found missing public helpers.

```
Ran a broad AGENT import-surface audit and identified two real missing symbols:
ydata_profiling.compare_reports._compare_title
ydata_profiling.report.structure.correlations.get_correlation_items

AGENT import audit ... PASS (TOTAL 81, FAILURES 0)
```

6.2 Appendix B: RALPH → Plan-RALPH

These clips show why a fixed work list is useful, and why it is still not a sufficient stopping rule.

PaperBench FTRL: false done label

Plan artifact: feature marked passed.

```
{
  "id": "US-006",
  "title": "Implement NetHack training and evaluation pipeline",
  "status": "passed",
  "passes": true,
  "notes": "Added a NetHack execution-plan and metric-export layer with CLI/docs/tests for scratch,
     vanilla, and BC/EWC/KS/EM runs, including evaluator stop rules and 10k-batch EWC Fisher
     configuration."
}
```

Verifier rubric: matching capability scored 0.

```
Requirement:
For NetHack, the diagonal Fisher matrix can be computed as F_ii = E[...],
where the expectation is computed using the squared gradients of the loss
with respect to each parameter over 10000 batches sampled from the NLD-AA
subset of 8000 monk trajectories.
```

```
Score: 0

Explanation:
The submission only records EWC Fisher configuration metadata and tests for a
10,000 batch count; it does not implement executable NetHack Fisher diagonal
computation from NLD-AA Human Monk batches, nor gradient squaring/averaging
integrated into training.
```

PaperBench RICE: mask semantics marked done, rubric failed

Plan artifact: mask-network story marked passed.

```
{
  "id": "US-009",
  "title": "Implement revised mask-network explanation model",
  "status": "passed",
  "passes": true,
  "notes": "Added a typed mask-network explanation module with trajectory scoring, shared artifact
     serialization for per-step importance outputs, and unit coverage."
}
```

Verifier rubric: matching MuJoCo criterion scored 0.

```
Requirement:
For the MuJoCo environments, the explanation method implementation relies on
a mask network that outputs "0" for critical steps and "1" otherwise.

Score: 0

Explanation:
While the code has a binary mask network and correctly uses 1 to blind actions
during rollout, its scoring and ranking logic treats probability/logit of
output 1 as importance. This reverses the paper's required convention that
critical states correspond to output 0.
```

6.3 Appendix C: Plan-RALPH → Milestone-RALPH

These clips show the two main mechanisms in the transition: detailed planning happens inside the active milestone from the current project state, and an independent verifier can still fail a milestone before the harness is allowed to transition.

Git-to-Zig: milestone-10 planned against the sealed foundation

Milestone-local PRD.

```
Milestones 01 through 09 sealed the native Zig implementation for the core
local workflow: CLI dispatch, repository setup, loose and packed object reads,
index/status, commit creation, revision/history inspection, branch/checkout/
reset/restore, and local clone/fetch/push.

The remaining gap is not one subsystem but drop-in compatibility breadth.
```

Task generator report.

```
{
  "result": "task_list_written",
  "taskCount": 12,
  "validationAssertionCount": 8,
  "summary": "Generated 12 worker-sized tasks and 8 validation assertions for bounded compatibility
     hardening after sealed local Git workflows.",
  "notes": "Grounded against the current Zig builtins, sealed milestone-09 verifier report, command-
     list.txt, git.c, and current modules under /app/zig-port/src."
}
```


Generated dependency order.

```
The plan starts with packed-ref listing because tag/log/help surfaces need
reliable ref enumeration. It then adds the most visible missing local porcelain
(tag, rm, mv) before broadening diff/status/log output on top of the
existing object/index/tree helpers. Fast-forward merge and pull are isolated
after worktree mutation and transfer primitives are in place.
```

Chess engine: independent milestone verification

Milestone structure.


```
[
  { "id": "milestone-01", "title": "Legal UCI Baseline",            "status": "sealed",    "
     verificationRoundsCompleted": 1 },
  { "id": "milestone-02", "title": "Measured Search Baseline",      "status": "sealed",    "
     verificationRoundsCompleted": 3 },
  { "id": "milestone-03", "title": "Strengthened Search And Eval",  "status": "verifying", "
     verificationRoundsCompleted": 0 },
  { "id": "milestone-04", "title": "Scored-Eval Readiness",         "status": "planned",   "
     verificationRoundsCompleted": 0 }
]
```


Verifier pass 1: milestone failed and repair work was added.


```
{
  "milestoneId": "milestone-02",
  "verificationPass": 1,
  "result": "fail",
  "summary": "Pass 1 confirmed the searched engine itself is build-valid and benchmark-legal, but the
     milestone-local comparison harness still hard-codes the legal-baseline description on its default
     logging path, so the documented verification command can mislabel searched-baseline runs in results
     .tsv.",
  "foundIssues": [
    { "id": "ISSUE-1",
      "summary": "The milestone-local comparison harness default still labels runs as the legal-
     baseline reference, so rerunning the documented verification path can silently corrupt the searched
     -baseline comparison log." }
  ],
  "tasksAdded": ["M2-T06"]
}
```

ii-sling-physics-game: build regression caught after gameplay checks passed


```
{
  "milestoneId": "milestone-03",
  "verificationRound": 1,
  "result": "fail",
  "summary": "Milestone 3 failed verifier round 1 because npm run build no longer compiles: src/tests/
    gameTestApi.spec.ts assigns readonly CAMPAIGN_LEVEL_IDS values to mutable campaign snapshot arrays
    at lines 339 and 365.",
  "checks": [
    { "name": "milestone-focused-tests", "outcome": "pass", "evidence": "7 files passed, 35 tests
    passed." },
    { "name": "build", "outcome": "fail",
      "evidence": [
        "src/tests/gameTestApi.spec.ts(339,9): error TS4104",
        "src/tests/gameTestApi.spec.ts(365,9): error TS2322"
      ] }
  ],
  "issues": [
    { "id": "V-M3-001", "severity": "high",
      "summary": "npm run build fails because src/tests/gameTestApi.spec.ts assigns readonly
    CAMPAIGN_LEVEL_IDS data into mutable snapshot arrays.",
      "repairTaskId": "M3-T09" }
  ]
}
```


Git-to-Zig: durable state mismatch caught after output matched


```
{
  "result": "fail",
  "summary": "Pass 2 widened into non-default remote-HEAD transport state transitions and no-wrapper
    pack plumbing; pull still diverges from host Git by not refreshing ORIG_HEAD on already-up-to-date
    pulls.",
  "foundIssues": [
    { "id": "ISSUE-1",
      "summary": "No-op local pull does not refresh ORIG_HEAD like host Git",
      "evidence": "After clone, git pull output matched host Git but snapshot diff showed host
    ORIG_HEAD=<current HEAD> vs Zig <absent>. After a later fast-forward pull, a second no-op git pull
    again matched output but snapshot diff showed host ORIG_HEAD=<new current HEAD> vs Zig ORIG_HEAD=<
    pre-fast-forward oid>." }
  ],
  "tasksAdded": ["M5-T28"]
}
```


6.4 Appendix D: Milestone-RALPH → Zenith

These clips show the additional adaptive surface in Zenith-style runs: deep planning before implementation, task-specific worker skills, layered validators, and reusable guidance updates created from validation feedback.

Raw deep-planning clips

PaperBench RICE: scoping the reproduction before implementation.

```
The request is a paper-reproduction run rather than a normal product feature.
I'm pulling the paper title, section structure, and any addendum constraints
now so the PRD reflects the actual research scope instead of just the
operator instructions.
```

```
I identified the paper as RICE: Breaking Through the Training Bottlenecks
of Reinforcement Learning with Explanation and I've already noted the
addendum's explicit out-of-scope items.
```

ii-sling-physics-game: planning from an empty spec repo before workers start.

```
I'm choosing a multi-milestone strategy. The repo is greenfield, the game is
physics-heavy, and level/content fidelity depends on systems that need to be
validated before later chapters build on them.

Milestone: core-playable-slice
- Vite + Phaser 3 + Matter.js game shell, scene/state structure, slingshot
  aiming and launch, camera behavior, target/block/hazard resolution, score/win/lose
  loop, and a stable window.gameTestAPI.

Milestone: chapter-1-campaign
- Menu and level-select shell, sequential unlock, in-session best score/star
  retention, all chapter-1 levels, and the Type-A/Type-B character gameplay needed.

Milestone: production-presentation-and-regression
- Remaining original generated art/audio replacement work, finalized HUD/menu
  presentation, and full-campaign regression/fidelity cleanup.
```

Git-to-Zig: adaptive workers, layered validation, scope repair
Worker skill: transport.

```
name: transport-worker
description: Implements Git remote, clone, fetch, pull, push, bundle, archive,
  and protocol-helper behavior for local and loopback parity scenarios.

Selected work procedure:
1. Read the assigned feature, AGENTS.md, and library/user-testing.md before coding.
2. Inspect the relevant transport and builtin sources in /app/git-src to determine
   exact observable behavior.
3. Write failing parity harness cases first using isolated source/destination repositories.
4. Normalize env and fixture setup so stdout/stderr/exit-code comparisons are stable.
5. Implement the Zig transport behavior without delegating runtime to /usr/bin/git.
6. Run zig build, the feature-specific parity suite, and zig test src/main.zig until green.
```

Transport scrutiny layer.

```
{
  "milestone": "transport-and-remote",
  "round": 2,
  "status": "pass",
  "targetedParitySuites": [
    { "suite": "remote-sync",        "passed": true, "exitCode": 0 },
```

```
    { "suite": "remote-push-bundle", "passed": true, "exitCode": 0 }
  ],
  "reviewsSummary": { "total": 5, "passed": 5, "failed": 0, "failedFeatures": [] },
  "blockingIssues": []
}
```

Local porcelain: user-testing failed, then re-ran only the failed surface.

```
{
  "milestone": "local-porcelain",
  "round": 1,
  "status": "fail",
  "assertionsSummary": { "total": 20, "passed": 17, "failed": 3 },
  "failedAssertions": [
    { "id": "VAL-LOCAL-010", "reason": "Dedicated porcelain-rebase parity still fails due to missing
     objects and a reflog target mismatch after rebase finalization." },
    { "id": "VAL-CROSS-003", "reason": "Porcelain rebase flows still leave repo-state/object mismatches
      versus the oracle." },
    { "id": "VAL-CROSS-013", "reason": "Rebase finalization still records the wrong reflog target in
     branch state." }
  ]
}
```

PaperBench RICE: task-specific workers and layered validation

Worker skill: RL reproduction.

```
name: rl-reproduction-worker
description: Implements RL reproduction features, writes tests first, and verifies
  experiment plumbing and trend artifacts.

Selected work rules:
- For experiment features, run at least one reduced/smoke execution of the
  actual pipeline and inspect the generated artifact(s), not just tests.
- Ensure all outputs and configs use relative paths.
- Never satisfy a paper claim with fabricated tables, hardcoded rankings, or
  synthetic fallback artifacts that were not derived from executed runs.
```

Scrutiny validation layer.

```
{
  "milestone": "experiments-and-packaging",
  "round": 1,
  "status": "pass",
  "validatorsRun": {
    "test":      { "passed": true, "command": ".venv/bin/python -m pytest -q",   "exitCode": 0 },
    "typecheck": { "passed": true, "command": ".venv/bin/python -m mypy src tests","exitCode": 0 },
    "lint":      { "passed": true, "command": ".venv/bin/python -m ruff check .", "exitCode": 0 }
  },
  "reviewsSummary": { "total": 2, "passed": 2, "failed": 0, "failedFeatures": [] }
}
```

ii-sling-physics-game: adaptive worker skills and reusable guidance

Worker skill split.

```
name: game-engine-worker
description: Implements core game engine features - physics, mechanics, systems,
  UI, audio, and game logic for the ii-sling-physics-game browser game.
```

```
name: game-content-worker
description: Creates game content - level data, sprites, and audio assets for the
  ii-sling-physics-game browser game using internal reference images and specification sources.
```

Core-engine validation synthesis.

```
{
  "milestone": "core-engine",
  "round": 1,
  "status": "pass",
  "appliedUpdates": [
    { "target": "library",
      "description": "Created phaser-patterns.md documenting entity architecture pattern (pure data +
    Phaser class + back-references), Phaser timer convention, and input handling for agent-browser
    testing",
      "sourceFeature": "blocks-and-targets, slingshot-mechanics" }
  ],
  "suggestedGuidanceUpdates": [
    { "target": "skills",
      "suggestion": "Update game-engine-worker skill: (1) Add caveat that TDD is impractical for
    scaffolding features. (2) Update example handoff to reference ignoreGravity approach instead of
    Matter.js spring constraint for slingshot." }
  ]
}
```

7. Result Detail

ii-sling-physics-game

Method	Harness	Total tokens	Cost	Score
One-session	Claude	59.6 M	$37.32	0.30
One-session	Codex	11.7 M	$5.70	0.15
Ralph	Claude	2,185.5 M	$1,466.47	0.55
Ralph	Codex	881.4 M	$415.90	0.50
Plan-ralph	Claude	643.8 M	$480.39	0.35
Plan-ralph	Codex	953.8 M	$443.25	0.25
Milestone-ralph	Claude	456.1 M	$408.87	0.45
Milestone-ralph	Codex	238.8 M	$113.00	0.40
Zenith	Opus 4.6 + GPT-5.4	519.5 M	$499.77	**0.60**

Cowork

Method	Harness	Tokens (M)	Cost ($)	Score
One-session	Claude	46.3	27.95	0.3554
One-session	Codex	29.2	10.13	0.1074
Ralph	Claude	2,126.3	1,354.00	0.9504
Ralph	Codex	2,027.6	641.52	0.9256
Plan-ralph	Claude	265.0	187.08	0.6529
Plan-ralph	Codex	1,087.6	412.91	0.0661
Milestone-ralph	Claude	294.6	276.69	0.9504
Milestone-ralph	Codex	535.2	201.40	0.9422
Zenith	Opus 4.6 + GPT-5.4	589.4	171.81	**0.9587**

Ydata-profiling

Method	Harness	Tokens (M)	Cost ($)	Score
One-session	Claude	25.9	21.71	0.009166
One-session	Codex	18.3	7.18	0.03071
Ralph	Claude	569.8	377.06	0.06141
Ralph	Codex	206.1	87.84	0.055
Plan-ralph	Claude	322.7	281.99	0.05637
Plan-ralph	Codex	20.7	10.70	0.03758
Milestone-ralph	Claude	357.9	310.22	0.06505
Milestone-ralph	Codex	85.1	43.93	0.04583
Zenith	Opus 4.6 + GPT-5.4	63.7	60.05	**0.07883**

Git-To-Zig

For Git-To-Zig, we report the score at a fixed 20-hour timeout for consistency with FrontierSWE.

Method	Harness	Tokens (M)	Cost ($)	Score
One-session	Claude	27.4	25.43	0.2067
One-session	Codex	18.8	7.27	0.1514
Ralph	Claude	503.7	333.32	**0.287**
Ralph	Codex	697.9	311.67	0.2177
Plan-ralph	Claude	45.0	34.18	0.2308
Plan-ralph	Codex	403.8	215.92	0.1772
Milestone-ralph	Claude	230.7	203.39	0.2278
Milestone-ralph	Codex	634.0	279.23	0.201
Zenith	Opus 4.6 + GPT-5.4	426.6	185.39	0.2493

Chess Engine

Method	Harness	Tokens (M)	Cost ($)	Score
One-session	Claude	449.3	167.37	2,328
One-session	Codex	16.7	5.83	2,381
Ralph	Claude	443.2	256.15	**2,867**
Ralph	Codex	693.3	255.67	2,586
Plan-ralph	Claude	527.0	196.70	2,582
Plan-ralph	Codex	376.2	130.84	2,328
Milestone-ralph	Claude	139.3	154.89	2,593
Milestone-ralph	Codex	53.4	28.17	2,402
Zenith	Opus 4.6 + GPT-5.4	127.6	100.54	2,612

Web Traffic Forecasting

Score direction: *lower is better*; best human score: 0.622.

Method	Harness	Tokens (M)	Cost ($)	Score
One-session	Claude	13.7	7.67	0.9892
One-session	Codex	29.3	7.11	0.9736
Ralph	Claude	367.5	228.00	0.964
Ralph	Codex	370.3	131.21	0.954
Plan-ralph	Claude	5.6	89.90	0.987
Plan-ralph	Codex	122.6	44.00	0.962
Milestone-ralph	Claude	316.1	299.07	0.956
Milestone-ralph	Codex	130.7	54.65	0.964
Zenith	Opus 4.6 + GPT-5.4	195.7	152.01	**0.8827**

PaperBench: Rice

Method	Harness	Tokens (M)	Cost ($)	Score
One-session	Claude	21.5	8.47	0.2644
One-session	Codex	15.7	3.23	0.0846
Ralph	Claude	385.7	240.72	0.34
Ralph	Codex	429.5	113.64	**0.363**
Plan-ralph	Claude	11.0	7.45	0.2906
Plan-ralph	Codex	97.4	27.79	0.2036
Milestone-ralph	Claude	505.5	351.01	0.3031
Milestone-ralph	Codex	989.6	384.47	0.2568
Zenith	Opus 4.6 + GPT-5.4	103.5	104.14	0.342

PaperBench: FTRL

Method	Harness	Tokens (M)	Cost ($)	Score
One-session	Claude	24.3	10.35	0.184
One-session	Codex	9.2	2.58	0.0872
Ralph	Claude	346.2	182.33	0.2258
Ralph	Codex	357.7	125.71	0.2306
Plan-ralph	Claude	11.3	7.74	0.1789
Plan-ralph	Codex	40.2	13.66	0.12
Milestone-ralph	Claude	187.1	122.57	0.2219
Milestone-ralph	Codex	251.6	119.93	0.16
Zenith	Opus 4.6 + GPT-5.4	95.3	131.73	**0.2421**