

Enterprise Agentic Architecture
& Secure Coding Sandboxes
Engineering Blueprints for Vibe Coding, Swarm
Prototyping, and Autonomous Remediation (v3.0)

The Agentic Developer's Architectural Blueprint



Aligning with Google Cloud Professional Agentic Architect (PAA) specifications.

The Paradigm Shifts From Syntax To Intent


Legacy Coding



Sequential, Character-by-Character Input

Focus on How: Syntax, Formatting, Low-Level Details

Vibe Coding (Coined by Andrej Karpathy, 2025)



AI-Driven, Multi-Layered Implementation from Intent

Focus on What: Outcomes, System Design, High-Level Specs

Natural Language First:
Translating plain English specs into working software.

Intent Over Syntax:
Focus moves from how to write it to what it should do.

Human as Architect:
The developer makes design decisions, sets boundaries, and owns production quality.

The 5-Step Conversational Iteration Cycle


1. Describe: Prompting features, constraints, or bug fixes in natural language.

2. Generate: AI produces code, architecture, or components.

3. Review: Developer reads, tests, and evaluates the generated diff.

4. Refine: Follow-up prompts to fix edge cases or refactor.


5. Ship: Passing automated CI/security gates, documenting, and deploying.




Key Insight: Vibe coding amplifies expertise. The best vibe coders know exactly what to ask for and when to manually intervene.

Operating Across The Vibe Coding Spectrum

> Karpathy warns: Vibe coding in its purest form is not for production systems. Unchecked autopilot accumulates hidden technical debt and security vulnerabilities.



Swarm Prototyping Unlocks Architectural A/B Testing



Concept:

Deploying multiple AI agents simultaneously to build competing variants or decoupled microservices.

Mechanism:

Scale-by-Agents instead of serial human hours.

Outcome:

Disposable candidate code that rapidly reveals the best architectural approach.

Rule of Thumb: Use for proofs-of-concept and parallel microservices. Do not use for tightly coupled systems requiring sequential design or when merge costs exceed generation savings.

Core Roles Within A Multi-Agent Swarm



Worker Agents:
Specialized execution units (UI builder, API implementer, pytest author).


Orchestrator Agent:
Central coordinator.
Decomposes tasks, provisions isolated worktrees, assigns work.

Merger Agent:
Integrates winning outputs from multiple branches, resolving schema conflicts.

Critic / Evaluator Agent:
Reviews outputs in a clean context window, runs security suites, scores quality.


Swarm Topologies: Fan-Out & Tournament Patterns

Topology A: Fan-Out / Fan-In



One decomposable task -> split across parallel agents -> merge.

Topology B: Tournament




Deterministic test suite + critic picks the winning implementation.

Swarm Topologies: Pipeline, Grid, & Ensemble Patterns








Architectural Matrix: Vibe Coding vs. Swarm Prototyping

	Vibe Coding	Swarm Prototyping
Agents	1 Human : 1 Agent	1 Human : N Agents
Workflow	Conversational / Sequential	Parallel / Orchestrated
Context	Human maintains session	Split across subagent windows
Speed	Fast for single tasks	Faster for broad multi-service builds
Token Cost	Low	Higher (~4x-15x multiplier)
Best For	Features, bug fixes	Architecture tournaments, parallel microservices

Insight: Complementary, not competing. Use Swarms to explore ambiguous designs, and Vibe Coding to execute focused features.

The Threat Landscape Highlights The “It Works” Trap



Hidden Technical Debt:
- Duplicated imperative glue eroding modularity.

Security Blind Spots:
- SSRF, insecure deserialization, hardcoded credentials.

Slopsquatting:
- Agents hallucinating SDK methods or non-existent packages, which attackers register on PyPI/npm.

The “It Works” Trap Checklist

- [ ] Are tests generated alongside specs?
- [ ] Are dependencies verified against approved registries?
- [ ] Has performance been load-tested for tail latency? (AI optimizes for plausibility, not p99 performance).

Enterprise Sandboxing Secures The Blast Radius

Antigravity Terminal	OS-level process sandbox (`--sandbox`). Blocks .env reads. Deny > Ask > Allow precedence.
Claude Code	Sandboxed bash + `CLAUDE_CODE_USE_VERTEX=1` for IAM governance.
Cloud Workstations	Dedicated VMs, zero public IP, VPC-SC perimeters, `idleAction=SUSPEND`.
Agent Sandbox on GKE	Dedicated Kubernetes Pod per sandbox using **gVisor** (`runsc`) for untrusted execution.

`Architectural Warning:` Giving an autonomous swarm unrestricted shell access on a laptop holding production gcloud tokens creates a catastrophic blast radius.

Isolating Terminal Swarms With Git Worktrees




Operational Directives

Antigravity: Use `Workspace='branch'` in `invoke_subagent` to prevent collision. Note: Terminal Sandbox is off by default in UI presets, must toggle explicitly.

Claude Code: Spawn parallel swarm workers using `claude -w <name>`.

Result: Agents share the object store without duplicating disk space, while independently modifying files and running `pytest`.

Cloud Workstations Enforce Zero-Exfiltration Boundaries



The Idle Timeout Solution


Problem: Unattended VMs terminate during long 3-hour agent builds.

Solution: Configure `idleAction=SUSPEND` and deploy `/google/scripts/keep_alive.sh` to detect active agent PIDs.


Result: VMs hibernate to persistent disk (halting compute charges) when truly idle, resuming with terminal memory intact.

GKE Sandboxex Isolate Untrusted Code Execution

Agent Sandbox on GKE



Agent Substrate




Key Architectural Rule:

Use Agent Sandbox (gVisor) with SandboxWarmPool (<1s claim latency) for untrusted, multi-tenant code generation.


Do not use actor-based Agent Substrate when executing arbitrary LLM-generated Python/Bash that requires strict per-tenant kernel isolation.

Google AI Threat Defense Closes The Security Loop



Core Concept: Traditional SAST buries AppSec in false positives. AI Threat Defense correlates cloud runtime exposure with autonomous remediation.

Inside CodeMender: Hybrid Client-Service Architecture



The Input Mechanism (Exam Note):

- CodeMender doesn't just find its own bugs (`cm find`).
- It natively ingests third-party scanner reports (Wiz/SAST) via `cm report import --file ./findings.json` to verify and patch them.

The Exploit-Verified Autonomous Remediation Cycle

1. Find / Import

Ingesting SARIF findings.



2. Verify (cm verify)

Synthesizes and executes a concrete Proof-of-Concept (PoC) exploit in a mandatory process sandbox to trigger the vulnerability, eliminating false positives.

3. Fix (cm fix –y)

Generates multi-file patch, re-runs the PoC to assert it now fails, runs regression suites, passes LLM-as-judge, and stages a PR.

Mandatory Guardrails:

cm verify compiles live exploit payloads. It must always run in a Sandbox (Cloud Workstation, GKE gVisor). Human maintainers retain final PR merge authority.

PAA Assessment I: Swarm Architecture & Workstations

Scenario A:

A 4-agent swarm experiences .git/index.lock errors locally.

Architectural Solution:

Isolate subagents in Git worktrees (Workspace='branch' or claude -w) and enable terminal sandboxing off by default in Antigravity UI).

Scenario B:

Preventing a 3-hour agent build from dying during Cloud Workstation idle timeouts without paying 24/7 compute.

Architectural Solution:

Pair /google/scripts/keep_alive.sh with idleAction=SUSPEND to hibernate VM to disk while preserving RAM state.

PAA Assessment II: Secure Execution & CodeMender

Scenario C:

Executing untrusted AI-generated Python at scale with sub-second startup.

Architectural Solution:

Choose Agent Sandbox on GKE over Substrate. Provision dedicated gVisor (runsc) pods blocking hostNetwork, utilizing SandboxWarmPool.




Scenario D:

Resolving 65% false-positive rates from legacy SAST scanners.

Architectural Solution:

Ingest Wiz/SAST reports via **cm report import**. Use **cm verify** in an isolated sandbox to run a live PoC exploit (filtering non-exploitable bugs), followed by **cm fix** for a regression-tested PR.



The Human Evolves From Typist To Architect



Legacy code generation,
character-by-character syntax,
manual SAST triage.

The Agentic Shift.
Vibe Coding, Swarm Prototyping,
CodeMender PoC verification.

The Future State.
The human engineer standing
above the infrastructure layer.

As AI commoditizes code generation, the value of the software engineer shifts entirely to system architecture, threat modeling, and intent specification. The agent writes the code; the architect builds the enterprise shield.

Review every line. Sandbox every agent. Verify every exploit. Architect the future.