
Beyond Binary Out-of-Distribution Detection: Characterizing Distributional Shifts with Multi-Statistic Diffusion Trajectories

Achref Jaziri*
Goethe University

Martin Rogmann
Goethe University

Martin Mundt
University of Bremen

Visvanathan Ramesh
Goethe University

Abstract

Detecting out-of-distribution (OOD) data is critical for machine learning, be it for safety reasons or to enable open-ended learning. However, beyond mere detection, choosing an appropriate course of action typically hinges on the type of OOD data encountered. Unfortunately, the latter is generally not distinguished in practice, as modern OOD detection methods collapse distributional shifts into single scalar outlier scores. This work argues that scalar-based methods are thus insufficient for OOD data to be properly contextualized and prospectively exploited, a limitation we overcome with the introduction of DISC: Diffusion-based Statistical Characterization. DISC leverages the iterative denoising process of diffusion models to extract a rich, multi-dimensional feature vector that captures statistical discrepancies across multiple noise levels. Extensive experiments on image and tabular benchmarks show that DISC matches or surpasses state-of-the-art detectors for OOD detection and, crucially, also classifies OOD type, a capability largely absent from prior work. As such, our work enables a shift from simple binary OOD detection to a more granular detection.

1 INTRODUCTION

In the real world, distribution shifts are the norm rather than the exception (Quiñonero-Candela et al., 2022). Predictive models are commonly used on test

data which are drawn from distributions that differ from the training data, such as images acquired with a different protocol or a population change (Amodei et al., 2016). These settings highlight the importance of building models that are robust to natural transformations (Hendrycks et al., 2018). Two prevalent strategies exist for dealing with distribution shifts: improving model generalization or detecting the shifts themselves (Zhou et al., 2022; Hendrycks and Gimpel, 2016). In this context, detecting out-of-distribution (OOD) data has become increasingly popular by training supervised predictive models or generative models on in-distribution data and examining some proxy features.

However, not all flagged shifts are and should be treated equally. Some shifts may indicate corrupted or irrelevant data that should be discarded, while others may represent opportunities for model adaptation and continual learning (Mundt et al., 2023; Wang et al., 2024). This raises a critical question: *are current OOD detection methods able to distinguish between different types of distribution shifts beyond the mere detection of a shift’s existence?*

For intuition, consider a standard image setting with CIFAR-10 (Krizhevsky et al., 2009) as in-distribution and two OOD regimes: covariate corruptions and semantic shifts (e.g., unseen classes like butterflies). While several methods perform very well in the standard ID vs OOD setting, they remain fundamentally limited in their ability to distinguish between different types of shifts, a point we will quantify later. This is in part because scalar OOD scores conflate heterogeneous shifts. For instance, the theoretically sound family of open-set recognition methods aims to distinguish OOD samples by quantifying bounds on the “known” space, i.e., the closed set (Boult et al., 2019). These approaches are typically brought into practice by defining compact abating probabilities—measures that decay probabilities of decisions towards zero when moving beyond the training data support (Scheirer et al., 2012, 2014). In similar spirit, generative approaches predominantly employ measures of statistical

*Correspondence: Jaziri@em.uni-frankfurt.de

(dis-)similarity, decaying the likelihood of data away from the fitted training density (Kirsch et al., 2021). By definition, either of these approaches considers all OOD samples to be fundamentally the same, failing to capture the nuanced differences between various types of distributional shifts (see Figure 1 as an example).




Figure 1: Simplified illustration to highlight that standard out-of-distribution (OOD) detection methods typically fail to differentiate between the distinct types of shift. In the example, density or distance-based methods would collapse their scores and conflate the two kinds of OOD samples. Reasoning of failure modes for other methods follows analogously.

This work thus seeks to move beyond the traditional binary classification of inputs as simply "in" or "out" of distribution. We first corroborate above mentioned observations empirically and show that the difficulty in distinguishing between different types of OOD stems from common limitations of existing methods. We further demonstrate theoretically that this limitation is inherent to any approach using a single test statistic, as it necessarily collapses the multidimensional nature of distributional differences into a single dimension. Finally, we propose a method based on denoising diffusion probabilistic models (DDPMs) (Ho et al., 2020) that addresses these limitations. Our introduced scoring approach captures discrepancies at multiple levels of abstraction, enabling us to disentangle different types of distributional shifts for different data modalities.

2 PRELIMINARIES AND BACKGROUND

We formalize the taxonomy used throughout the paper. The following subsections fix notation, define shift types, and review OOD detection approaches.

2.1 Preliminaries: OOD Detection

We assume a standard supervised learning setting in which each training pair (x_i, y_i) is drawn i.i.d. from a joint distribution $P_{\text{id}}(X, Y)$ over $\mathcal{X}_{\text{id}} \times \mathcal{Y}_{\text{id}}$, where $\mathcal{X}_{\text{id}} \subset \mathcal{X}$ is the input space of in-distribution (ID) data and $\mathcal{Y}_{\text{id}} = \{1, 2, \dots, K\}$ is the set of known class labels. We denote by $P = P_{\text{id}}$ the marginal distribution of X restricted to $\mathcal{X}_{\text{id}}$. In its most general form, OOD detection can be framed as a single-sample hypothesis test (Nalisnick et al., 2018). Let $\mathcal{Q}$ denote a family of candidate out-of-distribution alternatives, with $P \notin \mathcal{Q}$. Given a sample x , the goal is to decide between $H_0 : x \sim P$ and $H_A : x \sim Q$, $Q \in \mathcal{Q}$.

The decision is based on a predetermined test statistic $\phi : \mathcal{X} \rightarrow \mathbb{R}$ which can be any (measurable) function of the single sample x . Commonly, one rejects H_0 (i.e. declares x to be OOD) if $\phi(x) < k$ for some threshold k . In practice, one may define a test statistic $\phi(x)$ and reject H_0 whenever $\phi(x) < \tau$. The goal is that $\phi(x)$ be well-separated on $\mathcal{X}_{\text{id}}$ versus $\mathcal{X}_{\text{ood}}$, so that novel or shifted inputs are flagged as OOD with high reliability.

2.2 Types of Out-of-Distribution Shifts

The space of out-of-distribution inputs $\mathcal{X}_{\text{ood}} = \mathcal{X} \setminus \mathcal{X}_{\text{id}}$ can be decomposed into several subsets that correspond to distinct types of distributional shifts. These shifts affect either the marginal distribution of inputs, the label distribution, or the semantic content as prominently defined by Quinero et. al (Quiñonero-Candela et al., 2022).

In this work, we focus on covariate and semantic shifts because they act directly on the input distribution, either altering its geometry/texture or introducing novel concepts. We thus most directly test an OOD detector’s ability to reason about features and semantics at inference time. Label shifts primarily reflect downstream curation effects, such as class reweighting, later editing, or mislabeling, rather than changes in the support or geometry of the input distribution. They also require different assumptions and estimation tools and are therefore beyond our present scope.

Covariate Shift occurs when the distribution of inputs changes while the conditional label distribution remains unchanged. In this case, the support of $\mathcal{X}_{\text{test}}$ includes regions that are disjoint from $\mathcal{X}_{\text{id}}$, i.e., $\mathcal{X}_{\text{ood}}^{\text{cov}} \subset \mathcal{X}_{\text{ood}}$. Examples include shifts in background, sensor characteristics, or adversarial perturbations.

Semantic Shift denotes the appearance of novel classes not seen during training. In this case, test inputs from these unseen classes lie in a subset $\mathcal{X}_{\text{ood}}^{\text{sem}} \subset \mathcal{X}_{\text{ood}}$, and their associated labels belong to $\mathcal{Y}_{\text{ood}} = \mathcal{Y}_{\text{test}} \setminus \mathcal{Y}_{\text{id}}$. This is the canonical setting for open-set

recognition and novelty detection (Scheirer et al., 2012; Pimentel et al., 2014).

Our primary emphasis is on *differences within* a given shift type, rather than only contrasting covariate versus semantic shifts as a whole, as interventions and risks differ across families even within the same type (e.g., in continual settings: denoise vs. throw away vs. retrain). We therefore treat each corruption or dataset as a distinct OOD family.

2.3 OOD Score Computation

Regardless of the modeling choice, most modern OOD detectors compress the evidence for an input x into a *single* scalar and apply a common decision rule, $\delta(x) = \mathbb{1}[o(x) \geq \tau]$. What differs is *where* this evidence comes from: the prediction space, the representation space, or a generative model, and whether it is further reshaped at test time. We categorize representative methods through this lens: **Output-score based**. These methods derive $o(x)$ from classifier outputs without modeling density. Canonical choices include maximum softmax probability (MSP), predictive entropy (Hendrycks and Gimpel, 2016), and the energy score $o_E(x) = -\log \sum_c \exp f_c(x)$. The latter avoids softmax normalization and often improves separation (Liu et al., 2020). Calibration can be improved by ODIN (temperature scaling + small input perturbations) or Outlier Exposure (OE), which penalizes overconfidence on auxiliary outliers (Hsu et al., 2020; Hendrycks et al., 2018). Ensembles and MC-Dropout further encourage uncertainty on unfamiliar inputs (Lakshminarayanan et al., 2017; Gal and Ghahramani, 2016).

Feature-based. These methods compute $o(x)$ from layer embeddings $z(x)$. Class-conditional (Mahalanobis) distances and related prototype distances measure how far $z(x)$ lies from ID clusters; nearest-neighbor variants estimate isolation in feature space (Lee et al., 2018; Ren et al., 2021; Sun et al., 2022). Activation-shaping improves these signals at test time: ReAct truncates extreme activations, DICE clips activations dynamically, and ASH uses asymmetric clipping; each can be paired with logit- or feature-based scores (Sun et al., 2021; Sun and Li, 2022; Djurjic et al., 2022). Gradient/sensitivity cues (e.g., Grad-Norm) and Fisher-style approximations also correlate with being off-manifold (Huang et al., 2021; Dauncey et al., 2024).

Generative: density and reconstruction methods. Explicit likelihood models (PixelCNN++, Glow) set $o(x) = -\log p(x)$ (Salimans et al., 2017; Kingma and Dhariwal, 2018). However, raw likelihood can mis-rank OOD due to sensitivity to low-level statis-

tics (Nalisnick et al., 2018; Zhang et al., 2021). Reconstruction methods (VAEs; diffusion) score via $\|x - r(x)\|$, or via typicality surrogates. Recent diffusion-based detectors leverage denoising trajectories, inpainting errors, and noisy-denoised feature mismatches to boost performance without labels (Graham et al., 2023; Livernoche et al., 2023; Liu et al., 2023; Heng et al., 2024; Yang et al., 2024; Oko et al., 2023).

Inference-modifying and augmentation-based. Beyond fixed scoring, many methods perturb inputs or internal activations to widen ID/OOD separation at test time—ODIN-style input nudges or activation clipping are typical examples (Hsu et al., 2020; Sun et al., 2021; Sun and Li, 2022).

Strong systems often *combine* components (e.g., activation shaping + energy; Mahalanobis on features from a diffusion backbone). Yet there are trade-offs between “near” and “far” OOD, and no single score performs well across all regimes (Guille-Escuret et al., 2024; Zhang et al., 2021; Li et al., 2025). Finite-sample effects and high dimensionality further complicate separation (Ghosal et al., 2024; Aggarwal et al., 2001). Recent impossibility results show OOD detection is not distribution-free PAC-learnable in general; learnability requires structure relating ID and OOD or restrictions on hypothesis spaces (Fang et al., 2022; Garov and Chaudhuri, 2025).

3 MOTIVATING OBSERVATIONS

In this section, we first present the empirical observations that motivate our work, then link them to design choices in current OOD detectors, and finally corroborate them with a theoretical non-identifiability result showing the limits of standard OOD tests.

3.1 Score Distributions Align Across OODs

To examine how existing OOD detectors respond to diverse out-of-distribution inputs, we analyze OOD detection scores for multiple datasets on a shared CIFAR-10 in-distribution base. Figure 2 displays representative histograms for Mahalanobis (with and without ODIN), Energy-based scoring, and SHE (Zhang et al., 2022). Across methods, each OOD family produces a clear shift away from the ID mode; however, the OOD histograms *overlap heavily* with one another. Consistent with this, standard ID-vs-OOD AUROC remains high across detectors (Figure 3), When we ask *which* OOD family a sample belongs to, accuracy drops markedly in both unsupervised (K-means) and supervised (MLP) settings (Figure 4).

The *relative* positions of the different OOD types are also strikingly similar across methods: CIFAR-FGSM




Figure 2: OOD scores overlap significantly for different OOD types for models trained on CIFAR-10 as in-distribution. This observation is independent of the employed OOD detector (panels a-c).




Figure 3: AUROC in the standard OOD detection setting across various OOD types remains high across detectors (x-axis) for models trained on CIFAR-10.

and CIFAR-Flip cluster closer to the ID peak, whereas *Butterflies* and *MNIST* are scored as more novel. This consistency holds for logit-based (Energy), feature-distance (Mahalanobis), and score-normalized embedding (SHE) approaches.

3.2 Constraints of Current OOD Detectors

The empirical regularity found in the previous subsection points to a deeper issue: most existing approaches rely on scoring functions that are inherently scalar and coarse. They fail to disentangle between different shifts. Fundamentally, these scalar approaches collapse the multidimensional nature of distributional differences into a single dimension, typically following some form of exponential or heavy-tailed distribution that tends to be unimodal. This dimensionality reduction pushes all different types of OOD inputs toward the extremes or tails of the score distribution, making distinguishing between them impossible regardless of their underlying structural differences.

Moreover, supervised models are trained to minimize classification error on in-distribution data and are not optimized to assess distributional membership. As a result, they conflate discriminative uncertainty (i.e., uncertainty over class labels) with epistemic uncer-




Figure 4: OOD-type classification accuracy (using unsupervised K-means and supervised MLP approaches) is substantially worse when compared to traditional binary OOD-detection, as presented in Figure 3.

tainty about the underlying data distribution. This conflation induces irreducible errors, particularly in near-OOD regimes, where samples lie in ambiguous feature regions or closely resemble in-distribution examples. However, the distance to the boundary does not tell us the nature of the shift.

Generative models aim to capture the data distribution $p(x)$ and are thus often viewed as more principled for OOD detection. However, methods that rely solely on the likelihoods produced by these models inherit their own fundamental limitations. The quantity $p(x)$ does not provide direct access to the decision-relevant posteriors $p(\text{OOD}_i | x)$, where OOD_i denotes a specific type of out-distribution. In other words, a high likelihood under $p(x)$ does not imply low novelty across all possible modes of OOD variation, nor does it allow discrimination between different types of OOD inputs.

Typicality-based methods attempt to mitigate this mismatch by testing whether a sample lies in a high-probability region of the estimated distribution $p(x)$, rather than relying solely on its likelihood value. However, these methods still reduce the input to a scalar

test statistic $\phi_p(x) : \mathcal{X} \rightarrow \mathbb{R}$, using some sort of exponential distribution, effectively projecting the high-dimensional input space onto a one-dimensional axis.

3.3 Non-Identifiability Under Singular Test-static: A Theoretical Result

Prior work (Zhang et al., 2021) formalizes a fundamental limitation of scalar-valued test statistics in the context of single-sample out-of-distribution detection. They show that for any test statistic $\phi_p : \mathcal{X} \rightarrow \mathbb{R}$, if the conditional distribution $P(X | \phi_p(X) = t)$ is non-degenerate on a set of nonzero measure, then there exists an alternative distribution $Q \neq P$ such that $\phi_p(X) \sim Q = \phi_p(X) \sim P$. Consequently, any test relying solely on $\phi_p(x)$ cannot distinguish between P and such alternatives, and has power equal to the false positive rate. Extending this proposition, we show that multiple, distinct distributions can induce the same distribution over $\phi_p(X)$, rendering them mutually indistinguishable under any test based solely on $\phi_p(x)$:

Proposition. *Let P be a probability measure on a sample space $\mathcal{X}$ and let $\phi_p : \mathcal{X} \rightarrow \mathbb{R}$ be any (measurable) test statistic. Suppose there exists a measurable set $\Phi_0 \subseteq \text{Range}(\phi_p)$ with $P(\phi_p(X) \in \Phi_0) > 0$ such that, for almost every $\phi \in \Phi_0$, the conditional law $P(\cdot | \phi_p(X) = \phi)$ is non-degenerate (i.e. not a point mass). Then, there exist two distributions Q_1 and Q_2 such that $Q_1 \neq P$, $Q_2 \neq P$, and $Q_1 \neq Q_2$, yet all three distributions induce the same distribution over $\phi_p(X)$; specifically, $\phi_p(X) \sim Q_1 = \phi_p(X) \sim Q_2$. As a result, any test that relies solely on the value of $\phi_p(x)$ has power equal to the false positive rate, and therefore cannot distinguish between Q_1 and Q_2 .*

Proof Sketch. See the Appendix A for the full proof. The proof sketch is as follows: We construct two distributions, Q_1 and Q_2 , that are distinct from P and each other, yet produce the exact same marginal distribution for the statistic $\phi_p(X)$. The strategy is to identify a set of statistic values, Φ , where the conditional distribution $P(X | \phi_p(X) = \phi)$ is not concentrated on a single point (non-degenerate Condition). For each $\phi \in \Phi$, this non-degeneracy allows us to find at least two disjoint subsets of the outcome space, A_ϕ and B_ϕ , which both have positive conditional probability. We then define new conditional distributions, $q_1(x | \phi)$ and $q_2(x | \phi)$. For $\phi \in \Phi$, these new distributions slightly re-weight the probability mass between the sets A_ϕ and B_ϕ . For any $\phi \notin \Phi$, we leave the conditional distribution unchanged ($q_i(x | \phi) = p(x | \phi)$). Finally, we construct the full distributions Q_1 and Q_2 by combining these new conditional distributions with the original marginal density of $\phi_p(X)$. This procedure guarantees that the marginal law of $\phi_p(X)$ is identi-

cal under P , Q_1 , and Q_2 , while the joint distributions are provably different. Any test that depends only on $\phi_p(X)$ therefore attains identical rejection probabilities under all three measures, so its power equals its false-positive rate.

4 SCORE-BASED GENERATIVE MODELS FOR MULTI-DIMENSIONAL OOD DETECTION

In this section, we first motivate the use of score-based generative models to expose structure across noise levels. We then introduce our suggested approach, *DISC*, which replaces a single anomaly score with a multi-statistic embedding. We conclude by specifying the metric suite and feature construction for both images and tabular data.

4.1 Motivation

A fundamental challenge in OOD detection is that the separability of in- and out-of-distribution samples depends on where in the pipeline one looks—input, latent, or output space. Certain classes of OOD samples can appear indistinguishable in one space but clearly deviate in another. For example, adversarial samples are nearly identical to normal ones in input space but induce drastically different activations in latent and output space. Conversely, perturbations like adding a few black pixels produce negligible changes in latent or output representations, despite being clearly anomalous at the input level. More generally, if a model is invariant to the features responsible for a given shift, then examining a single representational space will inevitably collapse certain classes of OOD. This observation explains why adversarial detection methods have often been treated as a separate research branch (Metzen et al., 2017).

The limitations of scalar-based detection methods motivate a shift toward richer, multi-dimensional characterizations of distributional shift. We adopt score-based generative models (Song et al., 2020) as the foundation for this approach: *their iterative denoising process decomposes data generation across multiple timesteps, naturally exposing both coarse semantic structure and fine-grained statistical details.*

To motivate with an example (Figure 5): when training on butterflies, the Structural Similarity Index (SSIM) (Wang et al., 2004) separates naturalistic shifts such as flip or black occlusion from in-distribution samples, reflecting divergence in structural coherence. A perceptual metric like LPIPS (Zhang et al., 2018), on the other hand, highlights a complementary per-




Figure 5: (a) Average SSIM vs. diffusion timestep. When trained on butterflies, SSIM highlights the structural separation of naturalistic shifts (e.g., flip, black occlusion) from in-distribution samples as denoising progresses. (b) Average LPIPS vs. diffusion timestep. Perceptual similarity score for different distribution shifts show different trends over time, revealing the importance of time-expanded information in capturing differences across OOD types.

spective: perceptual similarity decreases more sharply for certain datasets (e.g., CIFAR) while remaining comparatively stable for others (e.g., black occlusion), with these contrasts becoming more pronounced at later timesteps. Taken together, SSIM and LPIPS illustrate a complementary effect that motivates the design of DISC, which explicitly integrates diverse metrics across the diffusion trajectory to achieve a more comprehensive characterization of distributional shift.

4.2 DISC: Diffusion-based Statistical Characterization for OOD Detection

Score-based generative models (Sohl-Dickstein et al., 2015; Song et al., 2020) learn to approximate the score

function $\nabla \log p(x)$ by training a family of denoisers $\{D_\sigma\}$ at varying noise levels. Beyond generative sampling, score-based generative models offer a principled framework for constructing a collection of test statistics that address the limitations of scalar-valued detectors.

Given a clean sample $x_0 \sim p(x)$, Gaussian perturbations produce noisy versions $x_\sigma \sim \mathcal{N}(x_0, \sigma^2 I)$. At each noise level σ , the model learns a denoiser $D_\sigma(x_\sigma)$ that estimates the posterior mean $\mathbb{E}[x | x_\sigma]$, or equivalently, the score function $\nabla \log p_\sigma(x_\sigma)$ via Tweedie’s formula (Efron, 2011). This leads to a family of estimators $\{D_\sigma\}_{\sigma \in \Sigma}$, each associated with a different degree of corruption and thus encoding distinct information.

At sampling time, these learned score functions are employed to reverse the diffusion process and generate samples from the underlying clean distribution $p(x)$ via a discretized reverse diffusion procedure.

This decomposition across noise levels naturally induces a set of test statistics, each conditioned on σ , which compare forward-diffused samples $x_\sigma \sim p(x_\sigma | x)$ to their corresponding reconstructions $D_\sigma(x_\sigma)$.

Rather than relying on a single test statistic $\phi(x)$, we propose a more general *multi-statistic framework* that leverages a collection of complementary metrics. For each noise level $\sigma \in \Sigma$, we define

$$\phi_\sigma^{(m)}(x) = d^{(m)}(x_\sigma, D_\sigma(x_\sigma)), \quad m = 1, \dots, M,$$

where each discrepancy $d^{(m)}$ captures a distinct view of the data manifold (e.g. pixel fidelity, perceptual quality, structural integrity, or distributional statistics). Aggregating these M metrics across all $N = |\Sigma|$ levels yields the embedding

$$s(x) = [\{\phi_{\sigma_i}^{(m)}(x)\}_{m=1}^M]_{i=1}^N \in \mathbb{R}^{NM}.$$

which serves as the input for various downstream OOD tasks. As mentioned, we refer to this framework as DISC: Diffusion-based Statistical Characterization.

4.3 Complementary Metrics to Distinguish Different Types of OOD

The central question is how to select a collection of test statistics that enables *fine-grained* OOD detection. The choice of metrics depends on the data modality and on the specific shifts we aim to disentangle. Our guiding principle is to probe complementary manifestations of shift—pixel-level deviations, local structure, perceptual change, representation stability, and texture/frequency statistics. The goal is a *partially orthogonal* set rather than a single “best” score.

At each noise level σ_i , we evaluate four metrics on the noisy input x_{σ_i} and its denoised estimate $\hat{x}_{\sigma_i}$:

Mean Squared Error (MSE) captures pixel-level deviations; Learned Perceptual Image Patch Similarity (LPIPS) (Zhang et al., 2018) measures discrepancies in deep feature space, reflecting higher-level, perceptual changes; the Structural Similarity Index (SSIM) (Wang et al., 2004) assesses local luminance, contrast, and texture fidelity; and Local Complexity (LC) (Humayun et al., 2024b,a) quantifies the stability of intermediate representations under small perturbations.

Metrics computed in learned feature spaces (e.g., perceptual distances) inherit the invariances of their networks and training datasets. While beneficial for the in-distribution, these invariances can create "blind spots" (Li et al., 2025): if the model down-weights texture, fine-scale frequency content, or mild geometric warps, distances in that space may not detect shifts expressed along those factors. To mitigate this, we pair learned metrics with specification-driven, *non-learned* descriptors (in this case texture and frequency statistics). The resulting trajectory vector is more disentangled, less sensitive to dataset-specific invariances.

Texture and frequency descriptors (e.g., Local Binary Patterns (Pietikäinen, 2010) and Discrete Wavelet Transform bands (Heil and Walnut, 1989)) provide orthogonal information by capturing fine-grained patterns, spectral energy distributions, and orientation structure that are often invisible to pixel- or feature-level distances (Jaziri et al., 2024; Ditzel et al., 2025). Accordingly, in parallel we extract these descriptors from x_{σ_i} and $\hat{x}_{\sigma_i}$. For each descriptor type, we construct normalized histograms h_{σ_i} and $\hat{h}_{\sigma_i}$ with K bins per sample and ϵ -smoothing for numerical stability, and compare them using the Kullback–Leibler divergence. These divergences are included in $s(x)$.

For tabular data, where perceptual and texture descriptors are not meaningful, we apply the same principle: augment reconstruction error with a structural consistency measure to obtain richer and more discriminative anomaly scores. Concretely, we use standard MSE for pointwise deviations and *Reconstruction Rank-Order Consistency* (Singh et al., 2008) to evaluate whether pairwise feature orderings are preserved between x and $\hat{x}$. MSE reflects absolute reconstruction fidelity, while rank consistency exposes structural misalignments that purely distance-based scores may miss.

Nonetheless, it is important to emphasize that we do not claim these metrics are optimal for all datasets. Rather, the choice of scores should be guided by the types of shifts most relevant to a given application. For our considered datasets, metrics spanning multiple representational levels are particularly well-motivated.

5 EXPERIMENTS

In this section, we evaluate DISC on image and tabular benchmarks. We begin by detailing the datasets, models, and evaluation protocols, then present and discuss empirical results, examining standard ID-vs-OOD detection as well as OOD-type separability.

5.1 Experimental Set-Up

We adopt the Variance Preserving formulation (as in DDPMs (Ho et al., 2020)), which interpolates between the data distribution and a fixed-variance Gaussian. By concatenating the reconstruction-error and histogram-based statistics across all noise levels, we obtain a high-dimensional feature vector $s(x)$. We evaluate this embedding under three different settings:

1. **Unsupervised anomaly detection:** using an IForest (Liu et al., 2008) fitted exclusively on in-distribution feature vectors to assign anomaly scores.
2. **Unsupervised clustering:** using K-means with the number of clusters fixed to the number of OOD categories, assessing whether distinct shifts can be separated without labels.
3. **Supervised classification:** using a two-layer MLP trained on held-out in-distribution and OOD samples from different categories of Distribution shifts, measuring performance when limited supervision is available.

This evaluation framework probes the richness and disentanglement of the multi-statistic embedding $s(x)$: the first scenario aligns with the standard OOD detection setting, while the latter two allow us to investigate whether the representation supports finer-grained discrimination of diverse distributional shifts. Our aim here is not merely to maximize raw performance, but to characterize the type of information encoded in $s(x)$ under different conditions. To control for the dimensionality advantage of DISC, we also form a feature-rich baseline ('All detectors'). This concatenates the outputs of several strong scalar OOD scores into a single feature vector. We then apply identical protocols on this concatenated vector.

5.2 Image Analysis

We empirically corroborate our hypothesis on the usefulness of a multi-statistic design with experiments on ImageNet and CIFAR-10. Recall that our central claim is that time-expanded reconstructions, when

methods. The consistent gain over the MSE-only approach underscores the value of structural consistency: distributional shifts often disrupt feature relationships without large absolute errors, which further illustrates the importance of multi-statistic time-expanded reconstruction as a base framework.

6 CONCLUSION

We presented DISC: diffusion-based statistical characterization. DISC draws motivation from the observation that scalar detectors collapse heterogeneous shifts. As an alternative, DISC thus extracts complementary signals from diffusion trajectories to separate OOD families that classic scores tend to conflate. Across image and tabular benchmark corroboration, DISC yields consistent gains in standard ID-vs-OOD detection and, crucially, is able to classify *which* OOD family a sample belongs to. A natural trade-off of DISC is computational cost. Because it relies on denoising evaluations across multiple noise levels and on a richer metric suite, its inference cost is higher than that of standard single-pass scalar detectors. In this sense, DISC is better viewed alongside higher-cost uncertainty estimators such as Deep Ensembles or Monte Carlo Dropout, which also trade additional inference computation for improved uncertainty signals. Our results suggest that this added overhead is justified when the goal extends beyond binary rejection and toward OOD type characterization: unlike standard detectors, DISC provides a representation that supports both competitive binary detection and substantially stronger separation between distinct OOD families.

Overall, our work challenges the prevailing paradigms of OOD detection, which we demonstrate is fundamentally limited both empirically and theoretically. We hope that our work inspires a move beyond the simple ID-vs-OOD setting toward richer open-world evaluations and enable systems that reason about the *nature* of novelty.

Acknowledgments

This work was supported by the KIBA Project (Künstliche Intelligenz und diskrete Beladeoptimierungsmodelle zur Auslastungssteigerung im Kombinierten Verkehr - KIBA) under reference number 45KI16E051, funded by the German Ministry of Transportation.

References

Aggarwal, C. C., Hinneburg, A., and Keim, D. A. (2001). On the surprising behavior of distance met-

rics in high dimensional space. In *International conference on database theory*, pages 420–434. Springer.

Amodei, D., Olah, C., Steinhardt, J., Christiano, P., Schulman, J., and Mané, D. (2016). Concrete problems in ai safety. *arXiv preprint arXiv:1606.06565*.

Boult, T. E., Cruz, S., Dhamija, A. R., Gunther, M., Henrydoss, J., and Scheirer, W. J. (2019). Learning and the unknown: Surveying steps toward open world recognition. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, pages 9801–9807.

Dauncey, S., Holmes, C., Williams, C., and Falck, F. (2024). Approximations to the fisher information metric of deep generative models for out-of-distribution detection. *arXiv preprint arXiv:2403.01485*.

Ditzel, S., Jaziri, A., Pliushch, I., and Ramesh, V. (2025). Uncertainty-aware decomposed hybrid networks. *arXiv preprint arXiv:2503.19096*.

Djurisic, A., Bozanic, N., Ashok, A., and Liu, R. (2022). Extremely simple activation shaping for out-of-distribution detection. *arXiv preprint arXiv:2209.09858*.

Efron, B. (2011). Tweedie’s formula and selection bias. *Journal of the American Statistical Association*, 106(496):1602–1614.

Fang, Z., Li, Y., Lu, J., Dong, J., Han, B., and Liu, F. (2022). Is out-of-distribution detection learnable? *Advances in Neural Information Processing Systems*, 35:37199–37213.

Gal, Y. and Ghahramani, Z. (2016). Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *international conference on machine learning*, pages 1050–1059. PMLR.

Garov, K. and Chaudhuri, K. (2025). A closer look at the learnability of out-of-distribution (ood) detection. *arXiv preprint arXiv:2501.08821*.

Ghosal, S. S., Sun, Y., and Li, Y. (2024). How to overcome curse-of-dimensionality for out-of-distribution detection? In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 19849–19857.

Graham, M. S., Pinaya, W. H., Tudosi, P.-D., Nachev, P., Ourselin, S., and Cardoso, J. (2023). Denoising diffusion models for out-of-distribution detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2948–2957.

Guille-Escuret, C., Noël, P.-A., Mitliagkas, I., Vazquez, D., and Monteiro, J. (2024). Expecting the unexpected: Towards broad out-of-distribution

- detection. *Advances in Neural Information Processing Systems*, 37:130953–130976.
- Han, S., Hu, X., Huang, H., Jiang, M., and Zhao, Y. (2022). Adbench: Anomaly detection benchmark. *Advances in neural information processing systems*, 35:32142–32159.
- Heil, C. E. and Walnut, D. F. (1989). Continuous and discrete wavelet transforms. *SIAM review*, 31(4):628–666.
- Hendrycks, D. and Gimpel, K. (2016). A baseline for detecting misclassified and out-of-distribution examples in neural networks. *arXiv preprint arXiv:1610.02136*.
- Hendrycks, D., Mazeika, M., and Dietterich, T. (2018). Deep anomaly detection with outlier exposure. *arXiv preprint arXiv:1812.04606*.
- Heng, A., Soh, H., et al. (2024). Out-of-distribution detection with a single unconditional diffusion model. *Advances in Neural Information Processing Systems*, 37:43952–43974.
- Ho, J., Jain, A., and Abbeel, P. (2020). Denoising diffusion probabilistic models. *Advances in neural information processing systems*, 33:6840–6851.
- Hsu, Y.-C., Shen, Y., Jin, H., and Kira, Z. (2020). Generalized odin: Detecting out-of-distribution image without learning from out-of-distribution data. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10951–10960.
- Huang, R., Geng, A., and Li, Y. (2021). On the importance of gradients for detecting distributional shifts in the wild. *Advances in Neural Information Processing Systems*, 34:677–689.
- Humayun, A. I., Amara, I., Vasconcelos, C., Ramachandran, D., Schumann, C., He, J., Heller, K., Farnadi, G., Rostamzadeh, N., and Havaei, M. (2024a). What secrets do your manifolds hold? understanding the local geometry of generative models. *arXiv preprint arXiv:2408.08307*.
- Humayun, A. I., Balestrieri, R., and Baraniuk, R. (2024b). Deep networks always grok and here is why. *arXiv preprint arXiv:2402.15555*.
- Jaziri, A., Ditzel, S., Pliushch, I., and Ramesh, V. (2024). Representation learning in a decomposed encoder design for bio-inspired hebbian learning. In *European Conference on Computer Vision*, pages 203–213. Springer.
- Kingma, D. P. and Dhariwal, P. (2018). Glow: Generative flow with invertible 1x1 convolutions. *Advances in neural information processing systems*, 31.
- Kirchheim, K., Filax, M., and Ortmeier, F. (2022). Pytorch-ood: A library for out-of-distribution detection based on pytorch. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4351–4360.
- Kirsch, A., Rainforth, T., and Gal, Y. (2021). Test distribution-aware active learning: A principled approach against distribution shift and outliers. *arXiv preprint arXiv:2106.11719*.
- Krizhevsky, A., Nair, V., and Hinton, G. (2009). Cifar-10 (canadian institute for advanced research). *Technical Report*.
- Lakshminarayanan, B., Pritzel, A., and Blundell, C. (2017). Simple and scalable predictive uncertainty estimation using deep ensembles. *Advances in neural information processing systems*, 30.
- Lee, G. R., Gommers, R., Waselewski, F., Wohlfahrt, K., and O217;Leary, A. (2019). Pywavelets: A python package for wavelet analysis. *Journal of Open Source Software*, 4(36):1237.
- Lee, K., Lee, K., Lee, H., and Shin, J. (2018). A simple unified framework for detecting out-of-distribution samples and adversarial attacks. *Advances in neural information processing systems*, 31.
- Li, Y. L., Lu, D., Kirichenko, P., Qiu, S., Rudner, T. G., Bruss, C. B., and Wilson, A. G. (2025). Out-of-distribution detection methods answer the wrong questions. *arXiv preprint arXiv:2507.01831*.
- Liu, F. T., Ting, K. M., and Zhou, Z.-H. (2008). Isolation forest. In *2008 eighth ieee international conference on data mining*, pages 413–422. IEEE.
- Liu, L., Ren, Y., Lin, Z., and Zhao, Z. (2022). Pseudo numerical methods for diffusion models on manifolds. *arXiv preprint arXiv:2202.09778*.
- Liu, W., Wang, X., Owens, J., and Li, Y. (2020). Energy-based out-of-distribution detection. *Advances in neural information processing systems*, 33:21464–21475.
- Liu, Z., Zhou, J. P., Wang, Y., and Weinberger, K. Q. (2023). Unsupervised out-of-distribution detection with diffusion inpainting. In *International Conference on Machine Learning*, pages 22528–22538. PMLR.
- Livernoche, V., Jain, V., Hezaveh, Y., and Ravanbakhsh, S. (2023). On diffusion modeling for anomaly detection. *arXiv preprint arXiv:2305.18593*.
- Metzen, J. H., Genewein, T., Fischer, V., and Bischoff, B. (2017). On detecting adversarial perturbations. *arXiv preprint arXiv:1702.04267*.
- Mundt, M., Hong, Y., Pliushch, I., and Ramesh, V. (2023). A wholistic view of continual learning with

- deep neural networks: Forgotten lessons and the bridge to active and open world learning. *Neural Networks*, 160:306–336.
- Nalisnick, E., Matsukawa, A., Teh, Y. W., Gorur, D., and Lakshminarayanan, B. (2018). Do deep generative models know what they don’t know? *arXiv preprint arXiv:1810.09136*.
- Nichol, A. Q. and Dhariwal, P. (2021). Improved denoising diffusion probabilistic models. In *International conference on machine learning*, pages 8162–8171. PMLR.
- Oko, K., Akiyama, S., and Suzuki, T. (2023). Diffusion models are minimax optimal distribution estimators. In *International Conference on Machine Learning*, pages 26517–26582. PMLR.
- Pietikäinen, M. (2010). Local binary patterns. *Scholarpedia*, 5(3):9775.
- Pimentel, M. A., Clifton, D. A., Clifton, L., and Tarassenko, L. (2014). A review of novelty detection. *Signal processing*, 99:215–249.
- Pinaya, W. H., Graham, M. S., Kerfoot, E., Tudosi, P.-D., Dafflon, J., Fernandez, V., Sanchez, P., Wolleb, J., Da Costa, P. F., Patel, A., et al. (2023). Generative ai for medical imaging: extending the monai framework. *arXiv preprint arXiv:2307.15208*.
- Quiñonero-Candela, J., Sugiyama, M., Schwaighofer, A., and Lawrence, N. D. (2022). *Dataset shift in machine learning*. Mit Press.
- Ren, J., Fort, S., Liu, J., Roy, A. G., Padhy, S., and Lakshminarayanan, B. (2021). A simple fix to mahalnobis distance for improving near-ood detection. *arXiv preprint arXiv:2106.09022*.
- Riba, E., Mishkin, D., Ponsa, D., Rublee, E., and Bradski, G. (2020). Kornia: an open source differentiable computer vision library for pytorch. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 3674–3683.
- Rozsa, A. and Boulton, T. E. (2019). Improved adversarial robustness by reducing open space risk via tent activations. *arXiv preprint arXiv:1908.02435*.
- Salimans, T., Karpathy, A., Chen, X., and Kingma, D. P. (2017). Pixelcnn++: Improving the pixelcnn with discretized logistic mixture likelihood and other modifications. *arXiv preprint arXiv:1701.05517*.
- Scheirer, W. J., de Rezende Rocha, A., Sapkota, A., and Boulton, T. E. (2012). Toward open set recognition. *IEEE transactions on pattern analysis and machine intelligence*, 35(7):1757–1772.
- Scheirer, W. J., Jain, L. P., and Boulton, T. E. (2014). Probability models for open set recognition. *IEEE transactions on pattern analysis and machine intelligence*, 36(11):2317–2324.
- Singh, M., Parameswaran, V., and Ramesh, V. (2008). Order consistent change detection via fast statistical significance testing. In *2008 IEEE Conference on Computer Vision and Pattern Recognition*, pages 1–8. IEEE.
- Sohl-Dickstein, J., Weiss, E., Maheswaranathan, N., and Ganguli, S. (2015). Deep unsupervised learning using nonequilibrium thermodynamics. In *International conference on machine learning*, pages 2256–2265. pmlr.
- Song, Y., Sohl-Dickstein, J., Kingma, D. P., Kumar, A., Ermon, S., and Poole, B. (2020). Score-based generative modeling through stochastic differential equations. *arXiv preprint arXiv:2011.13456*.
- Sun, Y., Guo, C., and Li, Y. (2021). React: Out-of-distribution detection with rectified activations. *Advances in neural information processing systems*, 34:144–157.
- Sun, Y. and Li, Y. (2022). Dice: Leveraging sparsification for out-of-distribution detection. In *European conference on computer vision*, pages 691–708. Springer.
- Sun, Y., Ming, Y., Zhu, X., and Li, Y. (2022). Out-of-distribution detection with deep nearest neighbors. In *International Conference on Machine Learning*, pages 20827–20840. PMLR.
- Wang, L., Zhang, X., Su, H., and Zhu, J. (2024). A comprehensive survey of continual learning: Theory, method and application. *IEEE transactions on pattern analysis and machine intelligence*, 46(8):5362–5383.
- Wang, Z., Bovik, A. C., Sheikh, H. R., and Simoncelli, E. P. (2004). Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing*, 13(4):600–612.
- Yang, Y., Cheng, D., Fang, C., Wang, Y., Jiao, C., Cheng, L., Wang, N., and Gao, X. (2024). Diffusion-based layer-wise semantic reconstruction for unsupervised out-of-distribution detection. *Advances in Neural Information Processing Systems*, 37:26846–26871.
- Zhang, J., Fu, Q., Chen, X., Du, L., Li, Z., Wang, G., Han, S., Zhang, D., et al. (2022). Out-of-distribution detection based on in-distribution data patterns memorization with modern hopfield energy. In *The Eleventh International Conference on Learning Representations*.
- Zhang, L., Goldstein, M., and Ranganath, R. (2021). Understanding failures in out-of-distribution detection with deep generative models. In *International*

Conference on Machine Learning, pages 12427–12436. PMLR.

Zhang, R., Isola, P., Efros, A. A., Shechtman, E., and Wang, O. (2018). The unreasonable effectiveness of deep features as a perceptual metric. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 586–595.

Zhou, K., Liu, Z., Qiao, Y., Xiang, T., and Loy, C. C. (2022). Domain generalization: A survey. *IEEE transactions on pattern analysis and machine intelligence*, 45(4):4396–4415.

Checklist

1. For all models and algorithms presented, check if you include:
 - (a) A clear description of the mathematical setting, assumptions, algorithm, and/or model. [Yes]
 - (b) An analysis of the properties and complexity (time, space, sample size) of any algorithm. [Not Applicable]
 - (c) (Optional) Anonymized source code, with specification of all dependencies, including external libraries. [Yes]
2. For any theoretical claim, check if you include:
 - (a) Statements of the full set of assumptions of all theoretical results. [Yes]
 - (b) Complete proofs of all theoretical results. [Yes]
 - (c) Clear explanations of any assumptions. [Yes]
3. For all figures and tables that present empirical results, check if you include:
 - (a) The code, data, and instructions needed to reproduce the main experimental results (either in the supplemental material or as a URL). [Yes]
 - (b) All the training details (e.g., data splits, hyperparameters, how they were chosen). [Yes]
 - (c) A clear definition of the specific measure or statistics and error bars (e.g., with respect to the random seed after running experiments multiple times). [Yes]
 - (d) A description of the computing infrastructure used. (e.g., type of GPUs, internal cluster, or cloud provider). [Yes]
4. If you are using existing assets (e.g., code, data, models) or curating/releasing new assets, check if you include:
 - (a) Citations of the creator If your work uses existing assets. [Yes]
 - (b) The license information of the assets, if applicable. [Not Applicable]
 - (c) New assets either in the supplemental material or as a URL, if applicable. [Not Applicable]
 - (d) Information about consent from data providers/curators. [Not Applicable]
 - (e) Discussion of sensible content if applicable, e.g., personally identifiable information or offensive content. [Not Applicable]
5. If you used crowdsourcing or conducted research with human subjects, check if you include:
 - (a) The full text of instructions given to participants and screenshots. [Not Applicable]
 - (b) Descriptions of potential participant risks, with links to Institutional Review Board (IRB) approvals if applicable. [Not Applicable]
 - (c) The estimated hourly wage paid to participants and the total amount spent on participant compensation. [Not Applicable]

Beyond Binary Out of Distribution Detection: Characterizing Distributional Shifts with Multi-Statistic Diffusion Trajectories: Supplementary Materials

A Impossibility of ϕ -based OOD Tests: Indistinguishable Alternatives

Proposition

Let P be a probability measure on a sample space $\mathcal{X}$ and let $\phi_p: \mathcal{X} \rightarrow \mathbb{R}$ be any (measurable) test statistic. Assume there exists a measurable set

$$\Phi_0 \subseteq \text{Range}(\phi_p) \quad \text{with} \quad P(\phi_p(X) \in \Phi_0) > 0$$

such that, for almost every $\phi \in \Phi_0$, the conditional law $P(\cdot \mid \phi_p(X) = \phi)$ is *non-degenerate* (i.e. not a point mass). Then there exist two distributions Q_1 and Q_2 satisfying

$$Q_1 \neq P, \quad Q_2 \neq P, \quad Q_1 \neq Q_2, \quad \text{but} \quad \phi_p(X) \sim Q_1 = \phi_p(X) \sim Q_2 = \phi_p(X) \sim P.$$

All three distributions induce the same marginal law on the statistic $\phi_p(X)$. As a result, any hypothesis test that depends only on $\phi_p(X)$ attains power equal to its false-positive rate against both Q_1 and Q_2 .

Proof

Proof Sketch. We construct two distributions, Q_1 and Q_2 , that are distinct from P and each other, yet engineered to produce the exact same marginal distribution for the statistic $\phi_p(X)$. The strategy is to identify a set of statistic values, Φ , where the conditional distribution $P(X \mid \phi_p(X) = \phi)$ is not concentrated on a single point. For each $\phi \in \Phi$, this non-degeneracy allows us to find at least two disjoint subsets of the outcome space, A_ϕ and B_ϕ , which both have positive conditional probability. We then define new conditional distributions, $q_1(x \mid \phi)$ and $q_2(x \mid \phi)$. For $\phi \in \Phi$, these new distributions slightly re-weight the probability mass between the sets A_ϕ and B_ϕ . For any $\phi \notin \Phi$, we leave the conditional distribution unchanged ($q_i(x \mid \phi) = p(x \mid \phi)$). Finally, we construct the full distributions Q_1 and Q_2 by combining these new conditional distributions with the original marginal density of $\phi_p(X)$. This procedure guarantees that the marginal law of $\phi_p(X)$ is identical under P , Q_1 , and Q_2 , while the joint distributions are provably different. Any test that depends only on $\phi_p(X)$ therefore attains identical rejection probabilities under all three measures, so its power equals its false-positive rate.

Non-Degeneracy Assumption. By assumption, the family of conditional distributions $p(x \mid \phi_p(x))$ is non-degenerate on a set of statistic-values of positive measure. Formally, there exists a measurable set

$$\Phi \subseteq \text{Range}(\phi_p) \quad \text{with} \quad \mu(\Phi) = P(\phi_p(X) \in \Phi) > 0,$$

such that for μ -almost every $\phi \in \Phi$ one can find a measurable subset

$$A_\phi \subseteq \text{supp } p(\cdot \mid \phi) \quad \text{satisfying} \quad 0 < P(X \in A_\phi \mid \phi_p(X) = \phi) < 1.$$

For each $\phi \in \Phi$ define the level set

$$S_\phi = \{x \in \mathcal{X} : \phi_p(x) = \phi\}$$

Because the conditional law is non-degenerate, the subset A_ϕ is a *proper* part of S_ϕ . Set

$$B_\phi = S_\phi \setminus A_\phi.$$

Then, for μ -almost every $\phi \in \Phi$,

$$A_\phi \cap B_\phi = \emptyset, \quad A_\phi \cup B_\phi = S_\phi, \quad 0 < P(A_\phi \mid \phi) < 1, \quad 0 < P(B_\phi \mid \phi) < 1.$$

Definition of the Test Function $f_p(x)$ We now construct a measurable function $f_p(x)$ that separates P and Q under the law of expectation. Let $g(x)$ be any measurable function with $\mathbb{E}_{p(x|\phi)}[|g(x)|] < \infty$ for all $\phi \notin \Phi$. Fix the partition $A_\phi, B_\phi \subseteq \text{supp}(p(x|\phi))$ for each $\phi \in \Phi$ as above. Then define

$$f_p(x) = \begin{cases} 1, & \phi_p(x) \in \Phi \text{ and } x \in A_{\phi_p(x)}, \\ \frac{1}{2}, & \phi_p(x) \in \Phi \text{ and } x \in B_{\phi_p(x)}, \\ g(x), & \phi_p(x) \notin \Phi. \end{cases} \quad (1)$$

- If $\phi_p(x) \in \Phi$, then $f_p(x)$ takes value 1 on the “upper” set A_ϕ and ($\frac{1}{2}$) on the complementary piece B_ϕ .
- If $\phi_p(x) \notin \Phi$, we revert to $g(x)$, ensuring f_p remains integrable and well-behaved off Φ .

Construction of the Alternative Conditional Distributions $q_1(x|\phi_p(x))$ and $q_2(x|\phi_p(x))$. Fix a constant $0 < \lambda < 1$. For every statistic value ϕ in the *essential range* of ϕ_p we define new conditional densities: (The selector $\phi \mapsto A_\phi$ is measurable, so the map $(\phi, x) \mapsto q_i(x|\phi)$ is jointly measurable.)

$$q_1(x|\phi_p(x) = \phi) = \begin{cases} \frac{1}{C_\phi^{(1)}} [\lambda p(x|\phi) \mathbb{1}\{x \in A_\phi\} + p(x|\phi) \mathbb{1}\{x \in B_\phi\}], & \phi \in \Phi, \\ p(x|\phi), & \phi \notin \Phi, \end{cases}$$

$$q_2(x|\phi_p(x) = \phi) = \begin{cases} \frac{1}{C_\phi^{(2)}} [p(x|\phi) \mathbb{1}\{x \in A_\phi\} + \lambda p(x|\phi) \mathbb{1}\{x \in B_\phi\}], & \phi \in \Phi, \\ p(x|\phi), & \phi \notin \Phi, \end{cases}$$

where the normalization constants for each $\phi \in \Phi$ are

$$C_\phi^{(1)} = \int_{A_\phi} \lambda p(x|\phi) dx + \int_{B_\phi} p(x|\phi) dx = \lambda P_{p(x|\phi)}(A_\phi) + P_{p(x|\phi)}(B_\phi),$$

$$C_\phi^{(2)} = \int_{A_\phi} p(x|\phi) dx + \int_{B_\phi} \lambda p(x|\phi) dx = P_{p(x|\phi)}(A_\phi) + \lambda P_{p(x|\phi)}(B_\phi).$$

- For $\phi \notin \Phi$ no change is made: $q_i(\cdot|\phi) = p(\cdot|\phi)$ for $i = 1, 2$.
- For $\phi \in \Phi$:
 - q_1 “down-weights” the mass on A_ϕ by λ , leaving B_ϕ unchanged, then renormalizes by $C_\phi^{(1)}$.
 - q_2 “down-weights” the mass on B_ϕ by λ , leaving A_ϕ unchanged, then renormalizes by $C_\phi^{(2)}$.
- Since $0 < \lambda < 1$ and $0 < P(A_\phi), P(B_\phi) < 1$, one checks

$$0 < C_\phi^{(1)}, C_\phi^{(2)} < 1, \quad \frac{\lambda}{C_\phi^{(1)}} < 1, \quad \frac{\lambda}{C_\phi^{(2)}} < 1.$$

Support Preservation. Since $0 < \lambda < 1$ and $C_{\phi_p(x)}^{(i)} > 0$, we have

$$q_i(x|\phi_p(x)) > 0 \iff p(x|\phi_p(x)) > 0.$$

Thus every x with $p(x|\phi_p(x)) > 0$ also satisfies $q_i(x|\phi_p(x)) > 0$, and vice versa, proving the supports coincide. For each $i = 1, 2$ and every $\phi_p(x)$,

$$\text{supp}(q_i(\cdot|\phi_p(x))) = \text{supp}(p(\cdot|\phi_p(x))).$$

The parameter λ controls the redistribution of mass between A_ϕ and B_ϕ within each level set without violating support preservation. If $\lambda = 1$, then $q_i(x|\phi)$ reduces to $p(x|\phi)$, so $Q_i = P$, violating the goal of constructing distinct alternatives. If $\lambda = 0$, one region is entirely zeroed out, violating support preservation. Choosing $0 < \lambda < 1$ yields two valid, distinct alternatives Q_1, Q_2 that share the same marginal distribution of $\phi_p(X)$ as P .

Defining the Full Distributions Q_1 and Q_2 . Having specified the conditional probability kernels $q_i(dx | \phi)$, we construct the full measures by combining them with the original marginal law of the statistic $\phi_p(X)$.

Let $p_\phi(d\phi)$ be the push-forward measure of P by the map ϕ_p . We define the joint measures on the product space as:

$$Q_i(dx, d\phi) = p_\phi(d\phi) q_i(dx | \phi), \quad i = 1, 2.$$

The marginal measure on $\mathcal{X}$ is found by integrating over ϕ :

$$Q_i(dx) = \int_{\text{Range}(\phi_p)} q_i(dx | \phi) p_\phi(d\phi).$$

If $p_\phi(\cdot)$ is the density for the measure $p_\phi(d\phi)$, and $q_i(\cdot | \phi)$ is the density for $q_i(dx | \phi)$, then the density $q_i(x)$ for the measure $Q_i(dx)$ is given by:

$$q_i(x) = p_\phi(\phi_p(x)) \times q_i(x | \phi_p(x)). \quad (2)$$

- Because $\int q_i(dx | \phi) = 1$ for every ϕ , each Q_i is a valid probability measure.
- By construction, the push-forward of each Q_i by ϕ_p is $p_\phi(d\phi)$. Therefore, P, Q_1 , and Q_2 all share the same marginal law for the statistic.

Marginal matching of $\phi_p(X)$. Let $p_\phi(d\phi) = P(\phi_p(X) \in d\phi)$ be the push-forward measure of P . For every measurable set $B \subseteq \text{Range}(\phi_p)$,

$$Q_i(\phi_p(X) \in B) = \int_B \int q_i(dx | \phi) p_\phi(d\phi) = \int_B p_\phi(d\phi) = P(\phi_p(X) \in B), \quad i = 1, 2,$$

where the middle equality uses $\int q_i(dx | \phi) = 1$ for all ϕ (joint measurability established earlier). Hence

$$Q_1 \circ \phi_p^{-1} = Q_2 \circ \phi_p^{-1} = P \circ \phi_p^{-1},$$

i.e. the statistic $\phi_p(X)$ has the same distribution under P, Q_1, Q_2 .

Verifying $Q_i \neq P$ and $Q_1 \neq Q_2$. Our goal is now to show that the expectations of the test function f_p under P and under the alternative distributions Q_1 and Q_2 differ, i.e.,

$$\mathbb{E}_P[f_p(X)] - \mathbb{E}_{Q_i}[f_p(X)] > 0 \quad \text{for } i = 1, 2,$$

using the law of total expectation.

Write $p_\phi(d\phi) = P(\phi_p(X) \in d\phi)$ for the push-forward measure of P . For every $\phi \in \Phi$ for which the partition is defined, set $a_\phi := P(A_\phi | \phi)$ and $b_\phi := P(B_\phi | \phi) = 1 - a_\phi$. Recall that the test function is $f_p(x) = 1$ on A_ϕ and $f_p(x) = \frac{1}{2}$ on B_ϕ .

For $\phi \in \Phi$, the conditional expectations are:

$$\mathbb{E}_P[f_p(X) | \phi] = a_\phi + \frac{1}{2} b_\phi, \quad \mathbb{E}_{Q_1}[f_p(X) | \phi] = \frac{\lambda a_\phi + \frac{1}{2} b_\phi}{\lambda a_\phi + b_\phi}, \quad \mathbb{E}_{Q_2}[f_p(X) | \phi] = \frac{a_\phi + \frac{1}{2} \lambda b_\phi}{a_\phi + \lambda b_\phi}.$$

For $\phi \notin \Phi$, all three conditional expectations are equal, so these terms cancel when computing differences of the full expectations.

For any $0 < \lambda < 1$ and $0 < a_\phi, b_\phi < 1$, the difference in conditional expectations is:

$$\Delta_1(\phi) := \mathbb{E}_P[f_p | \phi] - \mathbb{E}_{Q_1}[f_p | \phi] = \frac{0.5(1 - \lambda) a_\phi b_\phi}{\lambda a_\phi + b_\phi} > 0.$$

Since $\Delta_1(\phi) > 0$ on the set Φ which has positive measure, the integral is strictly positive:

$$\mathbb{E}_P[f_p(X)] - \mathbb{E}_{Q_1}[f_p(X)] = \int_{\Phi} \Delta_1(\phi) p_\phi(d\phi) > 0,$$

so $Q_1 \neq P$.

Similarly for Q_2 :

$$\Delta_2(\phi) := \mathbb{E}_P[f_p | \phi] - \mathbb{E}_{Q_2}[f_p | \phi] = \frac{0.5(1-\lambda) a_\phi b_\phi}{a_\phi + \lambda b_\phi} > 0.$$

Therefore $\mathbb{E}_P[f_p] - \mathbb{E}_{Q_2}[f_p] > 0$, and hence $Q_2 \neq P$.

For $\phi \in \Phi$, the difference in conditional expectations is:

$$\mathbb{E}_{Q_1}[f_p | \phi] - \mathbb{E}_{Q_2}[f_p | \phi] = \frac{0.5 a_\phi b_\phi (\lambda^2 - 1)}{(\lambda a_\phi + b_\phi)(a_\phi + \lambda b_\phi)}.$$

Since $0 < \lambda < 1$, the term $(\lambda^2 - 1)$ is strictly negative. Because a_ϕ, b_ϕ are strictly positive on Φ , the entire expression is non-zero. The integral of this difference over Φ is therefore non-zero, so $\mathbb{E}_{Q_1}[f_p(X)] \neq \mathbb{E}_{Q_2}[f_p(X)]$, which proves $Q_1 \neq Q_2$.

Hence Q_1, Q_2 are both distinct from P and from each other.

Indistinguishability by ϕ_p -based Tests. Any test that depends solely on the statistic $\phi_p(x)$ can be written as

$$\text{Reject } H_0 \iff \phi_p(x) \in R \text{ for some } R \subseteq \text{Range}(\phi_p).$$

Under P , the false-positive rate (size) of this test is

$$\text{FPR} = P(\phi_p(X) \in R).$$

Under either alternative Q_i ($i = 1, 2$), the test's power is

$$\text{Power}_i = Q_i(\phi_p(X) \in R).$$

But since $Q_i(\phi_p(X) \in R) = P(\phi_p(X) \in R)$ for both i , we have

$$\text{Power}_i = \text{FPR} \quad (\text{for } i = 1, 2).$$

Hence every ϕ_p -based test has power equal to size under Q_1 and Q_2 . Outline for Appendix: 1. Implementation Details 2. Additional Results More Detailed Results Dataset wise 3. Additional Detailed Results for the baselines showing how they struggle 4. The Results showcasing per Operator Performance 5. Tabular Data detailed Results 6. Tabular Data distinction between different types.

B Extended Background

B.1 Out-of-Distribution Detection Score Computation

Out-of-distribution (OOD) detection methods assign each input x an OOD score $o(x)$ that reflects how likely x lies outside the training distribution. Previous works have attempted to categorize these methods in various ways; however, most modern approaches leverage ideas from multiple paradigms to compute OOD scores. In the case of generative models, one can compute an OOD score either from the estimated density or from a reconstruction loss.

Density-Based Methods Density-based methods learn an explicit generative model $p(x)$ over in-distribution data and use the negative log-likelihood as the OOD score:

$$o(x) = -\log p(x).$$

Under this formulation, inputs falling into low-density regions—i.e., those that yield small values of $p(x)$ —incur large values of $o(x)$ (Nalisnick et al., 2018). For instance, PixelCNN++ is an autoregressive model that estimates image likelihoods using convolutional networks and computes $p(x)$ exactly via a tractable factorization (Salimans et al., 2017). Likewise, Glow employs invertible flow layers that permit exact likelihood evaluation through a sequence of bijective transformations (Kingma and Dhariwal, 2018). In both cases, test inputs that lie far from the training distribution receive high OOD scores via $-\log p(x)$.

Reconstruction-Based Methods Reconstruction-based methods rest on the assumption that in-distribution samples lie on or near a low-dimensional manifold embedded in the input space. One trains a reconstruction model $r(x)$ so that, for an in-distribution sample, $r(x) \approx x$. The OOD score is then taken to be the reconstruction error:

$$o(x) = \|x - r(x)\|_2.$$

Since OOD inputs do not conform to the learned manifold, they tend to yield large reconstruction errors. Common instantiations include variational autoencoders trained with a pixel-wise L_2 reconstruction loss, as well as diffusion models that are optimized to minimize the same loss on training data (Oko et al., 2023; Livernoche et al., 2023). In practice, an input x whose reconstruction $r(x)$ deviates substantially from x is flagged as likely OOD.

Discriminative Models and Calibration Discriminative models are typically trained on a supervised classification task and leverage outputs (logits) or internal features (e.g., from the penultimate layer) for a given input x for OOD Detection. Because such models often yield poorly calibrated confidences, especially on inputs outside the training distribution, many approaches first focus on calibration before computing a post-hoc score. One prominent calibration technique is *Outlier Exposure*, which augments the training process with a diverse set of outlier examples and penalizes high confidence on these samples (Hendrycks et al., 2018). Formally, let $p_\theta(y | x)$ denote the softmax probability of class y . During training, an auxiliary loss term encourages $p_\theta(y | x_{\text{out}})$ to remain near uniform for outlier inputs x_{out} , thereby reducing overconfidence on novel examples. Another calibration strategy is *ODIN*, which applies temperature scaling to the logits and adds a small adversarial perturbation to the input; this softens the softmax outputs and amplifies the gap between in-distribution (ID) and OOD confidences.

Post-Hoc Logit-Based Scores Once a discriminative model $f: x \mapsto \{f_c(x)\}_{c=1}^C$ is trained (and potentially calibrated), one can derive OOD scores directly from its logits $\{f_c(x)\}$. The simplest baseline is the *Maximum Softmax Probability* (MSP), defined as

$$o_{\text{MSP}}(x) = -\max_c (f(x))_c.$$

Although intuitive, MSP often remains overconfident on novel inputs, yielding poor separation between ID and OOD samples (Hendrycks and Gimpel, 2016). A more informative metric from information theory is the *predictive entropy*:

$$o_{\text{ent}}(x) = -\sum_{c=1}^C p(c | x) \log p(c | x), \quad p(c | x) = (f(x))_c.$$

Higher entropy indicates greater uncertainty, and thus a higher likelihood of being OOD. To produce better-calibrated uncertainty estimates, one can employ *Monte Carlo Dropout*—which aggregates stochastic predictions under dropout at test time (Gal and Ghahramani, 2016)—or *Deep Ensembles*, which average the outputs of multiple independently trained models (Lakshminarayanan et al., 2017). Both techniques approximate Bayesian inference and tend to assign higher entropy to inputs that deviate from the training distribution.

The *Energy Score* provides another logit-based measure by mapping logits to a scalar via a log-sum-exp operation:

$$o_E(x) = -\log \sum_{c=1}^C \exp(f_c(x)).$$

Since this score does not normalize the logits into a simplex, it mitigates the overconfidence issues of softmax; in practice, in-distribution samples produce strongly negative energy values, while OOD samples yield higher (less negative) energies (Liu et al., 2020).

Post-Hoc Feature-Based Scores Instead of relying on the logits, feature-based approaches compute OOD scores using internal representations—typically the output of the penultimate layer, denoted $z(x)$. A widely used method is the *Mahalanobis Distance* score: one fits a class-conditional Gaussian mixture model over the features, estimating a mean vector μ_c for each class c and a (shared) covariance matrix Σ . The Mahalanobis score is then given by

$$o_{\text{Maha}}(x) = \min_c (z(x) - \mu_c)^\top \Sigma^{-1} (z(x) - \mu_c).$$

Inputs whose features lie far from all class-conditional Gaussians receive large scores and are flagged as OOD (Lee et al., 2018; Ren et al., 2021). Alternatively, *Deep k-Nearest Neighbors* (Deep k -NN) computes the distance to the nearest neighbors among training embeddings, effectively measuring how isolated $z(x)$ is within the in-distribution feature manifold (Sun et al., 2022). Extreme Value Theory (EVT) can further refine thresholds on tail distances by fitting a distribution to the largest observed distances, thereby yielding more robust OOD detection (Ren et al., 2021).

Gradient-Based Metrics Gradient-based methods exploit the observation that OOD inputs, lying off the learned manifold, often induce larger gradients with respect to the input. One such metric is *GradNorm*, which measures the norm of the input gradient of the loss at the predicted label $\hat{y}$:

$$o_{\text{Grad}}(x) = \|\nabla_x \ell(\hat{y} | x)\|_2.$$

Because OOD samples typically incur higher input gradients, a larger value of $o_{\text{Grad}}(x)$ signals a greater chance of being OOD (Huang et al., 2021). More recent approaches fit the input’s Fisher information matrix to capture sensitivity peaks around OOD examples, thereby providing an alternative gradient-based OOD metric (Dauncey et al., 2024).

Inference-Modifying Post-Hoc Methods Beyond computing a static score, certain methods modify the inference process itself to improve OOD detection without retraining the model. For example, one can prune or clip activations at test time—techniques such as *ReAct*, which truncates excessively large ReLU activations (Sun et al., 2021); *DICE*, which dynamically clips activations based on batch statistics (Sun and Li, 2022); and *ASH*, which applies asymmetric activation clipping to preserve ID accuracy (Djurisic et al., 2022). After modifying activations, any of the aforementioned logit- or feature-based scores can be applied to achieve stronger separation between ID and OOD inputs.

It is important to note that many state-of-the-art methods weave together ideas from these different perspectives. For instance, one might compute a Mahalanobis score in the latent feature space of a generative model while using Monte Carlo Dropout to estimate predictive uncertainty, or measure input gradients of a diffusion-based generator. Consequently, the above categories—generative versus discriminative, density versus reconstruction, logit-based versus feature-based—should not be viewed as mutually exclusive; rather, they provide a taxonomy for understanding how various components may be combined to produce robust OOD detection.

B.2 Score Based Generative Models

Score-based generative models (Sohl-Dickstein et al., 2015; Song et al., 2020) learn to estimate the score function $\nabla \log p(x)$ by training a collection of denoisers $\{D_\sigma\}$ at varying noise levels. A *forward diffusion* corrupts a clean sample $x_0 \sim p(x)$ through a Markov chain of Gaussian perturbations:

$$x_{\sigma_0} \longrightarrow x_{\sigma_1} \longrightarrow \cdots \longrightarrow x_{\sigma_\infty},$$

with $\sigma_0 < \sigma_1 < \cdots < \sigma_\infty$ and

$$p(x_\sigma | x) = \mathcal{N}(x, \sigma^2 I), \quad p_\sigma(x_\sigma) = \int \mathcal{G}_\sigma(x_\sigma - x) p(x) dx.$$

Tweedie’s formula (Efron, 2011) connects MMSE denoising to score estimation:

$$D_\sigma(x_\sigma) = \mathbb{E}[x | x_\sigma] = x_\sigma + \sigma^2 \nabla \log p_\sigma(x_\sigma), \quad (3)$$

so minimizing $\mathbb{E} \|x - D_\sigma(x_\sigma)\|_2^2$ recovers $\nabla \log p_\sigma(x_\sigma)$.

Based on the formulation of (Song et al., 2020), score-based models come in two main categories:

- **Variance Preserving (VP)**

$$x_t = \sqrt{\alpha(t)} x_0 + \sqrt{1 - \alpha(t)} \epsilon, \quad \epsilon \sim \mathcal{N}(0, I),$$

with $\alpha(t) \in [0, 1]$ decreasing, so $\text{Var}(x_t)$ remains bounded.

- **Variance Exploding (VE)**

$$x_t = x_0 + \sigma(t) \epsilon, \quad \epsilon \sim \mathcal{N}(0, I),$$

where $\sigma(t)$ increases, causing $\text{Var}(x_t) = \sigma^2(t) \rightarrow \infty$.

In practice, the denoiser D_σ is parameterized (e.g., by a neural network) and trained to minimize the mean squared error (MSE) between the clean sample x and its denoised estimate $D_\sigma(x_\sigma)$:

$$\text{MSE}(D_\sigma) = \mathbb{E}_{x, x_\sigma} \|x - D_\sigma(x_\sigma)\|_2^2. \quad (4)$$

A diffusion model thus comprises a collection of minimum-mean-square-error denoisers $\{D_\sigma : \sigma \in \sigma\}$. Each denoiser implicitly provides access to the corresponding score function $\nabla \log p_\sigma(x_\sigma)$. At sampling time, these learned score functions are employed to reverse the diffusion process and generate samples from the underlying clean distribution $p(x)$ via a discretized reverse diffusion procedure.

C Related Work

Out-of-distribution (OOD) detection methods are broadly categorized into generative and discriminative approaches. Generative models learn the in-distribution (ID) data distribution either through explicit density estimation (e.g., PixelCNN++ (Salimans et al., 2017), Glow (Kingma and Dhariwal, 2018)) or reconstruction-based techniques that identify OOD samples by their high reconstruction error (e.g., VAEs, diffusion models (Graham et al., 2023)). However, the reliability of these density-based models has been challenged. Nalisnick et al. (2019) demonstrated that deep generative models can paradoxically assign a higher likelihood to OOD datasets than to the in-distribution data they were trained on, revealing a fundamental failure in their OOD detection capabilities (?). Further investigation by Zhang et al. (2021) attributed this failure to the models’ reliance on simple background statistics or low-level features, which can cause them to assign high likelihood to OOD samples that share these trivial features with the training data (Zhang et al., 2021).

Recent work has demonstrated that generative denoising processes are particularly effective OOD detectors (Graham et al., 2023; Livernoche et al., 2023). For example, some methods use diffusion inpainting to reconstruct masked image regions, using the resulting error as an OOD score (Liu et al., 2023). Others have shown that a single, unconditional diffusion model can flag OOD instances by analyzing anomalies in its denoising trajectories (Heng et al., 2024). Another approach aggregates mismatches between noisy and denoised feature maps across diffusion steps, boosting detection sensitivity without requiring label supervision (Yang et al., 2024).

Discriminative models, typically trained for classification, are repurposed for OOD detection using various scoring functions. These include logit-based approaches (e.g., MSP, energy scores (Hendrycks and Gimpel, 2016; Liu et al., 2020)), feature-based methods (e.g., Mahalanobis distance, Deep k-NN), gradient-based metrics (Huang et al., 2021), and activation-based strategies (e.g., Tent (Rozsa and Boulton, 2019), DICE (Sun and Li, 2022)). To mitigate classifier overconfidence on OOD inputs, calibration techniques like ODIN and Outlier Exposure are often employed (Hsu et al., 2020; Hendrycks et al., 2018). While efficient at inference, the performance of these methods hinges on the classifier’s decision boundary and learned features, which are not always optimal for OOD detection (Li et al., 2025).

Modern approaches often combine generative and discriminative components to achieve robust performance. However, a fundamental trade-off exists between detecting "near" versus "far" OOD samples, suggesting that no single method excels at both (Guille-Escuret et al., 2024; Zhang et al., 2021). Furthermore, many methods implicitly assume a unimodal, exponentially decaying score distribution. This assumption is adequate for binary ID-vs-OOD decisions but is ill-suited for complex, multi-modal OOD landscapes. The challenges are compounded by the finite-sample problem, especially in high-dimensional spaces where the curse of dimensionality makes it difficult to distinguish genuine distributional shifts from sampling artifacts (Ghosal et al., 2024; Aggarwal et al., 2001). Recent impossibility theorems have established that OOD detection is not generally PAC-learnable in distribution-free settings. Learnability is only possible under restrictive conditions on the hypothesis spaces and the relationship between ID and OOD data (Fang et al., 2022; Garov and Chaudhuri, 2025).

D Implementation Details

This section details datasets, models, hyperparameters, and evaluation protocols to reproduce our results.

Datasets and preprocessing. For images we use **CIFAR-10** and **ImageNet-1k** as in-distribution (ID) datasets. For CIFAR-10 we evaluate the following OOD families: **CIFAR-10-FGSM** ($\epsilon = 0.1$, steps = 1), horizontal flips, 90° rotations, central black-pixel occlusion covering up to $\approx 20\%$ of the image area, **Butterflies** (Smithsonian subset from HuggingFace), and **MNIST** (replicated to 3-channel RGB and resized). For ImageNet we use **ImageNet-A**, **ImageNet-O**, **ImageNet-C** (no fixed severity index), **CIFAR-10**, and **MNIST** as OOD. CIFAR images are resized to 32×32 and normalized to $[-1, 1]$ using per-channel mean/std $\mu = (0.5, 0.5, 0.5)$, $\sigma = (0.5, 0.5, 0.5)$; ImageNet images are resized to 64×64 and normalized with ImageNet statistics $\mu = (0.485, 0.456, 0.406)$, $\sigma = (0.229, 0.224, 0.225)$. When diffusion models are used, we (de)scale to $[-1, 1]$ as required by the backbone. No test-time augmentation is used for OOD scoring.

For tabular experiments we adopt the **ADBench** subset via our TabDDPM pipeline. Unless otherwise noted in per-dataset configs, numeric features are standardized (z-scoring) on the ID training split, categorical features use either **one-hot** or leave-one-out **counter** encoding, numeric missing values are imputed with the mean (or rows dropped where configured), categorical missing values use the most-frequent category, and we do not apply outlier clipping.

Backbones for baselines. For image-based baselines we use **WideResNet-28-10** pretrained on CIFAR-10 (for CIFAR experiments) and **ResNet-50** pretrained for ImageNet experiments. These backbones are used as-is (no additional training/label smoothing). Representation-space methods (Mahalanobis, SHE, ViM, kNN when used, DICE/ASH/ReAct) operate on *penultimate avg-pool* features. For tabular baselines we wire **DeepSVDD**, **ICL**, **DevNet**, and **SLAD**; model depth/width and optimizer hyperparameters follow the dataset-specific configs in our Code.

Diffusion backbone (DISC). We adopt two complementary VP-style DDPM backbones, both with U-Net denoisers, but used for different roles. For analyses on 64×64 images we rely on the *improved-diffusion* implementation, instantiated once with a cosine noise schedule and 3000 diffusion steps. The model predicts ϵ without label conditioning, and uses timestep and learned-sigma rescaling. Its U-Net has 128 base channels with multipliers $[1, 2, 2, 2]$, three residual blocks per stage, four attention heads, attention at resolutions 16 and 8, zero dropout, and scale-shift normalization. We train DDPM with a linear β schedule ($\beta_{\min}=10^{-4}$, $\beta_{\max}=2 \times 10^{-2}$), **Adam** with learning rate 2.5×10^{-5} , exponential moving average, and no mixed precision; and **PNDM** (Liu et al., 2022) for sampling. For feature extraction we sample diffusion trajectories with **PNDM** using 10–20 steps (dataset-dependent), $\eta=0$, and guidance scale 1 (unconditional).

DISC feature construction. For each input x we form a feature vector $s(x)$ by aggregating metrics across timesteps $t \in \mathcal{T}$. On CIFAR-10 we set $|\mathcal{T}| = 20$. On ImageNet we subsample $\mathcal{T}$ to $|\mathcal{T}| = 10$ from a 3000-step grid. At each t we compute: (i) *reconstruction fidelity* between x and $\hat{x}_t$: MSE, SSIM (Kornia defaults (Riba et al., 2020); 11×11 window) and LPIPS (AlexNet backbone); (ii) *score/trajectory consistency*, using local-complexity (LC) construction around noised images at timestep t , hyperplane/intersection counts following the original paper.

Baseline OOD detectors and settings. We use the reference implementations provided by the respective packages (primarily **pytorch-ood**, and official author repositories where applicable) and run each detector with the *default* hyperparameters used in state-of-the-art benchmark suites. When a method requires calibration (e.g., ODIN temperature/perturbation), we follow the package’s standard ID-only validation protocol and reuse the resulting setting across all OOD families. No additional per-family tuning or deviations from the released implementations were introduced.

Evaluation protocols. For binary ID-vs-OOD detection we report AUROC. Any fixed thresholds τ are chosen on ID validation. For optional multi-OOD classification, we (i) run unsupervised K-means with k equal to the number of OOD families on either scalar scores or DISC vectors and perform Hungarian alignment for cluster-to-family mapping; and (ii) train a small supervised MLP (2 hidden layers, width 256, ReLU, dropout 0.2). Optional pairwise OOD-vs-OOD separability is computed as AUROC on the chosen features. Unless otherwise noted, we report mean $\pm$ std over $N = 5$ seeds; where confidence intervals are shown we use nonparametric bootstrap over samples.

Computing environment and reproducibility. All experiments run on a single NVIDIA GPU (≥ 16 GB VRAM). We use PyTorch (2.1), CUDA (12.2), and most notably the following libraries: `pytorch-ood` (Kirchheim et al., 2022), `Kornia` (Riba et al., 2020), `PyWavelets` (Lee et al., 2019), `MONAI Generative` (Pinaya et al., 2023), and `improved-diffusion` (Nichol and Dhariwal, 2021).

Hyperparameters (summary). Full hyperparameters are recorded in the configuration files. In brief: *CIFAR-10 (images)*. Diffusion scheduler with $T=1000$ training steps (MONAI DDPM), linear β -schedule ($10^{-4} \rightarrow 2 \times 10^{-2}$), PNDM sampler with $|\mathcal{T}| = 20$ evaluation timesteps; base lr 2.5×10^{-5} ; batch size 128. *ImageNet-1k (images)*. Improved-diffusion U-Net with $T=4000$ and cosine schedule; LC/evaluation uses $|\mathcal{T}| = 10$ subsampled timesteps; batch size 128. *DISC metrics*. SSIM uses Kornia defaults (window 11×11), LPIPS backbone `alex`, score-step $\Delta = 1$, LBP hist 256 bins, edge-orientation 36 bins, DCT/wavelet hist 50 bins, wavelet `haar` (level 1). *Baselines*. ODIN $\epsilon = 0.002$ (temperature tuned on ID validation), Mahalanobis layer = penultimate avg-pool (no shrinkage unless specified), DICE $p = 0.65$, ViM $d = 64$, MCD 30 samples. A single tuned setting per detector is reused across OOD families.

All remaining implementation details are included in the code release to ensure exact reproducibility.

E Additional Results

This appendix augments the main text with four sets of results. First, we provide additional score distributions and two-dimensional embeddings (t-SNE) on **CIFAR-10** and **ImageNet** to visualize how ID and OOD families separate under different detectors. Second, we report ImageNet-wide AUROC tables that cover both standard baselines and diffusion-derived features, enabling a fine-grained assessment of **DISC** across OOD types. Third, we ablate **DISC** by varying the underlying metric operators (reconstruction fidelity, texture/geometry, and path-consistency) and quantify their individual and combined contributions. Finally, we present comprehensive **tabular** benchmarks with average AUROC and rank, per-dataset breakdowns, and qualitative embeddings. We keep the same experimental protocol as the main body.

E.1 Image Data: Extended Baselines

More score histograms. Figure 7 extends the histogram analysis in the main body to nine representative detectors on CIFAR-10. Across all methods, OOD families shift away from the ID peak but *retain substantial overlap*. Near-distribution shifts (CIFAR-FGSM, CIFAR-Flip, central black occlusion) stay closest to the ID mode, while semantic OODs (Butterflies, MNIST) move further into the high-novelty tail. The relative ordering of families is consistent across detectors, replicating the main-text observation that a single scalar score is often sufficient for ID-vs-OOD but not for *family-aware* separation.

Score histograms. Figure 8 expands the score-distribution view on **ImageNet**. Across detectors the same pattern holds: every OOD family shifts away from the ID mode, but natural-image OODs (ImageNet-A/O/C) occupy essentially the *same* score range as ID, producing heavy overlap and long shared tails. Detectors that operate directly on prediction confidence (MSP/Entropy/MaxLogit) display highly skewed, low-variance ID peaks with OOD mass bleeding into the shoulder; Energy behaves similarly but with a broader dynamic range, which makes far-domain OODs (MNIST, Butterflies) accumulate in the high-novelty tail. Feature-space methods (Mahalanobis and Maha+ODIN) sharpen the ID spike and pull the near-distribution transforms (flips/occlusions) closer to it, while still separating the extreme-domain OODs; ODIN’s temperature/perturbation mainly reduces overlap in the immediate ID shoulder. ViM and ReAct alter calibration rather than class order: they shift all curves but preserve the relative difficulty of families.

t-SNE embeddings across detectors. Figure 9 visualizes the joint embedding of *combined detector scores* for CIFAR-10 (a) and ImageNet (b). On **CIFAR-10**, the far-shift MNIST forms a compact island well separated from the ID cloud, while Butterflies occupies a broad swath that is partly distinct yet still interleaves with ID at its boundary. In contrast, near-distribution transformations (FGSM, flips, central black-out) dissolve into the ID manifold and trace smooth arcs along its periphery, consistent with their small score deltas in the histograms. On **ImageNet**, the strongest separation again occurs for extreme domain shifts (MNIST, and to a lesser extent CIFAR-10), whereas natural-image families (ImageNet-A/O/C) largely overlap with the ID lobe and with each




Figure 7: Extended OOD score distributions on **CIFAR-10** for nine baseline detectors. Near-OOD families shift modestly from the ID mode; semantic OODs shift further yet overlap with one another and with some near-OODs. Densities are normalized and share identical binning.

other, reflecting the difficulty of disentangling semantically similar content using a single signal. Taken together, the embeddings reinforce our central claim: even if scalar detectors are adequate for binary ID-vs-OOD they compress family structure, which makes fine grained detection very hard.




Figure 8: Extended OOD score distributions on **ImageNet**. Family ordering is broadly consistent across detectors; the overlap among natural-image OODs remains pronounced.

Per-dataset AUROC on ImageNet. Table 2 lists AUROC by OOD family. Diffusion-derived features (**DISC**) achieve the best *average* (**0.728**), surpassing the strongest scalar baseline, Mahalanobis+ODIN (0.653), by +0.075. The largest gains appear on texture/shape mismatches and occlusions—**Butterflies** 0.983 (MSE), **MNIST** 0.989, **CIFAR-10** 0.956 (LBP), and **ImageNet-Black** 0.898. For natural outliers (**ImageNet-O**), Mahalanobis+ODIN remains competitive (0.690 vs. 0.658 for DISC), and flips favor calibrated confidence methods (MSP/Energy ~ 0.56 vs. DDPM ~ 0.51). Overall, diffusion trajectories add complementary texture/geometry cues, while near-invariant transforms are still best handled by calibrated logits.

F Additional Ablation Studies

Ablation over metric groups. To assess whether the full metric suite is both necessary and beneficial for DISC, we performed a leave-one-out ablation over the different metric groups. Results averaged across 5 random seeds are reported in Table 3.

The results show that removing any individual metric group leads to a drop in supervised accuracy. The largest decreases are observed when excluding LPIPS or Wavelets, suggesting that these components contribute most strongly to the supervised setting. In the unsupervised setting, measured via clustering accuracy, performance declines are more evenly distributed across metric groups. The main exception is SSIM: removing SSIM yields a small increase of roughly 1% for K-means clustering. Overall, these findings support the value of the proposed




Figure 9: t-SNE of detector features/scores on **ImageNet**. Far OODs form more distinct clusters than on CIFAR-10, but natural corruptions and near-distribution variants still overlap across detectors. t-SNE of detector features/scores on **CIFAR-10**. Far OODs separate clearly, but near-OOD families entangle with the ID manifold across most detectors, underscoring the limits of single-score detectors for family-aware analysis

Table 2: AUROC results across OOD datasets for various methods with ImageNet as in-distribution dataset. Boldface in text discusses notable family-wise trends.

Method	ImageNet-A	ImageNet-F	ImageNet-O	ImageNet-B	ImageNet-C	Butterflies	CIFAR10	MNIST	AVG
DDPM:									
ALL (DISC)	0.607	0.507	0.658	0.767	0.557	0.939	0.801	0.989	0.728
LBP	0.547	0.494	0.601	0.898	0.555	0.638	0.956	0.995	0.710
LC	0.598	0.505	0.587	0.749	0.539	0.858	0.507	0.990	0.667
MSE	0.544	0.505	0.611	0.482	0.530	0.983	0.558	0.989	0.650
LPIPS	0.626	0.506	0.627	0.685	0.606	0.705	0.837	0.474	0.633
SSIM	0.577	0.504	0.588	0.849	0.559	0.826	0.498	0.650	0.631
HOG	0.609	0.495	0.558	0.490	0.469	0.377	0.527	0.748	0.534
OOD detectors									
EnergyBased	0.592	0.564	0.561	0.510	0.516	0.436	0.154	0.826	0.506
Entropy	0.575	0.556	0.552	0.566	0.516	0.501	0.147	0.694	0.506
MCD	0.549	0.556	0.503	0.551	0.514	0.512	0.155	0.489	0.481
MSP	0.570	0.554	0.552	0.560	0.516	0.508	0.150	0.663	0.502
Mahalanobis	0.475	0.482	0.671	0.718	0.512	0.867	0.751	0.643	0.640
Mahalanobis+ODIN	0.472	0.480	0.690	0.721	0.503	0.880	0.743	0.763	0.653
MaxLogit	0.591	0.563	0.561	0.516	0.516	0.443	0.154	0.810	0.506
ODIN	0.540	0.537	0.612	0.610	0.482	0.524	0.184	0.873	0.533
ReAct	0.556	0.515	0.549	0.516	0.523	0.468	0.219	0.560	0.478
ViM	0.574	0.553	0.623	0.550	0.529	0.638	0.256	0.773	0.545

multi-statistic embedding and indicate that combining complementary metric groups leads to the most robust OOD characterization.

Table 3: Leave-one-out ablation of the DISC metric groups. We report clustering accuracy (Clust. Acc.) and supervised accuracy (Sup. Acc.), together with standard deviations over 5 runs and the relative change (Δ) with respect to the full metric suite.

Combination	Clust. Acc	Clust. Acc Std	Sup. Acc	Sup. Acc Std	Δ Clust. Acc	Δ Sup. Acc
All Combined	0.4911	0.0118	0.6203	0.0163	0	0
All except SSIM	0.5020	0.0148	0.5957	0.0137	+0.0108	-0.0246
All except MSE	0.4623	0.0173	0.5950	0.0204	-0.0289	-0.0253
All except LBP	0.4456	0.0196	0.5924	0.0103	-0.0456	-0.0279
All except LPIPS	0.4794	0.0124	0.5911	0.0130	-0.0117	-0.0292
All except Wavelets	0.4694	0.0095	0.5870	0.0093	-0.0217	-0.0333
All except LC	0.4894	0.0075	0.6170	0.0064	-0.0017	-0.0033

Table 4 compares metric groups under unsupervised (KMeans/GMM) and supervised (MLP) multi-OOD classification. Supervision consistently boosts performance, and **combining all metrics** yields the best accuracy (MLP 0.625), confirming complementarity across reconstruction fidelity, local complexity, and texture operators.




Figure 10: Sensitivity of an isolation-forest head to different DISC metric subsets on ImageNet (higher is better). Trends mirror Table 4: texture and LC are strong standalone; the full combination is best.

Table 4: Classification accuracy of OOD Types using different Test Statistics. Experiments repeated 5 times and average results are reported.

Method	KMeans	GMM	MLP
MSE	0.3275	0.3594	0.3905
SSIM	0.3728	0.4410	0.5033
LPIPS	0.2750	0.2862	0.4165
LC	0.3145	0.4151	0.4881
DISC	0.4776	0.4512	0.6203

Why we adopt KL divergence. We compare several discrepancy choices: KL , JS , *total variation*, *Wasserstein*, and an absolute-deviation proxy (MAD). Table 5 makes two points clear. *First*, the best divergence is operator-dependent: LBP favors JS /TVD, while DTCWT (especially Level 1) prefers KL , and vector distances behave best with Euclidean. *Second*, aggregating complementary operators (“DISC”) achieves best performance in unsupervised and supervised settings. We therefore standardize on **KL** in the main pipeline for distributional comparisons: it yields stable, monotone behaviour along the diffusion trajectory and competitive accuracy across families, while still allowing operator-specific alternatives (JS /TVD/*Wasserstein*/MAD) when robustness or symmetry is desired.

Ablation on the Number of Timesteps. To study the contribution of different diffusion noise levels, we conducted an ablation on ImageNet that compares the full diffusion trajectory against restricted temporal subsets (early versus late timesteps) as well as the best-performing single timestep. Here, “Early Half” denotes features extracted from the first half of the diffusion trajectory, whereas “Late Half” denotes features from the second half.

As shown in Table 6, using the full trajectory consistently yields the best performance in both clustering and supervised evaluation. This supports our hypothesis that the temporal evolution of the diffusion process carries important diagnostic information that is not fully captured by any restricted subset of timesteps. Moreover, relying on a single timestep—even the best-performing one at $t = 2500$ —results in a marked performance drop, ranging from 3.8 to 8.5 percentage points. These results underscore the importance of aggregating information across the full diffusion trajectory.

Table 5: OOD Type Classification Accuracy ($\mu \pm \sigma$) for **KMeans** (unsupervised Setting) and am **MLP** (Supervised Setting) by *operator* and *divergence/metric*. Best overall result in **bold**.

Operator	Divergence / Metric	KMeans	MLP
<i>Aggregate</i>			
DISC	—	0.4776 $\pm$ 0.0005	0.7209 $\pm$ 0.0173
<i>Intensity statistics</i>			
Histogram	KL	0.3754 $\pm$ 0.0023	0.3769 $\pm$ 0.0229
Histogram	JS	0.4339 $\pm$ 0.0015	0.4582 $\pm$ 0.0144
Histogram	Total variation	0.4288 $\pm$ 0.0001	0.4579 $\pm$ 0.0108
Histogram	Wasserstein	0.4286 $\pm$ 0.0003	0.4248 $\pm$ 0.0150
Vector	Euclidean	0.4060 $\pm$ 0.0007	0.4061 $\pm$ 0.0303
Vector	Cosine	0.3725 $\pm$ 0.0022	0.3866 $\pm$ 0.0197
<i>LBP (texture)</i>			
LBP	KL	0.3754 $\pm$ 0.0023	0.3769 $\pm$ 0.0229
LBP	JS	0.4339 $\pm$ 0.0015	0.4582 $\pm$ 0.0144
LBP	Total variation	0.4288 $\pm$ 0.0001	0.4579 $\pm$ 0.0108
LBP	Wasserstein	0.4286 $\pm$ 0.0003	0.4248 $\pm$ 0.0150
<i>HOG (shape/orientation)</i>			
HOG	KL	0.2673 $\pm$ 0.0000	0.2747 $\pm$ 0.0177
HOG	JS	0.2653 $\pm$ 0.0012	0.2749 $\pm$ 0.0187
HOG	Total variation	0.2679 $\pm$ 0.0004	0.2744 $\pm$ 0.0170
HOG	Wasserstein	0.2650 $\pm$ 0.0002	0.2786 $\pm$ 0.0157
<i>DTCWT (multi-scale wavelets)</i>			
Level 1	KL	0.3572 $\pm$ 0.0018	0.4777 $\pm$ 0.0203
Level 1	MAD	0.2749 $\pm$ 0.0007	0.2891 $\pm$ 0.0166
Level 2	KL	0.3342 $\pm$ 0.0004	0.3443 $\pm$ 0.0184
Level 2	MAD	0.2725 $\pm$ 0.0005	0.2766 $\pm$ 0.0183
Level 3	KL	0.2612 $\pm$ 0.0015	0.2593 $\pm$ 0.0200
Level 3	MAD	0.2727 $\pm$ 0.0011	0.2680 $\pm$ 0.0230
LL band	KL	0.2775 $\pm$ 0.0007	0.2621 $\pm$ 0.0176
LL band	MAD	0.3580 $\pm$ 0.0015	0.3610 $\pm$ 0.0143

Table 6: Ablation of the diffusion timesteps used for feature extraction on ImageNet. Using the full trajectory gives the strongest performance in both clustering and supervised evaluation.

Scenario	Clust. Acc	Sup. Acc
Full Trajectory	49.1%	60.6%
Early Half	47.8%	58.0%
Late Half	47.0%	59.9%
Best Single Step ($t = 2500$)	47.5%	56.8%

F.1 Tabular Data

Average performance and rank. Table 7 summarizes mean AUROC and mean rank across tabular datasets. **DISC** attains the best average performance (0.860) and the best (lowest) average rank (4.54). Diffusion-enhanced baselines follow, with classical detectors trailing. The gap is not uniform—some classical methods excel on specific domains (e.g., network intrusion, small- d tabular).

Per-dataset results. Table 8 reports per-dataset AUROCs. DISC is consistently competitive and often state-of-the-art. On `http/WBC`, classical one-class methods approach saturation, narrowing the margin. We observe weaker gains on `Wilt` and `landsat`, where low SNR and class imbalance limit the added value of trajectory features; these are promising targets for feature-engineering or per-dataset calibration.

t-SNE examples and real vs. synthetic disentanglement. Figure 11 visualizes DISC embeddings. Across datasets, synthetic OODs form compact, well-separated clusters (cyan), while real OODs (red) sit closer to, but still distinct from, the ID manifold (blue). The improved separation over synthetic perturbations indicates

that diffusion trajectories capture shifts aligned with density-preserving transformations, while still retaining sensitivity to semantic deviations in real OODs. (As before, t-SNE distances are not calibrated across panels.)




Figure 11: t-SNE of DISC features on tabular datasets. Blue: ID, red: real OOD, magenta: synthetic ID, cyan: synthetic OOD. Synthetic perturbations separate cleanly from ID; real OODs are closer yet remain distinguishable.

Characterizing Distributional Shifts with Multi-Statistic Diffusion Trajectories

Metric	DISC (ours)	DDPM(MSE-IFOREST)	CBLOF	IForest	HBOS	PCA	KNN	OCSVM	SOD	ECOD	COPOD	DDPM(MSE)	COF	DDPM(MSE-GEV)	LOF	DDPM(MSE-GPD)	DAGMM
avg_performance	0.860246	0.849808	0.765023	0.763110	0.737901	0.729835	0.708433	0.695064	0.693449	0.667007	0.665289	0.641453	0.627385	0.621617	0.620708	0.608327	0.522257
avg_rank	4.538462	5.076923	6.615385	6.615385	8.000000	8.026411	7.692308	9.461538	9.461538	8.858974	9.166667	11.371795	11.410256	11.730769	10.794872	11.769231	12.410256

Table 7: Average AUROC and average rank over tabular datasets. Lower rank is better.

	DISC	IForest	OCSVM	CBLOF	COF	COPOD	ECOD	HBOS	KNN	LOF	PCA	SOD	DAGMM
1_ALOI	0.965	0.567	0.558	0.552	0.647	0.537	0.563	0.526	0.615	0.666	0.566	0.611	0.520
4_breastw	0.919	0.983	0.803	0.968	0.388	0.997	0.992	0.989	0.970	0.406	0.951	0.940	NaN
5_campaign	0.991	0.717	0.657	0.642	0.574	0.783	0.767	0.785	0.723	0.590	0.728	0.692	0.560
6_cardio	0.712	0.932	0.939	0.899	0.714	0.923	0.936	0.847	0.766	0.663	0.956	0.732	0.750
7_Cardiotog	0.971	0.676	0.779	0.645	0.538	0.670	0.784	0.609	0.562	0.595	0.747	0.517	0.620
8_celeba	1.000	0.704	0.707	0.740	0.386	0.757	0.765	0.762	0.596	0.386	0.794	0.479	0.447
9_census	0.749	0.595	0.549	0.603	0.416	NaN	NaN	0.649	0.669	0.474	0.687	0.621	0.597
10_cover	0.955	0.867	0.926	0.893	0.769	0.886	0.919	0.802	0.860	0.846	0.937	0.745	0.899
11_donors	0.999	0.777	0.724	0.620	0.708	0.818	0.890	0.784	0.819	0.589	0.831	0.560	0.708
12_fault	0.980	0.570	0.477	0.641	0.621	0.439	0.454	0.513	0.730	0.589	0.460	0.681	0.459
14_glass	1.000	0.771	0.354	0.829	0.722	0.724	0.658	0.772	0.823	0.692	0.663	0.734	0.761
16_http	0.965	1.000	0.996	0.996	0.888	0.993	0.981	0.995	0.034	0.275	0.997	0.780	NaN
17_InternetAds	0.906	0.690	0.683	0.706	0.638	0.671	0.671	0.680	0.700	0.658	0.617	0.619	NaN
18_Ionosphere	0.884	0.845	0.759	0.907	0.868	0.793	0.732	0.625	0.883	0.906	0.792	0.864	0.734
19_landsat	0.738	0.476	0.361	0.635	0.535	0.415	0.361	0.551	0.580	0.539	0.358	0.595	0.439
41_Waveform	0.930	0.715	0.563	0.724	0.726	0.750	0.624	0.688	0.738	0.733	0.655	0.686	0.493
42_WBC	0.808	0.990	0.990	0.995	0.609	0.991	0.991	0.987	0.906	0.542	0.982	0.946	NaN
44_Wilt	0.659	0.419	0.313	0.325	0.497	0.334	0.363	0.325	0.484	0.507	0.204	0.533	0.373
47_yeast	0.997	0.378	0.410	0.448	0.445	0.370	0.438	0.396	0.391	0.453	0.412	0.425	0.411

Table 8: Per-dataset AUROC for DISC and baselines (DDPM variants removed for compactness).

References

- Aggarwal, C. C., Hinneburg, A., and Keim, D. A. (2001). On the surprising behavior of distance metrics in high dimensional space. In *International conference on database theory*, pages 420–434. Springer.
- Amodei, D., Olah, C., Steinhardt, J., Christiano, P., Schulman, J., and Mané, D. (2016). Concrete problems in ai safety. *arXiv preprint arXiv:1606.06565*.
- Boult, T. E., Cruz, S., Dhamija, A. R., Gunther, M., Henrydoss, J., and Scheirer, W. J. (2019). Learning and the unknown: Surveying steps toward open world recognition. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, pages 9801–9807.
- Dauncey, S., Holmes, C., Williams, C., and Falck, F. (2024). Approximations to the fisher information metric of deep generative models for out-of-distribution detection. *arXiv preprint arXiv:2403.01485*.
- Ditzel, S., Jaziri, A., Pliushch, I., and Ramesh, V. (2025). Uncertainty-aware decomposed hybrid networks. *arXiv preprint arXiv:2503.19096*.
- Djurisic, A., Bozanic, N., Ashok, A., and Liu, R. (2022). Extremely simple activation shaping for out-of-distribution detection. *arXiv preprint arXiv:2209.09858*.
- Efron, B. (2011). Tweedie’s formula and selection bias. *Journal of the American Statistical Association*, 106(496):1602–1614.
- Fang, Z., Li, Y., Lu, J., Dong, J., Han, B., and Liu, F. (2022). Is out-of-distribution detection learnable? *Advances in Neural Information Processing Systems*, 35:37199–37213.
- Gal, Y. and Ghahramani, Z. (2016). Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *international conference on machine learning*, pages 1050–1059. PMLR.
- Garov, K. and Chaudhuri, K. (2025). A closer look at the learnability of out-of-distribution (ood) detection. *arXiv preprint arXiv:2501.08821*.
- Ghosal, S. S., Sun, Y., and Li, Y. (2024). How to overcome curse-of-dimensionality for out-of-distribution detection? In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 19849–19857.
- Graham, M. S., Pinaya, W. H., Tudosi, P.-D., Nachev, P., Ourselin, S., and Cardoso, J. (2023). Denoising diffusion models for out-of-distribution detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2948–2957.

- Guille-Escuret, C., Noël, P.-A., Mitliagkas, I., Vazquez, D., and Monteiro, J. (2024). Expecting the unexpected: Towards broad out-of-distribution detection. *Advances in Neural Information Processing Systems*, 37:130953–130976.
- Han, S., Hu, X., Huang, H., Jiang, M., and Zhao, Y. (2022). Adbench: Anomaly detection benchmark. *Advances in neural information processing systems*, 35:32142–32159.
- Heil, C. E. and Walnut, D. F. (1989). Continuous and discrete wavelet transforms. *SIAM review*, 31(4):628–666.
- Hendrycks, D. and Gimpel, K. (2016). A baseline for detecting misclassified and out-of-distribution examples in neural networks. *arXiv preprint arXiv:1610.02136*.
- Hendrycks, D., Mazeika, M., and Dietterich, T. (2018). Deep anomaly detection with outlier exposure. *arXiv preprint arXiv:1812.04606*.
- Heng, A., Soh, H., et al. (2024). Out-of-distribution detection with a single unconditional diffusion model. *Advances in Neural Information Processing Systems*, 37:43952–43974.
- Ho, J., Jain, A., and Abbeel, P. (2020). Denoising diffusion probabilistic models. *Advances in neural information processing systems*, 33:6840–6851.
- Hsu, Y.-C., Shen, Y., Jin, H., and Kira, Z. (2020). Generalized odin: Detecting out-of-distribution image without learning from out-of-distribution data. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10951–10960.
- Huang, R., Geng, A., and Li, Y. (2021). On the importance of gradients for detecting distributional shifts in the wild. *Advances in Neural Information Processing Systems*, 34:677–689.
- Humayun, A. I., Amara, I., Vasconcelos, C., Ramachandran, D., Schumann, C., He, J., Heller, K., Farnadi, G., Rostamzadeh, N., and Havaei, M. (2024a). What secrets do your manifolds hold? understanding the local geometry of generative models. *arXiv preprint arXiv:2408.08307*.
- Humayun, A. I., Balestrieri, R., and Baraniuk, R. (2024b). Deep networks always grok and here is why. *arXiv preprint arXiv:2402.15555*.
- Jaziri, A., Ditzel, S., Pliushch, I., and Ramesh, V. (2024). Representation learning in a decomposed encoder design for bio-inspired hebbian learning. In *European Conference on Computer Vision*, pages 203–213. Springer.
- Kingma, D. P. and Dhariwal, P. (2018). Glow: Generative flow with invertible 1x1 convolutions. *Advances in neural information processing systems*, 31.
- Kirchheim, K., Filax, M., and Ortmeier, F. (2022). Pytorch-ood: A library for out-of-distribution detection based on pytorch. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4351–4360.
- Kirsch, A., Rainforth, T., and Gal, Y. (2021). Test distribution-aware active learning: A principled approach against distribution shift and outliers. *arXiv preprint arXiv:2106.11719*.
- Krizhevsky, A., Nair, V., and Hinton, G. (2009). Cifar-10 (canadian institute for advanced research). *Technical Report*.
- Lakshminarayanan, B., Pritzel, A., and Blundell, C. (2017). Simple and scalable predictive uncertainty estimation using deep ensembles. *Advances in neural information processing systems*, 30.
- Lee, G. R., Gommers, R., Waselewski, F., Wohlfahrt, K., and O8217;Leary, A. (2019). Pywavelets: A python package for wavelet analysis. *Journal of Open Source Software*, 4(36):1237.
- Lee, K., Lee, K., Lee, H., and Shin, J. (2018). A simple unified framework for detecting out-of-distribution samples and adversarial attacks. *Advances in neural information processing systems*, 31.
- Li, Y. L., Lu, D., Kirichenko, P., Qiu, S., Rudner, T. G., Bruss, C. B., and Wilson, A. G. (2025). Out-of-distribution detection methods answer the wrong questions. *arXiv preprint arXiv:2507.01831*.
- Liu, F. T., Ting, K. M., and Zhou, Z.-H. (2008). Isolation forest. In *2008 eighth ieee international conference on data mining*, pages 413–422. IEEE.
- Liu, L., Ren, Y., Lin, Z., and Zhao, Z. (2022). Pseudo numerical methods for diffusion models on manifolds. *arXiv preprint arXiv:2202.09778*.
- Liu, W., Wang, X., Owens, J., and Li, Y. (2020). Energy-based out-of-distribution detection. *Advances in neural information processing systems*, 33:21464–21475.

- Liu, Z., Zhou, J. P., Wang, Y., and Weinberger, K. Q. (2023). Unsupervised out-of-distribution detection with diffusion inpainting. In *International Conference on Machine Learning*, pages 22528–22538. PMLR.
- Livernoche, V., Jain, V., Hezaveh, Y., and Ravanbakhsh, S. (2023). On diffusion modeling for anomaly detection. *arXiv preprint arXiv:2305.18593*.
- Metzen, J. H., Genewein, T., Fischer, V., and Bischoff, B. (2017). On detecting adversarial perturbations. *arXiv preprint arXiv:1702.04267*.
- Mundt, M., Hong, Y., Pliushch, I., and Ramesh, V. (2023). A wholistic view of continual learning with deep neural networks: Forgotten lessons and the bridge to active and open world learning. *Neural Networks*, 160:306–336.
- Nalisnick, E., Matsukawa, A., Teh, Y. W., Gorur, D., and Lakshminarayanan, B. (2018). Do deep generative models know what they don’t know? *arXiv preprint arXiv:1810.09136*.
- Nichol, A. Q. and Dhariwal, P. (2021). Improved denoising diffusion probabilistic models. In *International conference on machine learning*, pages 8162–8171. PMLR.
- Oko, K., Akiyama, S., and Suzuki, T. (2023). Diffusion models are minimax optimal distribution estimators. In *International Conference on Machine Learning*, pages 26517–26582. PMLR.
- Pietikäinen, M. (2010). Local binary patterns. *Scholarpedia*, 5(3):9775.
- Pimentel, M. A., Clifton, D. A., Clifton, L., and Tarassenko, L. (2014). A review of novelty detection. *Signal processing*, 99:215–249.
- Pinaya, W. H., Graham, M. S., Kerfoot, E., Tudosiu, P.-D., Dafflon, J., Fernandez, V., Sanchez, P., Wolleb, J., Da Costa, P. F., Patel, A., et al. (2023). Generative ai for medical imaging: extending the monai framework. *arXiv preprint arXiv:2307.15208*.
- Quiñonero-Candela, J., Sugiyama, M., Schwaighofer, A., and Lawrence, N. D. (2022). *Dataset shift in machine learning*. Mit Press.
- Ren, J., Fort, S., Liu, J., Roy, A. G., Padhy, S., and Lakshminarayanan, B. (2021). A simple fix to mahalanobis distance for improving near-ood detection. *arXiv preprint arXiv:2106.09022*.
- Riba, E., Mishkin, D., Ponsa, D., Rublee, E., and Bradski, G. (2020). Kornia: an open source differentiable computer vision library for pytorch. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 3674–3683.
- Rozsa, A. and Boulton, T. E. (2019). Improved adversarial robustness by reducing open space risk via tent activations. *arXiv preprint arXiv:1908.02435*.
- Salimans, T., Karpathy, A., Chen, X., and Kingma, D. P. (2017). Pixelcnn++: Improving the pixelcnn with discretized logistic mixture likelihood and other modifications. *arXiv preprint arXiv:1701.05517*.
- Scheirer, W. J., de Rezende Rocha, A., Sapkota, A., and Boulton, T. E. (2012). Toward open set recognition. *IEEE transactions on pattern analysis and machine intelligence*, 35(7):1757–1772.
- Scheirer, W. J., Jain, L. P., and Boulton, T. E. (2014). Probability models for open set recognition. *IEEE transactions on pattern analysis and machine intelligence*, 36(11):2317–2324.
- Singh, M., Parameswaran, V., and Ramesh, V. (2008). Order consistent change detection via fast statistical significance testing. In *2008 IEEE Conference on Computer Vision and Pattern Recognition*, pages 1–8. IEEE.
- Sohl-Dickstein, J., Weiss, E., Maheswaranathan, N., and Ganguli, S. (2015). Deep unsupervised learning using nonequilibrium thermodynamics. In *International conference on machine learning*, pages 2256–2265. pmlr.
- Song, Y., Sohl-Dickstein, J., Kingma, D. P., Kumar, A., Ermon, S., and Poole, B. (2020). Score-based generative modeling through stochastic differential equations. *arXiv preprint arXiv:2011.13456*.
- Sun, Y., Guo, C., and Li, Y. (2021). React: Out-of-distribution detection with rectified activations. *Advances in neural information processing systems*, 34:144–157.
- Sun, Y. and Li, Y. (2022). Dice: Leveraging sparsification for out-of-distribution detection. In *European conference on computer vision*, pages 691–708. Springer.
- Sun, Y., Ming, Y., Zhu, X., and Li, Y. (2022). Out-of-distribution detection with deep nearest neighbors. In *International Conference on Machine Learning*, pages 20827–20840. PMLR.

- Wang, L., Zhang, X., Su, H., and Zhu, J. (2024). A comprehensive survey of continual learning: Theory, method and application. *IEEE transactions on pattern analysis and machine intelligence*, 46(8):5362–5383.
- Wang, Z., Bovik, A. C., Sheikh, H. R., and Simoncelli, E. P. (2004). Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing*, 13(4):600–612.
- Yang, Y., Cheng, D., Fang, C., Wang, Y., Jiao, C., Cheng, L., Wang, N., and Gao, X. (2024). Diffusion-based layer-wise semantic reconstruction for unsupervised out-of-distribution detection. *Advances in Neural Information Processing Systems*, 37:26846–26871.
- Zhang, J., Fu, Q., Chen, X., Du, L., Li, Z., Wang, G., Han, S., Zhang, D., et al. (2022). Out-of-distribution detection based on in-distribution data patterns memorization with modern hopfield energy. In *The Eleventh International Conference on Learning Representations*.
- Zhang, L., Goldstein, M., and Ranganath, R. (2021). Understanding failures in out-of-distribution detection with deep generative models. In *International Conference on Machine Learning*, pages 12427–12436. PMLR.
- Zhang, R., Isola, P., Efros, A. A., Shechtman, E., and Wang, O. (2018). The unreasonable effectiveness of deep features as a perceptual metric. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 586–595.
- Zhou, K., Liu, Z., Qiao, Y., Xiang, T., and Loy, C. C. (2022). Domain generalization: A survey. *IEEE transactions on pattern analysis and machine intelligence*, 45(4):4396–4415.