

Dual Monitor Mounts for Design Desks

DT Workshop Equipment Reference — D&T / STEM resource for school workshops | Design & Documentation



Photo: NASA/MSFC — Public domain — via Wikimedia Commons (Skylab_Dual_X-Ray_Telescope_(7012080).jpg)

Dual monitor mounts hold two displays on adjustable arms above the desk, freeing the work surface and letting students position screens for CAD, drawing and reference side by side. Clamp and grommet mounts fit most school desks.

Key Features

- Holds two 19-32 inch monitors
- Height, tilt and pivot adjustments
- Clamp or grommet desk mounting
- VESA 75/100 mounting standards
- Gas-spring or manual arms

Typical Uses in the Workshop

- Run CAD and reference documents side by side
- Position screens ergonomically for drawing
- Free desk space for sketching and models
- Support dual-screen teaching layouts

Safe Operation

1. Fit the VESA plates to the monitors first
2. Clamp the mount firmly to the desk edge
3. Adjust arm tension to hold the position
4. Arrange screens at eye level and arm's reach
5. Tidy cables along the arms

SAFETY NOTES

- Check the clamp holds the desk thickness
- Keep cables clear of the arm joints
- Do not exceed the rated monitor weight
- Tighten all bolts after assembly
- Check the mount is secure before use

Maintenance & Consumables

- Tighten loose bolts termly
- Clean the arms and joints
- Check gas springs hold position
- Re-route cables when rearranging
- Keep spare VESA screws in stock

Specification & Buying Notes

Choose mounts rated above the monitor weight with gas-spring height adjustment. Buy the VESA pattern to match the screens. A warranty and sturdy clamping design matter in classrooms.