

## 3D Printer Nozzle Cleaning Needle Kits

DT Workshop Equipment Reference — D&T / STEM resource for school workshops | Consumables & Spares



Photo: David Elliott from UK — CC BY 2.0 — via Wikimedia Commons (3D\_printer\_nozzle\_extruding\_plastic\_(15608959541).jpg)

Nozzle cleaning needle kits are fine steel needles sized to clear clogs from 3D printer nozzles, unblocking obstructions without removing the hotend. A set of diameters matches the nozzle orifice sizes in use.

### Key Features

- Needle diameters 0.2-0.8 mm
- Flexible steel wires
- Long reach for hotends
- Case sets with holders
- Brass brush companions

### Typical Uses in the Workshop

- Clear blocked and partial nozzles
- Maintain reliable extrusion
- Clean between filament colours
- Clear cold pulls residue

### Safe Operation

1. Heat the nozzle to printing temperature
2. Remove the filament and bowden tube
3. Insert the needle through the nozzle tip
4. Push and twist to break the clog
5. Purge with fresh filament after

### SAFETY NOTES

- The hotend is hot - keep hands clear
- Use pliers for the needles near heat
- Never probe a nozzle while printing
- Disconnect power for deep cleaning
- Store needles point-down

#### Maintenance & Consumables

---

- Return needles to the case
- Replace bent needles
- Check the case contents
- Keep a spare set per printer bank
- Clean needles with a cloth

#### Specification & Buying Notes

---

A needle kit with 0.2-0.6 mm sizes and a holder covers most printers. Quality steel needles stay straight; cheap wire bends inside the nozzle.