
Launch! Markdown Sample

This document is both a test file for !MKDOWN and a compact syntax reference. It intentionally exercises the Markdown features understood by Launch!.

Contents

- * Paragraphs and inline styles
- * Heading levels
- * Block quotes
- * Lists
- * Tables
- * Links

Use these internal links in [Show](#) to test heading navigation.

Paragraphs and inline styles

This is a normal paragraph of dummy text. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Integer vel neque sit amet lorem malesuada fringilla. Suspendisse potenti. Curabitur vitae justo at erat luctusposuere.

Plain text can contain *italic text*, **bold text**, underline text and inline code.

Launch! also supports strikethrough and HTML-style strike. Underline can be written as HTML underline or with the Launch! extension double-brace underline.

Superscript uses HTML tags, for example $E = mc^2$. Subscript works too, for example H_2O .

Styles can be combined: ***bold italic***, **bold with code nearby**, and underlined bold text.

Escaped Markdown characters can be shown literally: `*stars*` and `#hash`.

Heading levels

There are 6 heading levels that are formatted differently for easy recognition.

Heading 1

Above is a level 1 heading.

Heading 2

Launch! Markdown Sample

This document is both a test file for !MKDOWN and a compact syntax reference. It intentionally exercises the Markdown features understood by Launch!.

Contents

- * Paragraphs and inline styles
- * Heading levels
- * Block quotes
- * Lists
- * Tables
- * Links

Use these internal links in Show to test heading navigation.

Paragraphs and inline styles

This is a normal paragraph of dummy text. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Integer vel neque sit amet lorem malesuada fringilla. Suspendisse potenti. Curabitur vitae justo at erat luctusposuere.

Plain text can contain *italic text*, **bold text**, underline text and inline code.

Launch! also supports strikethrough and HTML-style strike. Underline can be written as HTML underline or with the Launch! extension double-brace underline.

Superscript uses HTML tags, for example $E = mc^2$. Subscript works too, for example H_2O .

Styles can be combined: ***bold italic***, **bold with code nearby**, and underlined bold text.

Escaped Markdown characters can be shown literally: `*stars*` and `#hash`.

Heading levels

There are 6 heading levels that are formatted differently for easy recognition.

Heading 1

Above is a level 1 heading.

Heading 2

Above is a level 2 heading.

Heading 3

Above is a level 3 heading.

Heading 4

Above is a level 4 heading.

Heading 5

Above is a level 5 heading.

Heading 6

Above is a level 6 heading.

Block quotes

This is a block quote. It should be visually distinct from ordinary body text and is useful for quotations, notes, and callouts.

A second quoted paragraph provides enough text to test wrapping and continuation across the preview width.

Unordered lists

- * First item
- * Second item
 - * Nested item A
 - * Nested item B
- * Third item

- * Asterisk list marker
- * Plus list marker

Ordered lists

1. First numbered item
2. Second numbered item
3. Third numbered item
 1. Nested numbered item
 2. Another nested item

Task lists

- * [] An unfinished task
- * [x] A completed task
- * [X] Completed with an upper-case X

Definition list

Launch!

A text-mode launcher and accessory suite for DOS.

Markdown

A lightweight markup language used for formatted plain-text documents.

Horizontal rule

Above this text should be a horizontal line.

Links

This is an [inline link](#).

Pipe table

Feature	Status	Notes
Headings	Yes	Levels
Lists	Yes	Ordered
Tables	Yes	Rendered
Code	Yes	Inline
Quotes	Yes	Styled

Plain-column table

Name	Type	Example
Alpha	Text	Ordinary content
Beta	Number	12345
Gamma	Mixed	DOS / VGA / EGA

Fenced code block

```
# include

int main(void)
{
    printf("Hello from DOS!\n");
    return 0;
}
```

A tilde fence is supported too.
This block should be rendered in the code style.

Indented code

```
REM This is an indented code block  ECHO Launch! Markdown sample  DIR
C:DOCS
```

Footnote-style markers

Launch! recognizes footnote-style markers in graphical output.^[^1]

^[^1]: This line is useful for testing the small footnote-style rendering.

Long wrapping paragraph

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Pellentesque sed diam vitae lacus suscipit aliquam. Morbi feugiat, sem at placerat faucibus, erat justo condimentum velit, non tempor magna lectus vitae metus. Praesent fermentum, mauris vitae feugiat malesuada, libero erat sollicitudin sapien, vitae tincidunt justo magna sit amet ligula. This paragraph is deliberately long enough to exercise soft wrapping in the editor, text preview, Focus mode, maximized view, graphical Show mode, printing, and exp

Character and punctuation test

ASCII punctuation: ! " # \$ % & ' () + , - . / : ; ? @ [] ^ { | } ~

Numbers: 0123456789

Common DOS text: C:LAUNCH!MD.EXE C:DOCSSAMPLE.MD

Images and media placeholders

Images are not rendered as raster graphics, but their Markdown syntax is recognized and represented by a media placeholder:

Image: example.bmp | Example image

End of Launch! Markdown sample.