

Radiance Data Assimilation in WRFDA

Jamie Bresch

Zhiquan Liu, Tom Auligné


WRFDA tutorial
Aug 2016



- Introduction to radiance data assimilation
 - Principles of satellite measurements
 - Introduction to Radiative Transfer theory
 - Elements of Radiance DA
- Practical aspects with WRFDA

Part I: Introduction to radiance data assimilation


Environment monitoring satellites



Valuable information from satellite measurements

- images
- retrieved/derived products
- radiances

Types of satellites




ECMWF Data Coverage (All obs DA) - AMSU-A

05/Jul/2015; 06 UTC

Total number of obs = 667314

Polar-orbiting satellites




ECMWF Data Coverage (All obs DA) - GRAD

05/Jul/2015; 06 UTC

Total number of obs = 483826

Geostationary satellites




ECMWF Data Coverage (All obs DA) - GPSRO

05/Jul/2015; 06 UTC

Total number of obs = 15867

GPS satellites



Satellite instruments / sensors

Types of sensors

- Passive
 - Visible
 - IR
 - Microwave
- Active
- Occultation

Scan strategies and viewing geometry

affecting coverage and
ground or field-of-view resolution

cross-track scan

- resolution degrades toward the edge of the swath because the viewing angle changes across the swath

conical scan

- constant ground resolution
- generally narrower swaths than cross-track scan swaths






Figure 2. GPM swath measurements
image credit: NASA

What do satellite instruments measure?



Satellite passive sensors

- observe radiation emitted and scattered from the earth's surface and atmosphere at discrete wavelength intervals

- measured radiation is calibrated and commonly processed into a unit of power known as "**spectral radiance**"
- radiance is related to geophysical atmospheric variables by the **radiative transfer equation**
- radiances are often converted to "**brightness temperature**" (equivalent blackbody temperature, by inverting Plank function)

Radiative Transfer

$$L(v) = \int_0^{\infty} B(v, T(z)) \left[\frac{d\tau(v)}{dz} \right] dz + \text{Surface} + \text{Cloud/Rain Aerosol}$$

TOA radiance at frequency v Planck function Atmospheric Absorption (weighting function)
 Emission/reflection Diffusion/scattering


Surface emission R_s

Up-welling atmosphere emission R_A


Reflected solar radiation R_o

Down-welling & reflected atmos.




Emission (R_D)



Passive Sensors from Weather/Environment Satellites




Atmospheric gas absorption-transmission



Satellite sensors are designed to make use of the frequency-dependent atmospheric absorption

Weighting functions



Weighting functions indicate the contribution to the outgoing radiance from various layers of the atmosphere

Weight functions are frequency (channel) dependent

Channel selection for NWP data assimilation

- Atmospheric sounding channels (measured radiance has no contribution from the surface)
- By selecting a number of channels with varying absorption strengths (i.e. varying peaking weight functions) we sample the atmospheric temperature at different altitudes
- Channels whose peaks of the weighting functions occur above the model top should not be used in data assimilation
- Window channels are sensitive to properties associated with earth and ocean surfaces as well as clouds

Radiance Assimilation in 3D/4D-VAR

Solving the inverse problem by minimizing a cost function


$$J(\mathbf{x}) = \frac{1}{2} (\mathbf{x} - \mathbf{x}_b)^T \mathbf{B}^{-1} (\mathbf{x} - \mathbf{x}_b) + \frac{1}{2} [\mathbf{y} - H(\mathbf{x})]^T \mathbf{R}^{-1} [\mathbf{y} - H(\mathbf{x})]$$



Observation operators include (Fast) Radiative Transfer Model

- Solving the inverse problem (extracting atmospheric information from the radiance) along with other observations in a more consistent way.
- Pixels are no longer independent of each other due to the horizontal correlation in B.
- Can affect non-measured quantities through multivariate correlation in B.


- ✓ Radiative transfer model
- ✓ Channel selection
- ✓ Observation errors
- ✓ Bias correction
- ✓ Quality control
- ✓ Thinning
- ✓ Monitoring



Part II: Practical implementation with WRFDA


- WRFDA applications
- Practical aspects
 - Data ingest (sources, instruments)
 - Radiative transfer model
 - Channel selection and observation errors
 - Variational bias correction
 - Diagnostics and monitoring

Assimilation and Verification Domain




- WRF/WRFDA V3.6+ (V3.6 with modifications and fixes)
- 1-hPa model top, 71 levels, 60-km resolution
- low/lateral boundary conditions from ERA-interim
- Snow from NCEP FNL
- 6-hour cycling starting from 2007070100
- 240-second time step, 180-sec for a couple dates that exceeded CFL criteria
- WSM 5-class microphysics
- RRTMG SW/LW radiation
- Ozone and aerosol climatology
- MYNN surface layer
- MYNN 2.5 TKE PBL
- Grell 3D cumulus parameterization
- conv: conventional data only
- conv_amsua: conventional data and AMSU-A radiances from NOAA-15, NOAA-16, NOAA-18, EOS-AQUA, METOP-2

RMSE 2007070112-2007071506 (FC06h every 06h)



verification against ERA-interim analysis

RMSE Profiles 2007070112-2007071500 (FC06h every 12h)



verification against SOUNDS

Quality control

- **Specific QC for each sensor**




AMSU-A, AMSU-B, MHS, SSMIS, AIRS,
AMSR2...

- **Pixel-level QC**

- Reject **limb** observations
- Reject pixels over **land** and **sea-ice**
- **Cloud/Precipitation** detection
- **Synergy** with imager (AIRS/VIS-NIR)

- **Channel-level QC**



- **Gross check**
(innovations $< 15 \text{ K}$)
- **First-guess check**
(innovations $< 3\sigma_0$).




Quality control

monitoring and blacklisting

Global
radiance
monitoring
against
ERA-
Interim




Bias Correction




Thinning

Dense data are very likely correlated, which is not taken into account in the observation covariance matrix R

No Thinning
noaa-18-amsua_ch0007 OBS 19869/26599



120km Thinning Mesh
noaa-18-amsua_ch0001 OBS 693/919



Variational Bias Correction (VarBC) in WRFDA

Modeling of errors in satellite radiances:

$$y = H(x_t) + B(\beta) + \varepsilon$$

$$\left\{ \begin{array}{l} \langle \varepsilon \rangle = 0 \\ B(\beta) = \sum_{i=1}^N \beta_i p_i \end{array} \right.$$

Bias-correction coefficients

Predictors:

- Offset (i.e., 1)
- 1000-300mb thickness
- 200-50mb thickness
- Surface skin temperature
- Total column water vapor
- Scan, Scan², Scan³

Bias parameters can be estimated within the **variational assimilation**, jointly with the atmospheric model state (Derber and Wu 1998) (Dee 2005) (Auligné et al. 2007)

Inclusion of the bias parameters in the control vector : $x^T \rightarrow [x, \beta]^T$

$$\mathbf{J}(\mathbf{x}, \beta) = (\mathbf{x}_b - \mathbf{x})^T \mathbf{B}_x^{-1} (\mathbf{x}_b - \mathbf{x}) + [\mathbf{y} - H(\mathbf{x}) - B(\beta)]^T \mathbf{R}^{-1} [\mathbf{y} - H(\mathbf{x}) - B(\beta)] + (\beta_b - \beta)^T \mathbf{B}_\beta^{-1} (\beta_b - \beta)$$

\mathbf{J}_b : background term for \mathbf{x}

\mathbf{J}_o : corrected observation term

\mathbf{J}_p : background term for β

Can be used for radiance **offline monitoring** by removing J_b term and other obs., and using some analysis fields as reference.

Sensors that can be assimilated in WRFDA

- NCEP global BUFR format radiance data within a 6-h time window (27 sensors from 12 satellites)
 - 6 HIRS from NOAA-16/17/18/19, METOP-2/1
 - 7 AMSU-A from NOAA-15/16/18/19, EOS-2, METOP-2/1
 - 3 AMSU-B from NOAA-15/16/17
 - 4 MHS from NOAA-18/19, METOP-2/1
 - 1 AIRS from EOS-2
 - 2 IASI from METOP-2/1
 - 1 ATMS from NPP
 - 3 SEVIRI from Meteosat-8/9/10
- JAXA GCOM-W1 AMSR-2 radiance data in HDF5 format
- NRL/AFWA/NESDIS produced DMSP-16/17/18/19 SSMI/S BUFR radiance data
- FY-3 MWTS and MWHS, CMA binary format.

Data sources and ingest

NCEP near real-time ftp server with radiance BUFR data

[http://www.ftp.ncep.noaa.gov/data/nccf/com/gfs/prod/gdas.\\${yyyymmddhh}](http://www.ftp.ncep.noaa.gov/data/nccf/com/gfs/prod/gdas.${yyyymmddhh})

NOAA archive: <http://nomads.ncdc.noaa.gov/data/gdas>

NCAR CISL archive: <http://rda.ucar.edu/datasets/ds735.0>

NCAR CISL archive: <http://rda.ucar.edu/datasets/ds099.0>

NCEP naming convention

gdas1.t^{hhz}.1bamua.tm00.bufr_d
gdas1.t^{hhz}.1bamub.tm00.bufr_d
gdas1.t^{hhz}.1bhrs3.tm00.bufr_d
gdas1.t^{hhz}.1bhrs4.tm00.bufr_d
gdas1.t^{hhz}.1bmhs.tm00.bufr_d
gdas1.t^{hhz}.airsev.tm00.bufr_d
gdas1.t^{hhz}.atms.tm00.bufr_d
gdas1.t^{hhz}.mtiasi.tm00.bufr_d
gdas1.t^{hhz}.sevcsr.tm00.bufr_d

^{hh} is the analysis time: [00/06/12/18](#)

WRFDA naming convention

amsua.bufr
amsub.bufr
hirs3.bufr
hirs4.bufr
mhs.bufr
airs.bufr
atms.bufr
iasi.bufr
seviri.bufr

JAXA AMSR2 radiance HDF5 data

http://suzaku.eorc.jaxa.jp/GCOM_W/data/data_w_index.html

JAXA naming convention

GW1AM2_201210271433_082A_L1SGRTBR_1110110.h5

WRFDA naming convention

L1SGRTBR-01.h5

- ✓ Direct input to WRFDA, no pre-processing required.
- ✓ Quality control, thinning, time and domain check, bias correction are done inside WRFDA

Data sources and ingest

Namelist switches (in wrfvar4 section) to decide if **reading** the data or not

use_amsuaobs	use_hirs3obs	use_airobs	use_sevirirobs
use_eos_amsuaobs	use_hirs4obs	use_iasiobs	
use_amsubobs			
use_mhsobs			
use_atmsobs			
use_amsr2obs			

Choose Radiative Transfer Model

Controlled by the namelist variable: “**rtm_option**” (under wrfvar14)

2 = CRTM (Community Radiative Transfer Model)

JCSDA (Joint Center for Satellite Data Assimilation)

ftp://ftp.emc.ncep.noaa.gov/jcsda/CRTM/

ftp://ftp.emc.ncep.noaa.gov/jcsda/CRTM/CRTM_User_Guide.pdf

Latest available released version: CRTM REL-2.1.3 (CRTM REL-2.2.3 is available)

Version included in WRFDA: CRTM REL-2.1.3

CRTM code and (limited) coeffs included in WRFDA release (since WRFDA V3.2.1)

1 = RTTOV (Radiative Transfer for TOVS)

EUMETSAT (European Organisation for the Exploitation of Meteorological Satellites)

http://research.metoffice.gov.uk/research/interproj/nwpsaf/rtm

Latest released version: RTTOV 11.3,

Version used in WRFDA: RTTOV 11, 11.1, 11.2, 11.3

Channel selection and error specification

```
WRFDA/var/run/radiance_info>ls -l
```

```
total 160
-rw-r--r-- 1 hclin users 17790 Aug 22 17:01 eos-2-aira.info
-rw-r--r-- 1 hclin users 1033 Aug 22 17:01 eos-2-amsua.info
-rw-r--r-- 1 hclin users 1036 Aug 22 17:01 metop-2-amsua.info
-rw-r--r-- 1 hclin users 391 Aug 22 17:01 metop-2-mhs.info
-rw-r--r-- 1 hclin users 1021 Aug 22 17:01 noaa-15-amsua.info
-rw-r--r-- 1 hclin users 391 Aug 22 17:01 noaa-15-amsub.info
-rw-r--r-- 1 hclin users 1277 Aug 22 17:01 noaa-15-hirs.info
-rw-r--r-- 1 hclin users 391 Aug 22 17:01 noaa-16-amsub.info
-rw-r--r-- 1 hclin users 1036 Aug 22 17:01 noaa-18-amsua.info
-rw-r--r-- 1 hclin users 1286 Aug 22 17:01 noaa-18-hirs.info
-rw-r--r-- 1 hclin users 391 Aug 22 17:01 noaa-18-mhs.info
```

gcom-w-1-amsr2.info

				clear-sky obs error						
478	5	1	1	0	0.8660000000E+00	0.0000000000E+00	21.93555			
478	6	1	1	0	1.1290000000E+00	1.0000000000E+00	40.92418			
478	7	1	1	0	1.2270000000E+00	0.0000000000E+00	28.30175			
478	8	1	1	0	1.7470000000E+00	1.0000000000E+00	57.58830			
478	9	1	1	0	1.6000000000E+00	0.0000000000E+00	12.69287			
478	10	1	1	0	2.6790000000E+00	1.0000000000E+00	27.33099			
478	11	1	1	0	1.1790000000E+00	0.0000000000E+00	23.24269			
478	12	1	1	0	2.2680000000E+00	1.0000000000E+00	53.35099			
478	13	1	-1	0	2.1310000000E+00	0.0000000000E+00	36.07700			
478	14	1	-1	0	4.0750000000E+00	1.0000000000E+00	33.61592			

-1: not used; 1: used

cloudy obs error
(AMSR2 only)

Setup and run WRFDA with radiances

To run **WRFDA**, first create a working directory,
for example, WRFDA/var/test, then follow the steps below:

cd WRFDA/var/test (go to the working directory)

In -sf WRFDA/run/LANDUSE.TBL ./LANDUSE.TBL

In -sf \$DAT_DIR/rc/2007010200/wrfinput_d01 ./fg (link first guess file as fg)

In -sf WRFDA/var/obsproc/obs_gts_2007-01-02_00:00:00.3DVAR ./ob.ascii (link OBSPROC processed
observation file as ob.ascii)

In -sf \$DAT_DIR/be/be.dat ./be.dat (link background error statistics as be.dat)

In -sf WRFDA/var/da/da_wrfvar.exe ./da_wrfvar.exe (link executable)

In -sf \$DAT_DIR/2007010200/gdas1.t00z.1bamua.tm00.bufr_d ./amsua.bufr (link radiance bufr files)

In -sf WRFDA/var/run/radiance_info ./radiance_info (radiance_info is a directory)

In -sf WRFDA/var/run/VARBC.in ./VARBC.in

(CRTM only) > In -sf WRFDA/var/run/crtm_coeffs ./crtm_coeffs #(crtm_coeffs is a directory)

this step is not needed if setting crtcoeffs_path='your_full_path_where_crtm_coeffs_reside'

(RTTOV only) > In -sf your_path/rtcoeff_rttov10/rttov7pred51L ./rttov_coeffs #(rttov_coeffs is a directory)

vi namelist.input (&wrfvar4, &wrfvar14, &wrfvar21, &wrfvar22)

da_wrfvar.exe >&! wrfda.log

Control which instruments to assimilate and which CRTM/RTTOV coefficient files to load

Sample namelist settings for instruments onboard various satellites:

&wrfvar14

```
RTMINIT_NSENSOR = 14
RTMINIT_PLATFORM = 12, 1, 1, 1, 1, 9,10, 1, 1,17, 1, 1, 10, 9, 2
RTMINIT_SATID = 3,16,18,19, 2, 2,15,16, 0,18, 19, 2, 2,16
RTMINIT_SENSOR = 21, 3, 3, 3, 3, 3, 3, 4, 4,19,15, 15,15,11,10
```

MSG-3-SEVIRI (12, 3, 21)

NOAA-16-AMSUA

NOAA-18-AMSUA

NOAA-19-AMSUA

EOS-2-AMSUA (9, 2, 3)

METOP-2-AMSUA (10, 2, 3)

NOAA-15-AMSUB (1, 15, 4)

NOAA-16-AMSUB

JPSS-0-ATMS (17, 0, 19)

NOAA-18-MHS (1, 18, 15)

NOAA-19-MHS

METOP-2-MHS (10, 2, 15)

EOS-2-AIRS (9, 2, 11)

DMSP-16-SSMIS (2, 16, 10)

GCOM-W1-AMSR2 (29, 1, 63)

CRTM and RTTOV have different naming convention for referring sensors

CRTM

seviri_m10.SpcCoeff.bin

amsua_n19.SpcCoeff.bin

RTTOV

rtcoef_msg_3_seviri.dat

rtcoef_noaa_19_amsua.dat

WRFDA is designed to use specified "instrument triplets" to retrieve proper names internally for the rtm_option selected

RTTOV Users Guide

http://nwpsaf.eu/deliverables/rtm/docs_rttov11/users_guide_11_v1.4.pdf

Table 2 and Table 3

Instrument triplets	platform_id
	satellite_id
	sensor_id

platform	platform_id	satellite_id
NOAA	1	15, 16, 17, 18 ,19
METOP	10	1, 2
EOS	9	2
JPSS	17	0
MSG	12	1, 2, 3
DMSP	2	16, 17, 18, 19
FY3	23	1, 2
GCOM-W	29	1

```

metop-2 = metop-a
metop-1 = metop-b
jpss-0 = npp
msg-1 = meteosat-8
msg-2 = meteosat-9
msg-3 = meteosat-10

```

sensor	sensor_id
HIRS	0
AMSU-A	3
AMSU-B	4
SSMIS	10
AIRS	11
MHS	15
IASI	16
ATMS	19
SEVIRI	21
FY3 MWTS	40
FY3 MWHS	41
AMSR2	63

Radiance namelist variables

THINNING: Logical, TRUE will perform thinning

THINNING_MESH (30): Real array with dimension RTMINIT_NSENSOR, values indicate thinning mesh (in KM) for different sensors.

QC_RAD=true: Logical, control if perform quality control, always set to TRUE.

WRITE_IV_RAD_ASCII: Logical, controls writing of Observation minus Background files, which are ASCII format and separated by sensors and processors.

WRITE_OA_RAD_ASCII: Logical, controls writing of Observation minus Analysis files (including also O minus B), which are ASCII format and separated by sensors and processors.

ONLY_SEA_RAD: Logical, controls if only assimilating radiance over water.

USE_CRTM_KMATRIX: new from Version 3.1.1, much faster. Set to TRUE

USE_RTTOV_KMATRIX: new from version 3.3, much faster. Set to TRUE

Radiance namelist (VarBC related)

USE_VARBC=true

freeze_varbc=false (VarBC coeffs not changed during minimization)

varbc_factor=1. (for scaling the VarBC preconditioning)

varbc_nbgerr=5000, (default value prior to V3.3.1 is 1 which is improper)

varbc_nobsmin=500. (defines the minimum number of observations required for the computation of the predictor statistics during the first assimilation cycle. If there are not enough data (according to "VARBC_NOBSMIN") on the first cycle, the next cycle will perform a coldstart again)

Variational Bias Correction (VarBC)

VARBC.in file is an ASCII file that controls all of what is going into the VarBC.

Sample VARBC.in

VARBC version 1.0 - Number of instruments:

2

Platform_id Sat_id Sensor_id Nchanl Npredmax

1 15 3 5 8

-----> Bias predictor statistics: Mean & Std & Nbgerr

1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
0.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
<u>10000</u>							

-----> Chanl_id Chanl_nb Pred_use(-1/0/1) Param

5	5	0	0	0	0	0	0
6	6	0	0	0	0	0	0
7	7	0	0	0	0	0	0
8	8	0	0	0	0	0	0
9	9	0	0	0	0	0	0

Platform_id Sat_id Sensor_id Nchanl Npredmax

1 16 4 3 8

-----> Bias predictor statistics: Mean & Std & Nbgerr

1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
0.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
10000	10000	10000	10000	10000	10000	10000	10000

-----> Chanl_id Chanl_nb Pred_use(-1/0/1) Param

3	3	0	0	0	0	0	0
4	4	0	0	0	0	0	0
5	5	0	0	0	0	0	0

Cold starting from an empty parameter file for the first cycle

Not used any more.
Now controlled by
namelist “varbc_nbgerr”

Sample VARBC.out (output from WRF-Var, used as VARBC.in for the next cycle)

VARBC version 1.0 - Number of instruments:

4

Platform_id Sat_id Sensor_id Nchanl Npredmax

1 15 4 5 8

----> Bias predictor statistics: Mean & Std & Nbgerr

	1.0	9273.1	8677.8	290.4	24.0	51.7	3502.8	260484.8
0.0	273.5	293.3	8.0	12.3	28.9	2827.2	252657.9	
10000	10000	10000	10000	10000	10000	10000	10000	

----> Chanl_id Chanl_nb Pred_use(-1/0/1) Param

1	1	0	0	0	0	0	0	-3.400	0.000	0.000	0.000	0.000	0.000	0.000	0.000
2	2	0	0	0	0	0	0	-0.200	0.000	0.000	0.000	0.000	0.000	0.000	0.000
3	3	1	1	1	1	1	1	1.213	-0.062	0.003	-0.070	0.008	-0.230	-0.111	-0.024
4	4	1	1	1	1	1	1	3.056	0.050	0.053	0.015	-0.059	0.304	0.241	0.203
5	5	1	1	1	1	1	1	0.869	0.034	-0.089	0.074	0.019	-0.118	-0.031	0.022

Platform_id Sat_id Sensor_id Nchanl Npredmax

1 16 4 5 8

----> Bias predictor statistics: Mean & Std & Nbgerr

	1.0	9280.2	8641.2	290.0	24.1	52.6	3568.9	264767.4
0.0	209.5	245.9	7.9	11.3	28.3	2792.1	249977.0	
10000	10000	10000	10000	10000	10000	10000	10000	

----> Chanl_id Chanl_nb Pred_use(-1/0/1) Param

1	1	0	0	0	0	0	0	0	0.700	0.000	0.000	0.000	0.000	0.000	0.000	
2	2	0	0	0	0	0	0	0	-0.800	0.000	0.000	0.000	0.000	0.000	0.000	
3	3	1	1	1	1	1	1	1	0.372	-0.028	0.010	0.060	0.025	0.117	0.023	-0.042
4	4	1	1	1	1	1	1	1	0.968	0.016	-0.003	-0.041	0.045	-0.018	-0.030	-0.028
5	5	1	1	1	1	1	1	1	-3.290	0.073	-0.093	0.096	0.018	0.011	0.010	0.004

Controls whether a cold-start (if 0)
Or warm-start (if 1) VarBC

Bias correction coefficients for 8 predictors
(used only for warm-start case)

Radiance namelist (cloudy radiance related)

&wrfvar14

crtm_cloud=true

to include the cloud effect in the CRTM calculation

&wrfvar7

cloud_cv_options=1

to get **cloud water** and **rainwater** analysis increments through the total water control variable modeling via a warm-rain scheme

Other **cloud_cv_options** (with additional cloud variables included) requires WRFDA to be compiled differently. The implementation is still preliminary and ad hoc.

For now, proper quality control procedures and observation error assignments for cloudy radiance are only implemented for AMSR2 instrument. The capability is available in a WRFDA beta release.

<http://www2.mmm.ucar.edu/wrf/users/wrfda/beta.html>

- ✓ http://www2.mmm.ucar.edu/wrf/users/wrfda/Docs/WRFDA_hydrometeors_and_cloudy_radiance.pdf

Diagnostics

```
Reading radiance 1b data from amsua.bufr
Bufr file date is      2015      7      9      12
amsua
num_tovs_file num_tovs_global num_tovs_local num_tovs_used num_tovs_thinned
 269588     3528     152      58      94
Allocating space for radiance innov structure 3 noaa-19-amsua 58
Observation summary
  ob time 1
    sound          102 global,      0 local
    synop           939 global,      0 local
    pilot            90 global,      0 local
    satem            36 global,      4 local
    geoamv          30171 global,   708 local
    airep          20533 global,      0 local
    gspsw            446 global,      0 local
    gpsrf           1673 global,      0 local
    metar            2809 global,      0 local
    ships             156 global,      0 local
    profiler          21 global,      0 local
    buoy              529 global,      0 local
    radiance          3528 global,     58 local
    sonde_sfc         102 global,      0 local

VARBC: Applying bias correction for noaa-15-amsua
VARBC: Applying bias correction for noaa-18-amsua
VARBC: Applying bias correction for noaa-19-amsua
VARBC: Applying bias correction for metop-2-amsua
VARBC: Estimate Hessian for preconditioning
VARBC:      0 active observations for noaa-15-amsua channel      6
VARBC:      0 active observations for noaa-15-amsua channel      7
VARBC:      0 active observations for noaa-15-amsua channel      8
VARBC:      0 active observations for noaa-18-amsua channel      6
VARBC:      0 active observations for noaa-18-amsua channel      7
VARBC:      0 active observations for noaa-18-amsua channel      8
VARBC: 1074 active observations for noaa-19-amsua channel      6
VARBC: 1019 active observations for noaa-19-amsua channel      7
VARBC:      0 active observations for metop-2-amsua channel      6
VARBC:      0 active observations for metop-2-amsua channel      8
```

rsl.out.0000

Diagnostics		
Final cost function J	=	40665.61
Total number of obs.	=	162763
Final value of J	=	40665.60731
Final value of Jo	=	33961.58347
Final value of Jb	=	2805.68023
Final value of Jc	=	0.00000
Final value of Je	=	3897.27532
Final value of Jp	=	1.06829
Final value of Jl	=	0.00000
Final J / total num_obs	=	0.24985
Jb factor used(1)	=	1.00000
Jb factor used(2)	=	1.00000
Jb factor used(3)	=	1.00000
Jb factor used(4)	=	1.00000
Jb factor used(5)	=	1.00000
Jb factor used	=	2.00000
Je factor used	=	2.00000
VarBC factor used	=	1.00000
Total number of radiances	=	2093
Cost function for radiances	=	782.70972

Writing radiance OMA ascii file

VARBC: Updating bias parameters

VARBC: Writing information in VARBC.out file

*** WRF-Var completed successfully ***

Diagnostics

01_qcstat_noaa-19-amsua

Quality Control Statistics for noaa-19-amsua

num_proc_domain	=	1528									
nrej_mixsurface	=	41									
nrej_windowchanl	=	695									
nrej_si	=	22									
nrej_clw	=	40									
nrej_topo	=	184									
nrej_limb	=	376									
nrej_omb_abs(:)	=										
245	386	37	0	0	0	0	0	0	0	0	0
0	0	11	0	135							
nrej_omb_std(:)	=										
148	301	37	607	542	3	129	476	535	653		
614	403	12	0	17							
nrej(:)	=										
1528	1528	1528	1528	1528	454	509	1528	1528	1528		
1528	1528	1528	1528	1528							
ngood(:)	=										
0	0	0	0	0	1074	1019	0	0	0		
0	0	0	0	0							

Diagnostics

statistics

Diagnostics of OI for radiance noaa-19-amsua

used_nchan: 2					
Channel	num	ave	rms	min	max
6	1074	0.13	0.26	-0.72	0.72
7	1019	0.08	0.37	-0.81	0.81


Diagnostics of AO for radiance noaa-19-amsua

used_nchan: 2					
Channel	num	ave	rms	min	max
6	1074	0.02	0.15	-0.49	0.42
7	1019	0.00	0.29	-0.77	0.79

Radiance output Post-Processing/Visualization

- WRFDA/var/scripts/da_rad_diags.ksh (included in the TOOLS bundle that can be downloaded from <http://www2.mmm.ucar.edu/wrf/users/wrfda/download/tools.html>
 - WRFDA outputs radiance 01_inv* or 01_oma* ASCII files separated for different sensors and CPUs.
 - the script converts ASCII files to one NETCDF file for each sensor (by executing a Fortran90 program), then generates graphics from *.nc files with a NCL script
 - NCL script can plot various graphics
 - Channel TB, Histogram, scatter plot, time series etc.
 - Can be included in the script to routinely produce graphics after WRFDA runs
 - Users can control (by simple script parameter setup) to plot over smaller domain, only over land or sea, QCed or no-QCed observations.

conv_amsua eos-2-amsua_chan-0005



Conclusions

- Radiance data assimilation is important
 - Major source of information over ocean and Southern Hemisphere
- Radiance DA is not trivial
 - Very easy to degrade the analysis!
 - Each sensor requires a lot of attention (observation operator, bias correction, QC, observation error, cloud/rain detection, ...)
 - Challenge for regional DA: lower model top, bias correction
- It's only the beginning...
 - New generation of satellite instruments
 - Future developments will increase satellite impact
 - Better representation of surface emissivity over land
 - Use of cloudy/rainy radiances
 -
- Get familiar with radiance DA with more practice
 - wrfhelp@ucar.edu