



WRF Data Assimilation System: Software and Compilation

Michael Kavulich, Jr.

July 24–July 26, 2017
National Center for Atmospheric Research
Boulder, CO

WRFDA System – Outline


- *Introduction*
- Compiling the code
- WRFDA software structure
- Computing overview

Introduction – What is WRFDA?


- A data assimilation system for the WRF Model (ARW core)
 - 3D- and 4D-VAR, FGAT, Ensemble, and Hybrid methods
- Designed to be flexible, portable and easily installed and modified
 - Open-source and public domain
 - Can be compiled on a variety of platforms
 - Part of the WRF Software Framework
- Designed to handle a wide variety of data
 - Conventional observations
 - Radar velocity and reflectivity
 - Satellite (radiance and derived data)
 - Accumulated precipitation

Introduction – What does WRFDA do?

- WRFDA takes a **first guess** of the atmospheric state, and combines that information with **model/ background error** and **observation** information through one of several assimilation methods and background error options to produce a **best guess** of the atmospheric state at the given time



WRFDA in WRF Modeling System



WRF Model review

- `real.exe` creates `wrfinput_d*` and `wrfbdy_d01`
 - `wrfinput_d01` file contains the 3d-initial condition state for the parent domain
 - `wrfbdy_d01` contains the lateral boundary conditions for the parent domain
 - For multiple domains, you will have `wrfinput_d02`, `wrfinput_d03`, etc., which are the initial conditions for domain 2, domain 3, etc., respectively. Boundary conditions for these files are taken from the parent domains
- `wrf.exe` creates `wrfout_d*` files
 - `wrfout_d###_YYYY_MM_DD:mm:ss` contains one or more 3d forecast states for domain `###` starting at the indicated date/time

WRFDA in WRF Modeling System


- WRFDA takes a single WRF file (either wrfinput* or wrfout*) and creates a single output file (wrfvar_output)
 - This wrfvar_output file is the updated “best guess” of the atmospheric state after data assimilation
 - wrfvar_output is in the same format as wrfinput files, so can be used to initialize a WRF forecast
 - WRFDA can only use wrfout files which have a single time dimension (In WRF namelist: frames_per_outfile=1)
- To perform data assimilation on multiple domains or multiple times, you must run WRFDA multiple times with the appropriate input files

Cycling mode

- Because WRFDA can take WRF forecast files as input, the system can naturally be run in cycling mode
- Output from WRFDA is used to initialize a WRF forecast, the output of which is fed back into WRFDA to initialize another WRF forecast
- Requires boundary condition updating



WRFDA in the WRF Modeling System



The following data are not processed by OBSPROC:

- Radar, Precipitation data in ASCII format (require separate pre-processing)
- Conventional obs in PREPBUFR format
- Radiance, GPSRO in BUFR format

Blue: Supported by WRFDA team

WRFDA System – Outline

- Introduction
- *Compiling the code*
- WRFDA software structure
- Computing overview

Compiling – What is needed?

- WRFDA has similar system requirements to WRF
 - Can be run on a wide variety of UNIX and Linux-based systems
 - Linux/Mac, desktops/laptops, clusters with UNIX-based OS
- WRFDA computational requirements depend on your task
 - Running a small 3DVAR case may take less than 1GB of RAM
 - Large 4DVAR cases may require hundreds of GB
- A supported C and Fortran compiler
 - ifort/icc
 - gfortran/gcc
 - pgf90/pgcc
- Some versions of these compilers have known problems; see <http://www2.mmm.ucar.edu/wrf/users/wrfda/known-problems.html#compilers>

Compiling – What is needed?

- Similar to WRF, there are required and optional libraries
 - netCDF C/fortran libraries are required, and must be downloaded and built by the user
 - <http://www.unidata.ucar.edu/downloads/netcdf/index.jsp>
 - MPI libraries (e.g. MPICH) are required for running WRFDA in parallel
 - BUFR libraries are required for reading PREPBUFR or radiance BUFR files, but they are included in WRFDA and built automatically

Compiling – What is needed?

- Similar to WRF, there are required and optional libraries
 - For radiance assimilation, a radiative transfer model is needed:
 - CRTM, the Community Radiative Transfer Model, is included with the WRFDA source code and built automatically
 - RTTOV is provided by EUMETSAT/NWP SAF, and must be downloaded and built separately
 - WRFDA does not yet support the most recent RTTOV release (v12.1), so you must download version 11 (11.1, 11.2, or 11.3)
 - <https://nwpsaf.eu/site/software/rttov/>
 - AMSR2 radiance files in HDF5 format
 - HDF5 libraries are maintained by The HDF5 Group, and must be downloaded and built separately
 - <https://support.hdfgroup.org/HDF5/>

Compiling – Getting the source code

- Visit the WRFDA download website:
 - http://www2.mmm.ucar.edu/wrf/users/wrfda/download/get_source.html
- Click “New Users” and fill out the registration form, (registration is free), or
- Click “Returning users” and enter your email if you have previously registered to download a WRF product
- Download the latest tar file (Version 3.9)
- Unzip (`gunzip WRFDA_V3.9.tar.gz`) and un-tar (`tar -xvf WRFDA_V3.9.tar`) the code package
- You should see a directory named “WRFDA”; this is the WRFDA source code

WRFDA Directory structure

- `arch`
- `clean`
- `compile`
- `configure`
- `dyn_em`
- `dyn_exp`
- `external`
- `frame`
- `inc`
- `main`
- `Makefile`
- `phys`
- `README.DA` ← *README file with information about WRFDA*
- `README.io_config`
- `Registry` ← *Contains registry.var*
- `run`
- `share`
- `test`
- `tools`
- `var` ← *WRFDA source code directory*

} *build scripts*

Legend:
Blue – directory
Green – script file
Gray – other text file

WRFDA/var Directory structure

<code>build</code>	←	<i>Executables built here</i>
<code>converter</code>		
<code>da</code>	←	<i>WRFDA main source code contained here</i>
<code>external</code>	←	<i>Source code for external libraries (CRTM, BUFR, etc.)</i>
<code>gen_be</code>	←	<i>GEN_BE source code</i>
<code>graphics</code>		
<code>Makefile</code>		
<code>obsproc</code>	←	<i>OBSPROC source code</i>
<code>README.basics</code>	}	<i>More README files with useful information</i>
<code>README.namelist</code>		
<code>README.radiance</code>		
<code>run</code>	←	<i>Useful runtime files (mostly for radiance)</i>
<code>scripts</code>		
<code>test</code>	←	<i>Data for tutorial cases</i>

Legend:

Blue – directory

Green – script file

Gray – other text file

WRFDA/var/da Directory structure

Main WRFDA Program (driver):

da_main

WRFDA Subroutines (mediation layer)

da_4dvar
da_control
da_etkf
da_define_structures
da_dynamics
da_grid_definitions
da_interpolation
da_minimisation
da_physics
da_setup_structures
da_varbc
da_vtox_transforms

Observation Types

da_airep	da_pseudo
da_airsr	da_qscat
da_bogus	da_radar
da_buoy	da_radiance
da_geoamv	da_rain
da_gpssp	da_satem
da_gpsref	da_ships
da_metar	da_sound
da_mtgirs	da_ssmi
da_pilot	da_synop
da_polaramv	da_tamdar
da_profiler	

Compiling – Preparing the environment

- As mentioned before, some libraries are required for WRFDA, and some are optional depending what you are using WRFDA for
 - netCDF is required; you should set an environment variable to specify where the netCDF libraries are built on your system:
 - `setenv NETCDF full_path_for_NETCDF`
- If you plan on doing radiance assimilation, you will need CRTM or RTTOV. WRFDA can be built with either or both
 - The CRTM source code is included in the WRFDA package, and will be built automatically
 - To use RTTOV, set an environment variable specifying where RTTOV is built on your system:
 - `setenv RTTOV full_path_for_RTTOV`

Compiling – Preparing the environment

- If you plan on assimilating AMSR2 data, you will need to link to the HDF5 libraries
 - Set an environment variable specifying where HDF5 is built on your system:
 - `setenv HDF5 full_path_for_HDF5`
- To build the code faster, if your computer has the gnu make utility, you can set the environment variable J to build the code in parallel
 - `setenv J "-j 4"` (will build on 4 processors)
 - Note that this is different from compiling the code to *run* in parallel

Compiling – Building the WRFDA code

- Two scripts must be run to build the code:
- `configure` asks for some information about your machine and how you want to build the code, and generates a `configure.wrf` file
- `./configure wrfda`

```
> ./configure wrfda
checking for perl5... no
checking for perl... found /usr/bin/perl (perl)
Will use NETCDF in dir: /usr/local/netcdf-3.6.3-gfortran
Will use HDF5 in dir: /usr/local/hdf5-1.8.15-gcc
PHDF5 not set in environment. Will configure WRF for use without.
Will use 'time' to report timing information
$JASPERLIB or $JASPERINC not found in environment, configuring to build without grib2 I/O...
-----
Please select from among the following Linux x86_64 options:

1. (serial)    2. (smpar)    3. (dmpar)    4. (dm+sm)    PGI (pgf90/gcc)
5. (serial)    6. (smpar)    7. (dmpar)    8. (dm+sm)    PGI (pgf90/pgcc): SGI MPT
9. (serial)   10. (smpar)   11. (dmpar)   12. (dm+sm)   PGI (pgf90/gcc): PGI accelerator
13. (serial)  14. (smpar)  15. (dmpar)  16. (dm+sm)  INTEL (ifort/icc)
... ..
```

- Select the option that is best for your purposes

Compiling – Building the WRFDA code

- Two scripts must be run to build the code:
- `compile` compiles all the code for the settings you specified

```
./compile all_wrfvar >& compile.wrfda.log
```
- Depending on your machine and what options you have selected, compilation can take less than 5 minutes up to an hour. For example, `gfortran` usually compiles WRFDA quite quickly, while `intel` compilers typically take longer to build (but the executables may run faster)

Compiling – review compiled code

- When the compilation script is completed, you should see the message “build completed:” followed by the date and time.
- **The script does not automatically check to make sure all executables were successfully built; you will need to check manually**
- There should be 44 executables built all together: 43 in the WRFDA/var/build directory, and WRFDA/var/obsproc/obsproc.exe
- In all likelihood, you will not use most of these directly: the majority of them are called by scripts for various tools such as GEN_BE and diagnostic packages


Compiling – review executables

- These are the executables you will most likely be using:
- `da_wrfvar.exe`
 - The main WRFDA executable: this program will perform the actual data assimilation and output a WRF-formatted `wrfvar_output` file
- `obsproc.exe`
 - The executable for OBSPROC, the observation pre-processor for text-based observation formats
- `da_update_bc.exe`
 - The executable for UPDATE_BC; used for updating boundary conditions after assimilation and during cycling runs

WRFDA System – Outline

- Introduction
- Compiling the code
- *WRFDA software structure*
- Computing overview


WRFDA Software – Architecture



Registry.wrfvar

- **Hierarchical** software architecture
 - **Insulate** scientists' code from parallelism and other architecture/implementation-specific details
 - Well-defined **interfaces** between layers, and **external packages** for communications, I/O.

WRFDA Software – Architecture



- **Registry**: an “Active” data dictionary
 - Tabular listing of model state and attributes
 - Large sections of interface code generated automatically
 - Scientists manipulate model state simply by modifying Registry, without further knowledge of code mechanics
 - **registry.var** is the main dictionary for WRFDA
 - registry.var is combined at compile time with Registry.EM_COMMON.var and others to produce **Registry.wrfvar**, which contains all of the registry definitions used by WRFDA

WRFDA Software – Architecture

registry.var

Variable
size

Variable
type


Variable
name

Namelist
name

Default
value


Variable type	Variable name	Namelist name	Variable size	Default value			
rconfig	integer	rttov_emis_atlas_ir	namelist,wrfvar14	1 0	-	"rttov_emis_atlas_ir"	"" ""
rconfig	integer	rttov_emis_atlas_mw	namelist,wrfvar14	1 0	-	"rttov_emis_atlas_mw"	"" ""
rconfig	integer	rtminit_print	namelist,wrfvar14	1 1	-	"rtminit_print"	"" ""
rconfig	integer	rtminit_nsensor	namelist,wrfvar14	1 1	-	"rtminit_nsensor"	"" ""
rconfig	integer	rtminit_platform	namelist,wrfvar14	max_instruments -1	-	"rtminit_platform"	"" ""
rconfig	integer	rtminit_satid	namelist,wrfvar14	max_instruments -1.0	-	"rtminit_satid"	"" ""
rconfig	integer	rtminit_sensor	namelist,wrfvar14	max_instruments -1.0	-	"rtminit_sensor"	"" ""
rconfig	integer	rad_monitoring	namelist,wrfvar14	max_instruments 0	-	"rad_monitoring"	"" ""
rconfig	real	thinning_mesh	namelist,wrfvar14	max_instruments 60.0	-	"thinning_mesh"	"" ""
rconfig	logical	thinning	namelist,wrfvar14	1 .true.	-	"thinning "	"" ""
rconfig	logical	read_biascoef	namelist,wrfvar14	1 .false.	-	"read_biascoef"	"" ""
rconfig	logical	biascorr	namelist,wrfvar14	1 .false.	-	"biascorr"	"" ""
rconfig	logical	biasprep	namelist,wrfvar14	1 .false.	-	"biasprep"	"" ""
rconfig	logical	rttov_scatt	namelist,wrfvar14	1 .false.	-	"rttov_scatt"	"" ""
rconfig	logical	write_profile	namelist,wrfvar14	1 .false.	-	"write_profile"	"" ""
rconfig	logical	write_jacobian	namelist,wrfvar14	1 .false.	-	"write_jacobian"	"" ""
rconfig	logical	qc_rad	namelist,wrfvar14	1 .true.	-	"qc_rad"	"" ""
rconfig	logical	write_iv_rad_ascii	namelist,wrfvar14	1 .false.	-	"write_iv_rad_ascii"	"" ""
rconfig	logical	write_oa_rad_ascii	namelist,wrfvar14	1 .false.	-	"write_oa_rad_ascii"	"" ""
rconfig	logical	write_filtered_rad	namelist,wrfvar14	1 .false.	-	"write_filtered_rad"	"" ""
rconfig	logical	use_error_factor_rad	namelist,wrfvar14	1 .false.	-	"use_error_factor_rad"	"" ""
rconfig	logical	use_landem	namelist,wrfvar14	1 .false.	-	"use_landem"	"" ""
rconfig	logical	use_antcorr	namelist,wrfvar14	max_instruments .false.	-	"use_antcorr"	"" ""
rconfig	logical	use_mspps_emis	namelist,wrfvar14	max_instruments .false.	-	"use_mspps_emis"	"" ""
rconfig	logical	use_mspps_ts	namelist,wrfvar14	max_instruments .false.	-	"use_mspps_ts"	"" ""

WRFDA Software – Architecture




- **Driver** Layer
 - **Domains:** Allocates, stores, decomposes, represents abstractly as *single data objects*

WRFDA Software – Architecture



- **Minimization/Solver Layer**
 - **Minimization/Solver** routine, choose the function based on the namelist variable, 3DVAR, 4DVAR, FSO or Verification, and choose the **minimization algorithm**.


WRFDA Software – Architecture



- **Observation Layer**
 - **Observation interfaces**: contains the gradient and cost function calculation subroutines for each type of observations.

Call Structure Superimposed on Architecture

da_sound.f90 (da_sound)




WRFDA System – Outline

- Introduction
- Compiling the code
- WRFDA software overview
- *Computing overview*

WRFDA Parallelism

- WRFDA can be run **serially** or as a **parallel** job
- WRFDA uses **domain decomposition** to divide total amount of work over parallel processes
- The **decomposition** of the application over processes has **two levels**:
 - The **domain** is broken up into rectangular pieces that are assigned to **MPI** (distributed memory) processes. These pieces are called **patches**
 - The **patches** may be further subdivided into smaller rectangular pieces that are called **tiles**, and these are assigned to **shared-memory threads** within the process.
- *However, WRFDA does not support shared memory parallelism! So distributed memory is what I will cover here.*

Parallelism in WRFDA: Multi-level Decomposition



Inter-processor
communication

Distributed Memory Communications

When Needed?

Communication is required between patches when a horizontal index is incremented or decremented on the right-hand-side of an assignment.

Why?

On a patch boundary, the index may refer to a value that is on a different patch.

Following is an example code fragment that requires communication between patches

Signs in code

Note the tell-tale **+1** and **-1** expressions in indices for `rr`, `H1`, and `H2` arrays on right-hand side of assignment.

These are *horizontal data dependencies* because the indexed operands may lie in the patch of a neighboring processor. That neighbor's updates to that element of the array won't be seen on this processor.

Distributed Memory Communications

(da_transfer_xatowrf.inc)

```
subroutine da_transfer_xatowrf(grid)
```

```
. . .
```

```
do k=kts,kte
```

```
do j=jts,jte+1
```

```
do i=its,ite+1
```

```
u_cgrid(i,j,k)=0.5*(grid%xa%u(i-1,j ,k)+grid%xa%u(i,j,k))
```



```
v_cgrid(i,j,k)=0.5*(grid%xa%v(i ,j-1,k)+grid%xa%v(i,j,k))
```

```
end do
```


```
end do
```

```
end do
```

```
. . .
```




Distributed Memory Communications



Halo (contains information about adjacent patch)

Distributed Memory Communications



Halo (contains information about adjacent patch)

Inter-processor communication
(Halos update from adjacent patch after each minimization step)

Grid Representation in Arrays

- Increasing indices in WRFDA arrays run
 - West to East (X, or I-dimension)
 - South to North (Y, or J-dimension)
 - Bottom to Top (Z, or K-dimension)
- Storage order in **WRFDA** is **IJK** , but for WRF, it is **IKJ** (**ARW**) and **IJK** (**NMM**)
- Output data has grid ordering independent of the ordering inside the WRFDA model

Grid Representation in Arrays

- The extent of the logical or *domain* dimensions is always the "staggered" grid dimension. That is, from the point of view of a non-staggered dimension (also referred to as the ARW "mass points"), there is always an extra cell on the end of the domain dimension
- In WRFDA, the minimization is on A-grid (non-staggered grid). The wind components will be interpolated from A-grid to C-grid (staggered grid) before they are output, to conform with standard WRF format

Summary

- WRFDA
 - is designed to be an easy-to-use data assimilation system for use with the WRF model
 - is designed within the WRF Software Framework for rapid development and ease of modification
 - is compiled in much the same way as WRF
 - can be run in parallel for quick assimilation of large amounts of data on large domains

Appendix – WRFDA Resources

- WRFDA users page
 - <http://www2.mmm.ucar.edu/wrf/users/wrfda>
 - Download WRFDA source code, test data, related packages and documentation
 - Lists WRFDA news and developments
- Online documentation
 - http://www2.mmm.ucar.edu/wrf/users/docs/user_guide_V3/users_guide_chap6.htm
 - Chapter 6 of the WRF Users' Guide; documents installation of WRFDA and running of various WRFDA methods
 - Online Tutorial, several helpful pages:
 - <http://www2.mmm.ucar.edu/wrf/users/wrfda/OnlineTutorial/>
- WRFDA user services and help desk
 - wrfhelp@ucar.edu

Appendix – WRFDA History

- Developed from MM5 3DVar beginning around 2002, first version (2.0) released December 2003
- 4DVAR capability added in 2008, made practical with parallelism starting with Version 3.4 (April 2012)
- Developed and supported by WRFDA group of the Mesoscale and Microscale Meteorology Lab of NCAR
- Requirements emphasize flexibility over a range of platforms, applications, users, performance
- Current release WRFDA v3.9 (April 2017)
- Shares the WRF Software Framework